

# **Adaptive Sparse Grids**

Seminar: High Dimensional Methods in Scientific Computing

Muhammed Kürşat Yurt

July 7, 2022



### **Outline**

- Introduction
- 2 A deeper look to Sparse Grids
- 3 Adaptivity on Sparse Grids
- 4 Sparse Grid in Action: Interpolation



What is a sparse grid?

A **numerical discretization technique** that can be used in a wide range of computatitonal problems:

Interpolation



What is a sparse grid?

- Interpolation
- Regression



What is a sparse grid?

- Interpolation
- Regression
- Classification



What is a sparse grid?

- Interpolation
- Regression
- Classification
- Density estimation



What is a sparse grid?

- Interpolation
- Regression
- Classification
- Density estimation
- Quadrature



What is a sparse grid?

- Interpolation
- Regression
- Classification
- Density estimation
- Quadrature
- Uncertainty Quantification



What is a sparse grid?

- Interpolation
- Regression
- Classification
- Density estimation
- Quadrature
- Uncertainty Quantification
- Solution of Partial Differential Equations



What is a sparse grid?

- Interpolation
- Regression
- Classification
- Density estimation
- Quadrature
- Uncertainty Quantification
- Solution of Partial Differential Equations
- . . .



Why do we need sparse grids?

In general solution on a *full grid* (i.e. a grid with all points) is only feasible if the dimensionality of the problem is low (d = 1, 2, 3)



Why do we need sparse grids?

In general solution on a *full grid* (i.e. a grid with all points) is only feasible if the dimensionality of the problem is low (d = 1, 2, 3)

However, in some cases, the dimensionality of the problem is high ( $d \ge 4$ ) and the solution on a *full grid* is not feasible.



Why do we need sparse grids?

In general solution on a *full grid* (i.e. a grid with all points) is only feasible if the dimensionality of the problem is low (d = 1, 2, 3)

However, in some cases, the dimensionality of the problem is high ( $d \ge 4$ ) and the solution on a *full grid* is not feasible.

This dilemma is called *curse of dimensionality* and is the reason why sparse grids are used in many scientific applications.



#### A brief comparision

The required grid points and the Euclidian norm of the interpolation error on a regular sparse grid and on a full grid is shown in the following table below for d dimensional space and grid level of n.

	Number of grid points	LZ Norm of interpolation End
Full Grid	O(2 <sup>nd</sup> )	$O(2^{-2n})$
Sparse Grid	$O(2^n n^{d-1})$	$O(2^{-2n}n^{d-1})$


Number of grid points 1.2 Norm of Interpolation Error



#### A brief comparision


The required grid points and the Euclidian norm of the interpolation error on a regular sparse grid and on a full grid is shown in the following table below for d dimensional space and grid level of n.

	Number of grid points	L2 Norm of Interpolation Error
Full Grid	$O(2^{nd})$	$O(2^{-2n})$
Sparse Grid	$O(2^n n^{d-1})$	$O(2^{-2n}n^{d-1})$







How they look?





How they look?







Requirements for a sparse grid

A scalar valued function f which maps some input parameter  $\mathbf{x}$  to a scalar value  $f(\mathbf{x})$ .



Requirements for a sparse grid

- A scalar valued function f which maps some input parameter  $\mathbf{x}$  to a scalar value  $f(\mathbf{x})$ .
- f is defined on a unit hyper-cube  $[0, 1]^d$ . Any input  $x_i$  should be transformed to [0, 1] easily.



Requirements for a sparse grid

- A scalar valued function f which maps some input parameter  $\mathbf{x}$  to a scalar value  $f(\mathbf{x})$ .
- f is defined on a unit hyper-cube  $[0, 1]^d$ . Any input  $x_i$  should be transformed to [0, 1] easily.
- f can be computable in any point in hyper-cube.



Requirements for a sparse grid

- A scalar valued function f which maps some input parameter  $\mathbf{x}$  to a scalar value  $f(\mathbf{x})$ .
- f is defined on a unit hyper-cube  $[0, 1]^d$ . Any input  $x_i$  should be transformed to [0, 1] easily.
- f can be computable in any point in hyper-cube.
- It is assumed that the function is computatinally expensive. So that we need to change f with another function which is cheaper and approximate original function well.



#### **Hierachical Basis Functions**

Using a standard hat function as a basis function, we can construct a sparse grid.

$$\phi(x) = \begin{cases} 1 - |x| & \text{if } x \in [-1, 1], \\ 0 & \text{otherwise} \end{cases}$$



Figure: Nodal Basis Functions




Figure: Hierarchical Basis Functions



Tensorial product and construction on d-dimensional space




Figure: Construction of the regular sparse grid of level in 2D, by Julian Valentin



Types of Adaptivity

A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.



- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.



- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.



- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.
- Adaptation criteria play an important role.



- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.
- Adaptation criteria play an important role.



#### Types of Adaptivity

- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.
- Adaptation criteria play an important role.

#### **Dimensional Adaptivity**

Can be used when f has a different characteristic in different dimensions.



#### Types of Adaptivity

- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.
- Adaptation criteria play an important role.

### **Dimensional Adaptivity**

Can be used when f has a different characteristic in different dimensions.



#### Types of Adaptivity

- A regular sparse grid is constructed in a way that takes a cut in diagonal hyperplane.
- All the dimensions and regions are assumed to be equally important.
- Adaptivity provides a smaller error with the same number of grid points.
- Adaptation criteria play an important role.

#### **Dimensional Adaptivity**

Can be used when f has a different characteristic in different dimensions.

#### **Spatial Adaptivity**

Can be used when f has a different characteristic in specific regions



Spatial Adaptivity

Consider a function f such that it is mostly flat expect a region in the domain.



Spatial Adaptivity

Consider a function f such that it is mostly flat expect a region in the domain. Let say the region is near (0.4, 0.6).



Spatial Adaptivity

Consider a function *f* such that it is mostly flat expect a region in the domain.

Let say the region is near (0.4, 0.6).

A regular or dimensionally adaptive sparse grid would require many points to capture the local behaviour of f near (0.4, 0.6).



Spatial Adaptivity

Consider a function *f* such that it is mostly flat expect a region in the domain.

Let say the region is near (0.4, 0.6).

A regular or dimensionally adaptive sparse grid would require many points to capture the local behaviour of f near (0.4, 0.6).

The point where f is mostly flat are wasted.



Spatial Adaptivity

Consider a function *f* such that it is mostly flat expect a region in the domain.

Let say the region is near (0.4, 0.6).

A regular or dimensionally adaptive sparse grid would require many points to capture the local behaviour of f near (0.4, 0.6).

The point where *f* is mostly flat are wasted.

Spatial adaptivity allows to use more grid points locally.



#### Adaptivity Criterion




Figure: Interpolation of a parabola using 2 level hierarchical basis and surpluses, surpluses are shown in red lines.

 One of the popular criterion is so called surplus-based criterion.



#### Adaptivity Criterion




Figure: Interpolation of a parabola using 2 level hierarchical basis and surpluses, surpluses are shown in red lines.

- One of the popular criterion is so called surplus-based criterion.
- It uses the absolute values of of hierarchical surpluses  $\alpha$ , to estimate second derivative of the function f. In general, a larger absolute surplus means a larger second derivative.



#### Adaptivity Criterion




Figure: Interpolation of a parabola using 2 level hierarchical basis and surpluses, surpluses are shown in red lines.

- One of the popular criterion is so called surplus-based criterion.
- It uses the absolute values of of hierarchical surpluses α, to estimate second derivative of the function f. In general, a larger absolute surplus means a larger second derivative.
- More grid points are inserted to vicinity of larger surplus values.



Spatial Adaptivity Requirements

The requirements for spatial adaptivity can be listed as follows:

An initial coarse grid.



Spatial Adaptivity Requirements

- An initial coarse grid.
- Iteratively choose region of interests.



Spatial Adaptivity Requirements

- An initial coarse grid.
- Iteratively choose region of interests.
- Add new points to region of interests.



Spatial Adaptivity Requirements

- An initial coarse grid.
- Iteratively choose region of interests.
- Add new points to region of interests.
- The grid should contain all the hierarchical ancestors of all grid points.




Spatial Adaptivity Requirements

- An initial coarse grid.
- Iteratively choose region of interests.
- Add new points to region of interests.
- The grid should contain all the hierarchical ancestors of all grid points.
- Due to the consistency constraint, the number of points added can be larger than  $2 \cdot d$ .



#### Spatial Adaptivity in Action






Figure: Level 3 Regular grid before adaptation.

Figure: Level 3 Regular grid after adaptation.



#### Franke's Function




Figure: Calculated surface of Franke's function




Figure: Interpolated surface of Franke's function



#### Franke's Function




Figure: The final sparse grid with 570 grid points.




Figure: Error reduction plot of Franke's function w.r.t. refinement steps.



Genz Test Functions: Product Peak




Figure: Calculated surface of Product Peak function




Figure: Interpolated surface of Product Peak function



#### Genz Test Functions: Product Peak




Figure: The final sparse grid with 570 grid points.




Figure: Error reduction plot of Product Peak function w.r.t. refinement steps.



Genz Test Functions: Discontinuous




Figure: Calculated surface of Discontinuous function




Figure: Interpolated surface of Discontinuous function



#### Genz Test Functions: Discontinuous




Figure: The final sparse grid with 570 grid points.




Figure: Error reduction plot of Discontinuous function w.r.t. refinement steps.



# Thank you for your attention!