

Lab 5

Kurt Delegard

PHYS 434 AB

Time spent drafting: 7 hours

Time spent revising: 3 hours

Total time spent: 10+ hours

```
clear;
clc;

h5disp("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5");
```

```
HDF5 heradata.uvh5
Group '/'
  Group '/Data'
    Dataset 'flags'
      Size: 4x1024x1x82680
      MaxSize: 4x1024x1x82680
      Datatype: H5T_ENUM
        Base Type: H5T_STD_I8LE
        Member 'FALSE': 0
        Member 'TRUE': 1
      ChunkSize: 1x32x1x2584
      Filters: unrecognized filter (lzf)
    Dataset 'nsamples'
      Size: 4x1024x1x82680
      MaxSize: 4x1024x1x82680
      Datatype: H5T_IEEE_F32LE (single)
      ChunkSize: 1x32x1x1292
      Filters: unrecognized filter (lzf)
    Dataset 'visdata'
      Size: 4x1024x1x82680
      MaxSize: 4x1024x1x82680
      Datatype: H5T_COMPOUND
        Member 'r': H5T_IEEE_F64LE (double)
        Member 'i': H5T_IEEE_F64LE (double)
      ChunkSize: 1x16x1x646
      Filters: none
  Group '/Header'
    Dataset 'Nants_data'
      Size: scalar
      Datatype: H5T_STD_I64LE (int64)
      ChunkSize: []
      Filters: none
      FillValue: 0
    Dataset 'Nants_telescope'
      Size: scalar
      Datatype: H5T_STD_I64LE (int64)
      ChunkSize: []
      Filters: none
      FillValue: 0
    Dataset 'Nb1s'
      Size: scalar
      Datatype: H5T_STD_I64LE (int64)
      ChunkSize: []
```

```

    Filters: none
    FillValue: 0
Dataset 'Nblts'
    Size: scalar
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'Nfreqs'
    Size: scalar
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'Npols'
    Size: scalar
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'Nspws'
    Size: scalar
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'Ntimes'
    Size: scalar
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'altitude'
    Size: scalar
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'ant_1_array'
    Size: 82680
    MaxSize: 82680
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'ant_2_array'
    Size: 82680
    MaxSize: 82680
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'antenna_diameters'
    Size: 52
    MaxSize: 52
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'antenna_names'
    Size: 52
    MaxSize: 52
    Datatype: H5T_STRING
    String Length: 5
    Padding: H5T_STR_NULLPAD

```

```

        Character Set: H5T_CSET_ASCII
        Character Type: H5T_C_S1
    ChunkSize: []
    Filters: none
    FillValue: ' '
Dataset 'antenna_numbers'
    Size: 52
    MaxSize: 52
    Datatype: H5T_STD_I64LE (int64)
    ChunkSize: []
    Filters: none
    FillValue: 0
Dataset 'antenna_positions'
    Size: 3x52
    MaxSize: 3x52
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'channel_width'
    Size: scalar
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'freq_array'
    Size: 1024x1
    MaxSize: 1024x1
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'history'
    Size: scalar
    Datatype: H5T_STRING
        String Length: 934
        Padding: H5T_STR_NULLPAD
        Character Set: H5T_CSET_ASCII
        Character Type: H5T_C_S1
    ChunkSize: []
    Filters: none
    FillValue: ' '
Dataset 'instrument'
    Size: scalar
    Datatype: H5T_STRING
        String Length: 4
        Padding: H5T_STR_NULLPAD
        Character Set: H5T_CSET_ASCII
        Character Type: H5T_C_S1
    ChunkSize: []
    Filters: none
    FillValue: ' '
Dataset 'integration_time'
    Size: 82680
    MaxSize: 82680
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000
Dataset 'latitude'
    Size: scalar
    Datatype: H5T_IEEE_F64LE (double)
    ChunkSize: []
    Filters: none
    FillValue: 0.000000

```

```

Dataset 'longitude'
  Size: scalar
  Datatype:  H5T_IEEE_F64LE (double)
  ChunkSize: []
  Filters: none
  FillValue: 0.000000
Dataset 'lst_array'
  Size: 82680
  MaxSize: 82680
  Datatype:  H5T_IEEE_F64LE (double)
  ChunkSize: []
  Filters: none
  FillValue: 0.000000
Dataset 'object_name'
  Size: scalar
  Datatype:  H5T_STRING
    String Length: 6
    Padding: H5T_STR_NULLPAD
    Character Set: H5T_CSET_ASCII
    Character Type: H5T_C_S1
  ChunkSize: []
  Filters: none
  FillValue: ' '
Dataset 'phase_type'
  Size: scalar
  Datatype:  H5T_STRING
    String Length: 5
    Padding: H5T_STR_NULLPAD
    Character Set: H5T_CSET_ASCII
    Character Type: H5T_C_S1
  ChunkSize: []
  Filters: none
  FillValue: ' '
Dataset 'polarization_array'
  Size: 4
  MaxSize: 4
  Datatype:  H5T_STD_I64LE (int64)
  ChunkSize: []
  Filters: none
  FillValue: 0
Dataset 'spw_array'
  Size: 1
  MaxSize: 1
  Datatype:  H5T_STD_I64LE (int64)
  ChunkSize: []
  Filters: none
  FillValue: 0
Dataset 'telescope_name'
  Size: scalar
  Datatype:  H5T_STRING
    String Length: 4
    Padding: H5T_STR_NULLPAD
    Character Set: H5T_CSET_ASCII
    Character Type: H5T_C_S1
  ChunkSize: []
  Filters: none
  FillValue: ' '
Dataset 'time_array'
  Size: 82680
  MaxSize: 82680
  Datatype:  H5T_IEEE_F64LE (double)
  ChunkSize: []
  Filters: none
  FillValue: 0.000000
Dataset 'uvw_array'

```

```

Size: 3x82680
MaxSize: 3x82680
Datatype: H5T_IEEE_F64LE (double)
ChunkSize: []
Filters: none
FillValue: 0.000000
Dataset 'vis_units'
Size: scalar
Datatype: H5T_STRING
String Length: 7
Padding: H5T_STR_NULLPAD
Character Set: H5T_CSET_ASCII
Character Type: H5T_C_S1
ChunkSize: []
Filters: none
FillValue: ' '
Group '/Header/extra_keywords'
Dataset 'cminfo'
Size: scalar
Datatype: H5T_STRING
String Length: 7788
Padding: H5T_STR_NULLPAD
Character Set: H5T_CSET_ASCII
Character Type: H5T_C_S1
ChunkSize: []
Filters: none
FillValue: ' '
Dataset 'cmver'
Size: scalar
Datatype: H5T_STRING
String Length: 40
Padding: H5T_STR_NULLPAD
Character Set: H5T_CSET_ASCII
Character Type: H5T_C_S1
ChunkSize: []
Filters: none
FillValue: ' '
Dataset 'duration'
Size: scalar
Datatype: H5T_IEEE_F64LE (double)
ChunkSize: []
Filters: none
FillValue: 0.000000
Dataset 'obsid'
Size: scalar
Datatype: H5T_STD_I64LE (int64)
ChunkSize: []
Filters: none
FillValue: 0
Dataset 'st_type'
Size: scalar
Datatype: H5T_STRING
String Length: 468
Padding: H5T_STR_NULLPAD
Character Set: H5T_CSET_ASCII
Character Type: H5T_C_S1
ChunkSize: []
Filters: none
FillValue: ' '
Dataset 'startt'
Size: scalar
Datatype: H5T_IEEE_F64LE (double)
ChunkSize: []
Filters: none
FillValue: 0.000000

```

```

Dataset 'stopt'
  Size: scalar
  Datatype: H5T_IEEE_F64LE (double)
  ChunkSize: []
  Filters: none
  FillValue: 0.000000

```

```

%data from baseline #1
visdata1 = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Data/visdata", [1 1]);

fs = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/freq_array");
Ntimes = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/Ntimes");
Nb1s = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/Nb1s");
%data from all baselines for time #1
visdata_all1 = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Data/visdata", [1 1]);

%data from baselines #1 and #2 for time #1
visdata_12 = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Data/visdata", [1 1]);

%data from baseline #2 at 10 time intervals
visdata2_time = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Data/visdata", [1 1]);

times = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/time_array");
ants_wdata = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/Nants_data");
ants = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/Nants_telescope");
ant_nums = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/antenna_numbers");
antind1 = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/ant_1_array");
antind2 = h5read("C:\Users\hsp_x\Desktop\PHYS_434\Lab 5\heradata.uvh5", "/Header/ant_2_array");
baselines = [antind1(1:Nb1s), antind2(1:Nb1s)];

```

Here we have data from the Hydrogen Epoch of Reionization Array ([HERA](#)) project. The goal of this project is to observe structure in the Universe before and during the epoch of ionization of hydrogen. In other words, the project aims to find the structure of the Universe as the first luminous objects (stars, black holes) "lit up" and reionized the intergalactic medium.

The data file above contains several forms of relevant data and metadata to this project. Data from each antenna is sent into a supercomputer called a **correlator**, which correlates the data from two antennas together. Each antenna pair is called a **baseline**. Since the data from every antenna is correlated with data from every other telescope, up to N_{ants}^2 baseline pairs will contribute to the data collection process.

```
ants
```

```
ants = int64
      52
```

```
ants.^2
```

```
ans = int64
     2704
```

Since we have data from up to 52 antennas, we should have data from up to 2704 baseline pairs.

One of the important parts of data we will be working with is the [visibility](#), which is a measure of the response of a particular baseline to incoming radiation. From the data preview above, we can see that 'visdata' is an array with dimensions 4x1024x1x82680. These correspond to:

- 4 different polarizations of light (XX, YY, XY, YX). For the following data, we will be working with XX polarization.
- 1024 different frequencies between 100 and 200 Mhz
- 1 spectral window (This data is irrelevant to our analysis)
- 82680 = (baseline pairs * times). This axis can be thought of as a column vector of data from every baseline pair for time t=1, vertically concatenated with a column vector of data from every baseline pair for time t=2, 3, 4.... etc. Note: time is given in units of Julian days, as demonstrated [here](#).

```
%Number of time intervals * number of baselines:  
Ntimes .* Nbls
```

```
ans = int64  
      82680
```


We are given a complex value of visibility for each entry in this matrix. We would like to observe how the visibility depends on the frequency of the incoming radiation. Let us begin by looking at the data from the first baseline pair:

```
baselines(1,:)
```

```
ans = 1x2 int64 row vector  
      0      0
```


This baseline actually corresponds to data from the first antenna (antenna #0) correlated with itself. We can plot the amplitude of the complex visibility vs. the frequency of the incoming radiation:

```
visim1 = visdat2img(visdata1, 1:1024);  
amplitude1 = squeeze(sum(visim1, 1));  
  
clf;  
t = tiledlayout(1, 2);  
nexttile  
plot(fs ./ 1e6, amplitude1(1:1024))  
ylabel('Visibility amplitude')  
xlabel('Frequency (MHz)')  
nexttile;  
semilogy(fs ./ 1e6, amplitude1(1:1024))  
title(t, 'Visibility vs. frequency for baseline (0, 0)')  
ylabel('Visibility amplitude (log scale)')  
xlabel('Frequency (MHz)')  
set(gcf, 'Units', 'Normalized', 'OuterPosition', [0, 0, 1, 0.9]);
```



We can also plot this as an image where the brightness corresponds to the amplitude of the complex visibility, and the x-axis corresponds to the frequency. This representation will become more useful once we plot more baselines.


```
clf;
imagesc(visim1);
xt = get(gca, 'XTick');
set(gca, 'XTick', xt, 'XTickLabel', round(xt/10.24 + 100));
xlabel('Frequency (MHz)');
set(gca, 'yticklabel', [])
c = colorbar;
c.Label.String = "Visibility amplitude";
title('Baseline 1 (0, 0) at time 1');
```

There are clearly some frequencies which correspond to very high values of visibility, shown by the bright vertical lines at around 106 and 137 MHz on both figures. However, there are also some hazy areas denoted by the light blue color which may correspond to background.

We can compare the data from baseline 1 with the data from the next baseline by stacking the plots for each baseline like so:


```
clf;
vismag_im_12 = visdat2img(visdata_12, 1:1024);
imagesc(vismag_im_12');
xt = get(gca, 'XTick');
set(gca, 'XTick', xt, 'XTickLabel', round(xt/10.24 + 100));
xlabel('Frequency (MHz)');
yticks([1 2])
ylabel('Baseline')
c = colorbar;
c.Label.String = "Visibility amplitude";
title('Baselines #1 and #2 at time 1')
```



While the bright signals at ~106 and ~137 MHz are apparent in both figures, only the top figure contains the hazy blue background.


Let's observe any patterns that arise from plotting data from all baselines for time $t=1$:

```
vismag_im_all1 = visdat2img(visdata_all1, 1:1024);
amplitude_all1 = squeeze(sum(vismag_im_all1', 1));
amplitude1 = squeeze(sum(visim1, 1));
clf;
semilogy(fs ./ 1e6, amplitude_all1(1:1024)), hold on;
semilogy(fs ./ 1e6, amplitude1(1:1024))
xlabel('Frequency (MHz)');
ylabel('Amplitude (Log scale)')
title('Amplitude vs. frequency for all baselines at time 1')
legend('All baselines', '1 baseline')
```



While the overall background is much larger for the sum of all baselines, the signal-to-noise ratio (height of the spikes relative to the background) has improved immensely. Stacking the images from each baseline on top of one another, as before:

```
clf;
imagesc(vismag_im_all1');
xt = get(gca, 'XTick');
set(gca, 'XTick', xt, 'XTickLabel', round(xt/10.24 + 100));
xlabel('Frequency (MHz)');
ylabel('Baseline')
c = colorbar;
c.Label.String = "Visibility amplitude";
title('All baselines at time t=1')
```




The background in this image is clearly reduced compared to the first two images; the hazy blue background is gone. However, in its place are these thin blue streaks, which correspond to individual baselines with the anomalous background. Since the first baseline corresponding to (0, 0) exhibited this unusual background, we might assume that this is a phenomena that occurs when the correlator combines data from the same antenna. Let us call these baselines (n,n) pairs to denote that data from an antenna is being correlated with itself. We can see if removing these data points will improve the data quality:

```
commonpair_indices = baselines(:, 1) == baselines(:, 2);
common_pairs = baselines(commonpair_indices, :)'
```

```
common_pairs = 2x52 int64 matrix
    0    1    2   11   12   13   14   23   24   25   26   27   36 ...
    0    1    2   11   12   13   14   23   24   25   26   27   36
```

```
clean_img = vismag_im_all1(:, ~commonpair_indices);


clf;
imagesc(clean_img')
xt = get(gca, 'XTick');
set(gca, 'XTick', xt, 'XTickLabel', round(xt/10.24 + 100));
xlabel('Frequency (MHz)');
ylabel('Baseline')
c = colorbar;
c.Label.String = "Visibility amplitude";
title('All baselines at time t=1 (Cleaned)')
```



It seems like we were successful in removing the signal contamination from the data. However, the exact process from which this anomalous background occurs is unknown at this point.

Finally, we can plot the data we have worked with so far on the same set of axes to see how our noise is reduced:

```
clean_amplitude = squeeze(sum(clean_img', 1));
clf;
semilogy(fs ./ 1e6, amplitude_all1(1:1024)), hold on;
semilogy(fs ./ 1e6, amplitude1(1:1024))
xlabel('Frequency (MHz)');
ylabel('Amplitude (Log scale)')
title('Amplitude vs. frequency for all baselines at time 1')
semilogy(fs ./ 1e6, clean_amplitude(1:1024));
legend('All baselines', '1 baseline', '1 baseline (noise removed)')
```




Note that the signal-to-noise ratio improves as:

1. Data from more baselines are added, and
2. The anomalous background data from the (n,n) baselines is removed.

Rather than stack images from different baselines together, we can stack images from the *same* baseline over several intervals of time to observe how the frequency dependence changes over time. This time, we can look at baseline 2, corresponding to antennas (0, 1):

```
vis2_time = sqrt(visdata2_time.r(1, :, 1, :).^2 + visdata2_time.i(1, :, 1, :).^2);
visim2_time = squeeze(vis2_time(1, :, 1, 1:1378:end));

clf;
imagesc(visim2_time');
xt = get(gca, 'XTick');
set(gca, 'XTick', xt, 'XTickLabel', round(xt/10.24 + 100));
xlabel('Frequency (Hz)');
yticks('auto');
ylabel('Time');
c = colorbar;
c.Label.String = "Visibility amplitude";
title('Baseline 2 (0, 1) at times 1-7');
```



Note that this plot represents the reading of this particular baseline at each instant of time among 7 equally spaced times. The exact Julian date of these times (which are too long and precise to be properly displayed on the plot) are, respectively:

```
times_baseline2 = times(1:1378:1378*6+2);
fprintf('%.6f\n', times_baseline2)
```

```
2458108.125574
2458108.125698
2458108.125822
2458108.125947
2458108.126071
2458108.126195
2458108.126320
```

We observe very little variation of the visibility over time for this baseline. Notable variations include:

- At time 4, the baseline picks up a ~132 MHz signal.
- The signal at ~137 MHz seems to get stronger over time.

While this data may possibly be used to identify noise contamination due to time-varying backgrounds, most analysis of the signal and background can be done by observing all baselines at a specific instant of time.

```
function visimg = visdat2img(visdata, freq_range)
    vismagnitude = sqrt(visdata.r(1, freq_range, 1, :).^2 + visdata.i(1, freq_range, 1, :).^2);
    visimg = squeeze(vismagnitude(1, freq_range, 1, :));
```

end