



DEPARTMENT OF INFORMATION SYSTEMS AND COMPUTER SCIENCE



```
001011100100011110111100100110101110100100101
1101010110101010000101010101001010101010101010
101001010010010010101010101010101010101010101010
1110000111101011000000011110101010101010000010101
111010101110010100010010111010100010100100111010
1010100101001001001000010101011010101010101010010111
00101010010101001010100000001010101001111101000011001
100011001000011100110101011000100110101010000101010
1100101010101000010011001010100010010101010101010
10100101001001001010101010101010101010101010101010
111000011110101100000001110101010101010000010101
00100101010010100100101001000101010101010101010010
1001010010000101010010010101001010010101010010010
10010100101010101010101010101010101010101010101001
10010100101010101010101010101010101010101010101010
```

										01
										02
										03
										04
										05
A	B	C	D	E	F	G	H			

Timing

Time for SFML

Lecture Time!

- ▶ Getting Started: Guided Tutorial
- ▶ Timing is Everything: Using the Clock in SFML

0010101001010100001111001101010010101
10001100100001111001101010010101
11001010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
001001010100101001001010010010010110
10010100100001010100100101001010
100101001010100101001010010101010101




DISCS

Tutorials

- ▶ You could just follow the tutorials in <http://www.sfml-dev.org/learn.php>
 - ▶ I recommend doing so if you're a fast learner and/or you're super excited
- ▶ Or we could accelerate the process through these slides

0010101001010100001111001101010010101
10001100100001111001101010010101
11001010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
00100101010010100100101001001010110
10010100100001010100100101001010
100101001010100101001010101010101




DISCS

Header File

- ▶ `#include <SFML/Graphics.hpp>`
- ▶ **Optional:** `using namespace sf;`
 - ▶ Things are going to get confusing if you already use the `std` namespace, so I don't recommend doing this

00101010010101000011110100001100
10001100100001111001101010010101
110010101010100001001100101010100
1001010010010010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
10010100100001010100100101001010
100101001010100101001010010101



DISCS

SFML Window (Initialization)

```
int main( void )  
{  
    sf::RenderWindow window( sf::VideoMode(  
        WINDOW_W, WINDOW_H ), "AppTitleHere" );  
    window.setFramerateLimit( FPS );  
    // ...  
}
```

► ~~What, did you think we'd be doing text games forever?~~

► Purpose of variables in all-caps should be obvious


001010100101010001111001101010010101
11001010101010100001001100101010100
10010100100100101010101010101010101
11100001111010110000000111101001
001001010100101001001010010010010110
10010100100001010100100101001010
10010100101010010100101010010101



SFML Clock

- ▶ Timing is very important for most games
 - ▶ You want some things to happen after a certain amount of time has passed
 - ▶ You want to prevent unfair spamming of player abilities
 - ▶ You want to maintain a certain number of frames per second without burning out your player's video card
 - ▶ What other time-dependent events do you

want?



DISCS

SFML Clock

```
// ...  
sf::Clock clock;  
sf::Time elapsedTime = sf::seconds( 0 );  
sf::Time anotherTime = sf::milliseconds( 17914 );  
// ...
```

- ▶ Remember, a constructor is called when you declare an object variable
 - ▶ Declaring an SFML clock starts it


0010101001010100011110100001100
10001100100001111001101010010101
11001010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
10010100100001010100100101001010
100101001010100101001010010101



DISCS

SFML Clock

```
int main( void )
{
    // ...
    while( yourAppIsRunning )
    {
        // do stuff
        sf::Time iterationTime = clock.restart();
        elapsedTime += iterationTime;
        // do stuff that depends on how much time passed
        // since either the clock started (elapsedTime)
        // or the clock's last restart() call
        //                                     (iterationTime)
    }
```



SFML Clock

- ▶ In other programs/libraries/etc., frame rate can be controlled using the system clock and a `sleep()` function
- ▶ Doesn't quite work very well in SFML so don't bother
 - ▶ Use `RenderWindow's` `setFramerateLimit()` function instead

0010101001010100011110100001100
10001100100001111001101010010101
110010101010100001001100101010100
1001010010010010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
1001010010001010100100101001010
100101001010100101001010010101



Reminders

- ▶ I have already provided a batch file to make your life easier (`make.bat`)
- ▶ Usage: `make FileToCompile.cpp`
- ▶ Assuming no errors, the result should be an executable (`a.exe`)
 - ▶ You may edit the batch file to change this, but this requires some knowledge of the `g++` compiler syntax



Homework

- ▶ Edit the program we used to test SFML (`main.cpp`) so that it prints out:
 - ▶ time it took for the last iteration (should be zero if this is the first), and
 - ▶ total time elapsed so far (should include current iteration, so this should NOT be zero when first displayed)

```
0010101001010100011110100001100
10001100100001111001101010010101
110010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
1001010010001010100100101001010
1001010010101001010010101010101
```



Homework

- ▶ In addition, disable/delete the mouse input portion of the code
- ▶ The program must be edited such that the circle's color will change to a random color every 3 seconds
 - ▶ The color must be chosen from a pool of 5 instead of 3 colors

```
001010100101010001111001101010010101
1000110010001111001101010010101
110010101010100001001100101010100
1001010010010010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
1001010010001010100100101001010
100101001010100101001010010101
```



Homework


► Speaking of random:

```
#include <cstdlib>      // header for srand() & rand()
#include <ctime>        // header for time()
```

```
// somewhere in initialization
srand( time( NULL ) );
```

```
// to get a random number from 0 to some maximum
someInt = rand() % SOME_MAX_PLUS_ONE;
```

00101010010101000111100101010010101
110010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
1001010010001010100100101001010
1001010010101001010010101010101



Homework

- ▶ For the time outputs, use the following format:
 - ▶ N seconds and X milliseconds
 - ▶ X should be a whole number between 0 and 999, inclusive
 - ▶ N should be a whole number greater than or equal to 0

0010101001010100011110100001100
10001100100001111001101010010101
11001010101010100001001100101010100
100101001001001010101010101010101
11100001111010110000000111101001
0010010101001010010010100100101010
10010100100001010100100101001010
10010100101010010100101010010101



DISCS

Homework

- ▶ How to get the time values you need:
 - ▶ <https://www.sfml-dev.org/tutorials/2.4/system-time.php>
 - ▶ You can also dig around for preset color variables in other tutorials or the API docs
- ▶ How to format the values after you've extracted what you need:
 - ▶ You can use the cplusplus.com site to search for “truncate”, “cast float as int”, etc.



Homework

- ▶ And don't forget peer evals
- ▶ Follow instructions stated in the syllabus
 - ▶ I may have ignored issues from the first peer evaluations, but I will start handing out deductions for those who don't follow instructions starting today

0010101001010100011110100001100
10001100100001111001101010010101
110010101010100001001100101010100
1001010010010010101010101010101
11100001111010110000000111101001
001001010100101001001010010010110
1001010010001010100100101001010
100101001010100101001010010101



DISCS