DrägerSensor® XS EC Amine

Order no. 68 09 545

Used in	Plug & Play	Replaceable	Guaranty	Expected sensor life	Selective filter
Dräger X-am 7000	yes	yes	1 year	> 1.5 years	–

MARKET SEGMENTS

Foundries, refineries, power plants

TECHNICAL SPECIFICATIONS

Detection limit:	2 ppm	
Resolution:	1 ppm	
Measurement range/ Relative sensitivity	0 to 100 ppm CH_3NH_2 (methylamine)	0.70
	0 to 100 ppm $(CH_3)_2NH$ (dimethylamine)	0.50
	0 to 100 ppm $(CH_3)_3N$ (trimethylamine)	0.50
	0 to 100 ppm $C_2H_5NH_2$ (ethylamine)	0.70
	0 to 100 ppm $(C_2H_5)_2NH$ (diethylamine)	0.50
	0 to 100 ppm $(C_2H_5)_3N$ (triethylamine)	0.50
	0 to 100 ppm NH_3 (ammonia)*	1.00
Response time:	≤ 30 seconds (t_{50})	
Precision		
Sensitivity:	≤ ± 3% of measured value	
Long-term drift, at 20°C (68°F)		
Zero point:	≤ ± 2 ppm/month	
Sensitivity:	≤ ± 3% of measured value/month	
Warm-up time:	≤ 12 hours	
Ambient conditions		
Temperature:	(–40 to 50)°C (–40 to 122)°F	
Humidity:	(10 to 90)% RH	
Pressure:	(700 to 1,300) hPa	
Influence of temperature		
Zero point:	≤ ± 5 ppm	
Sensitivity:	≤ ± 5% of measured value	
Influence of humidity		
Zero point:	≤ ± 0.1 ppm/% RH	
Sensitivity:	≤ ± 0.2% of measured value/% RH	
Test gas:	approx. 5 to 100 ppm NH_3, or one of the other target gases: C H_3NH_2, $(CH_3)_2NH$, $(CH_3)_3N$, $C_2H_5NH_2$, $(C_2H_5)_2NH$, $(C_2H_5)_3N$	

* lead compound

SPECIAL CHARACTERISTICS

Six different amines can be detected using this sensor. It is sufficient to calibrate it using an ammonia test gas. By doing so, all of the other amines are then automatically calibrated.

The values shown in the following table are standard and apply to new sensors. The values maybe fluctuate by ± 30%. The sensor may also be sensitive to additional gases (for more information, please contact Dräger). Gas mixtures may be displayed as the sum of all components. Gases with a negative cross sensitivity may displace an existing concentration of amine. To be sure, please check if gas mixtures are present.

RELEVANT CROSS-SENSITIVITIES

Gas/vapor	Chem. symbol	Concentration	Display in ppm NH_3
Acetone	CH_3COCH_3	1,000 ppm	No effect
Acetylene	C_2H_2	200 ppm	No effect
Carbon dioxide	CO_2	1.5 Vol. %	≤ 5(–)
Carbon monoxide	CO	200 ppm	No effect
Chlorine	Cl_2	10 ppm	≤ 20(–)
Ethene	C_2H_4	1,000 ppm	≤ 3
Hydrogen	H_2	1,000 ppm	≤ 3
Hydrogen cyanide	HCN	25 ppm	≤ 3
Hydrogen sulfide	H_2S	20 ppm	≤ 50
Methane	CH_4	10 Vol. %	No effect
Methanol	CH_3OH	200 ppm	≤ 3
Nitrogen dioxide	NO_2	20 ppm	≤ 10(–)
Nitrogen monoxide	NO	20 ppm	≤ 10
Phosphine	PH_3	5 ppm	≤ 8
Sulfur dioxide	SO_2	20 ppm	No effect
Tetrahydrothiophene	C_4H_8S	10 ppm	≤ 10

(–) Indicates negative deviation