DrägerSensor® XS EC Hydrazine

Order no. 68 09 190

Used in	Plug & Play	Replaceable	Guaranty	Expected sensor life	Selective filter
Dräger X-am 5100	no	yes	1 year	> 1 year	_

MARKET SEGMENTS

Rocket fuel, aircraft fuel (e.g. F-16), fuel for emergency power generators, for electrochemical power generation in secondary cells or in alkaline fuel cells, especially in space travel, submarines, and other military equipment.

TECHNICAL SPECIFICATIONS

Detection limit:	0.02 ppm				
Resolution:	0.01 ppm				
Measurement range:	0 to 5 ppm N ₂ H ₄ (hydrazine)	1			
	0 to 5 ppm CH ₃ NH-NH ₂ (methyl hydrazine)	0.6			
	0 to 5 ppm (CH ₃) ₂ N-NH ₂ (dimethylhydrazine)	0.6			
Response time:	≤ 180 seconds (t ₉₀)				
Precision					
Sensitivity:	≤ ± 5% of measured value				
Long-term drift, at 20°C (68°F)					
Zero point:	≤ ± 0.01 ppm/month				
Sensitivity:	≤ ± 5% of measured value/month				
Warm-up time:	≤ 1 hour				
Ambient conditions					
Temperature:	(-20 to 50)°C (-4 to 122)°F				
Humidity:	(15 to 95)% RH				
Pressure:	(700 to 1,300) hPa				
Influence of temperature					
Zero point:	No effect				
Sensitivity:	≤ ± 5% of measured value				
Influence of humidity					
Zero point:	No effect				
Sensitivity:	≤ ± 0.1% of measured value/% RH				
Test gas:	0.1 to 3 ppm N ₂ H ₄ , CH ₃ NH-NH ₂ , (CH ₃) ₂ N-NH ₂				

SPECIAL CHARACTERISTICS

This sensor is used exclusively in the Dräger X-am 5100 for monitoring concentrations of hydrazine (N_2H_4) , methyl hydrazine (CH_3NH-NH_2) , and dimethylhydrazine $((CH_3)_2N-NH_2)$.

The values shown in the following table are standard and apply to new sensors. The values maybe fluctuate by \pm 30%. The sensor may also be sensitive to additional gases (for more information, please contact Dräger). Gas mixtures may be displayed as the sum of all components. Gases with a negative cross sensitivity may displace an existing concentration of hydrazine. To be sure, please check if gas mixtures are present.

RELEVANT CROSS-SENSITIVITIES

Gas/vapor	Chem. symbol	Concentration	Display in ppm N ₂ H ₄	
Acetone	CH ₃ COCH ₃	1,000 ppm	No effect	
Ammonia	NH ₃	250 ppm	≤ 2.5	
Carbon dioxide	CO ₂	100 Vol. %	No effect	
Carbon monoxide	СО	1,000 ppm	No effect	
Chlorine	Cl ₂	10 ppm	≤ 0.1(-)	
Ethanol	C ₂ H ₅ OH	130 ppm	No effect	
Ethene	C ₂ H ₄	20 ppm	No effect	
Hydrogen	H ₂	1,000 ppm	No effect	
Hydrogen sulfide	H ₂ S	20 ppm	≤ 0.25	
i-propanol	(CH ₃) ₂ CHOH	1,000 ppm	No effect	
Methane	CH ₄	3 Vol. %	No effect	
Nitrogen dioxide	NO ₂	20 ppm	≤ 0,05	
Nitrogen monoxide	NO	25 ppm	≤ 0.05	
Propane	C ₃ H ₈	1.5 Vol. %	No effect	
Sulfur dioxide	SO ₂	10 ppm	No effect	