

Nitika

Head of New Product Development

E. npd@monarchgraphics.co.in

M. +91 84486 92407

www.monarchgraphics.in

Certified Inkjet Resists Hostile ts

Our Product Advantages

Special Drum Surface adhesive is an aggressive cold temperature adhesive specifically developed to adhere to all types of metal and polyethylene drums, both new and reconditioned. We have also kept in mind the adverse minimum temperature for pasting the labels at -20 degrees Celsius on Most Surfaces and Service Temperature due to various conditions across the globe at -40 degrees Celsius to +93 degrees Celsius. The Material also has a special top coat to meet the printing regulations and is depicted by the comparison between an ordinary label and our labels when put through abrasion testing.

Portfolio Characteristics

- Consistent Adherence to a range of Drum Surfaces
- Strong Enough to withstand ongoing Outdoor Exposure
- Weather-and Temperature-Resistant
- Impervious to contact with Aggressive Chemicals and Saltwater
- Highly adaptable to varying Container Sizes and Diameters
- A Range of Cost and Performance options

Inkjet Printing of Drum Label

Digital inkjet label printing is revolutionizing the printing industry with low cost, fast, reliable label printers with excellent print quality that meet the GHS requirements for labeling chemical products. True print-on-demand label printing with low cost, durable inks renders preprinted label inventory prohibitively expensive and inefficient.

Color inkjet printing has shown to be a consistently reliable and operationally sound print platform for labeling drums, pails and totes, particularly in high volume plants. We work with our clients to identify the best printer model and type for their operations.

Monarch Graphics labels are GHS compliant and are designed for color inkjet printing on a variety of tested and approved pigment ink printers. With our labels, we use a highly durable film face stock combined with BS5609-tested custom adhesives,

To get more information about GHS-compliant labeling, visit



Labeling of Dangerous Goods

SHIPMENT OF DANGEROUS GOODS		
INTERNATIONAL LEGISLATION		
United Nations Global Harmonised System (GHS)	BS 5609	International Maritime Organizations International Maritime Dangerous Goods Code (IMDG)
Label requirements when classifying chemicals		Label requirements if shipped by sea (e.g. sea water resistance)
Section Two Base material of the pressure sensitive, adhesive-coated label		Section Three Final printed pressure-sensitive, adhesive-coated label



What is BS5609

The IMDG Code is a global system developed by the International Maritime Organization to govern the safe transport of dangerous goods by sea. IMDG also requires that labels of dangerous goods meet certain durability standards to withstand the harsh conditions of marine transport. Specifically, IMDG requires labels to withstand three-month marine immersion. BS 5609 includes this test, and establishes durability standards for printed pressure-sensitive, adhesive-coated labels used in marine environment.

Guiding Principles

BS 5609 testing is a two-part certification for both the adhesive coated label base material and the printed label. Each must be certified separately before the complete label is approved. Including marine immersion (salt water testing), labels must resist:

- Weathering (Rain, Snow, UV Exposure)
- Temperature Cycling (Hot/Cold Fluctuations)
- Abrasion (Scratching/Tearing)
- Chemicals (Alcohol, Oil and Acetone; Solvent Resistance)
- Fading and Smudging

SECTION 2: Tests the base material and requires that labels withstand a three-month saltwater submersion test. The test specifically looks for dimensional stability, peel adhesion and color fastness after long-term exposure to salt spray and sunlight.

SECTION 3: Tests the printed label for permanence, abrasion resistance (legibility and contrast after exposure to sand and artificial seawater) and color fastness. This includes the inks or ribbons and print methods or systems that were used to create the label.