


$$\sigma(z) = \frac{1}{1+e^{-z}}$$

We know that  $\bar{x}_i \in [0, 1000]$

$$\Rightarrow \bar{z} = w\bar{x} + b$$

will have a higher magnitude  
since  $\bar{z} \propto \bar{x}$

The graph of  $\sigma(z)$  is as follows



$\therefore \forall z$  with high magnitude

$$\sigma(z) \rightarrow 1$$

$$\Rightarrow \sigma'(z) = \sigma(z)(\sigma(z) - 1)$$

approaches zero.

We know that  $\delta^L = \nabla_a C_x \odot \sigma'(z)$

$$\delta^L = (w^{\ell+1})^T \delta^{\ell+1} \odot \sigma'(z)$$

~~=~~ Since  $\sigma'(z)$  approaches zero it stagnates

learning.

Another problem this poses is the overflow problem. For high  $z$ ,  $e^z$  is very large and we might not be able to handle it.

Using ReLU function in the hidden layer.

ReLU being a linear function

does not stagnate learning.

Thus it definitely solves the problem.

However we see  $f'(z)$  for ReLU

$$= \begin{cases} 1 & \text{if } z > 0 \\ 0 & \text{else} \end{cases}$$

$\Rightarrow$  ReLU will not be able to handle the

big range of  $[0, 100]$  since gives

the same derivative for the complete range.

Pre-processing required:

To overcome sigmoid problem:

① we can scale the data to a smaller

range  $\rightarrow$  like  $[0, 1]$

To overcome ReLU problem:

② we can normalize the data about its mean to a range like  $[-1, 1]$

3. In quadratic cost

$$C_x = \frac{1}{2} \|A_x^L - y\|^2$$

$$\Rightarrow \nabla_a C_x = \|A_x^L - y\|$$

So, according to BP1,

$$\delta^L = \nabla_a C_x \odot \sigma'(z)$$

$$= \|A_x^L - y\| \odot \sigma'(z)$$

In this expression,  $\sigma'(z)$  slows down the learning as  $\sigma'(z)$  near 0 as  $z$  approaches maxima/minima.

$\Rightarrow$  If we are able to remove this term, we will be able to fasten the learning process.

This is exactly what the cross entropy cost function does.

Cross-entropy cost:

$$C_x = -(y \ln a_x^L + (1-y) \ln (1-a_x^L))$$

$$\Rightarrow \nabla_a C_x = - \left[ \frac{y}{a_x^L} + \frac{(1-y)}{(1-a_x^L)} \cdot (-1) \right]$$

$$= \frac{1-y}{1-a_x^L} - \frac{y}{a_x^L} = \frac{a_x^L(1-y) - y(1-a_x^L)}{a_x^L(1-a_x^L)}$$

$$\Rightarrow \nabla_a C_a = \frac{a_x^L - y a_x^L - y + y a_x^L}{a_x^L (1 - a_x^L)}$$

$$= \frac{a_x^L - y}{\sigma(z) [1 - \sigma(z)]}$$

$$= \frac{a_x^L - y}{\sigma'(z)}$$

$$[\because \sigma'(z) = \sigma(z)(1 - \sigma(z))]$$

$$\Rightarrow \delta^L = \nabla_a C_a \odot \sigma'(z)$$

$$= \frac{a_x^L - y}{\cancel{\sigma'(z)}} \cdot \cancel{\sigma'(z)}$$

$$= a_x^L - y$$

Hence, cross-entropy fastens the learning process