

TIQCollect — Feature List

All 21 tables and 457 columns, read from the data models on 2026-09-18. Every table also has `id`, `created_at`, `updated_at` (omitted below). Full dictionary with types, keys and enum values: [docs/data-dictionary.html](https://docs.data-dictionary.html) / .pdf.

BORROWER & DEBT

customers · the borrower · 32 columns

`customer_ref`, `full_name`, `date_of_birth`, `gender`, `pan_masked`, `aadhaar_masked`, `phone_primary`, `phone_alternate`, `email`, `address_line1`, `address_line2`, `city`, `state`, `pincode`, `latitude`, `longitude`, `risk_category`, `risk_score`, `cibil_score`, `preferred_contact_start`, `preferred_contact_end`, `language_preference`, `customer_segment`, `is_hostile`, `requires_female_agent`, `do_not_contact`, `fraud_flag`, `complaints_raised`, `tags`

loans · one bank loan · 32 columns

`loan_account_number`, `customer_id`, `loan_type`, `bank_name`, `branch_code`, `sanctioned_amount`, `disbursed_amount`, `outstanding_principal`, `total_outstanding`, `overdue_amount`, `emi_amount`, `disbursement_date`, `maturity_date`, `last_payment_date`, `next_due_date`, `dpd`, `dpd_bucket`, `status`, `interest_rate`, `outstanding_interest`, `penal_charges`, `tenure_months`, `last_payment_amount`, `npa_flag`, `legal_status`, `settlement_status`, `bank_risk_score`, `collection_priority_score`, `recovery_potential`

cases · one collection assignment on a loan · 30 columns

`case_number`, `customer_id`, `loan_id`, `agent_id`, `assigned_by_id`, `status`, `priority`, `target_amount`, `collected_amount`, `waiver_approved`, `allocation_date`, `allocation_score`, `is_ml_allocated`, `visit_count`, `max_visits_allowed`, `resolved_at`, `resolution_notes`, `collection_stage`, `bank_ptp_date`, `bank_ptp_amount`, `bank_ptp_status`, `bank_agent_remarks`, `handover_notes`, `is_escalated`, `escalation_reason`, `escalated_at`, `escalation_notes`

FIELD ACTIVITY

visits · one doorstep event · 54 columns

`case_id`, `agent_id`, `check_in_latitude`, `check_in_longitude`, `check_in_time`, `check_out_time`, `distance_from_customer_metres`, `geo_verified`, `within_contact_hours`, `customer_met`, `outcome`, `person_met`, `default_reason`, `not_met_reason`, `borrower_disposition`, `visit_number`, `selfie_photo_key`, `agent_photo_key`, `borrower_photo_key`, `object_photo_key`, `agent_photo_lat`, `agent_photo_lon`, `agent_photo_accuracy`, `agent_photo_altitude`, `agent_photo_captured_at`, `borrower_photo_lat`, `borrower_photo_lon`, `borrower_photo_accuracy`, `borrower_photo_altitude`, `borrower_photo_captured_at`, `object_photo_lat`, `object_photo_lon`, `object_photo_accuracy`, `object_photo_altitude`, `object_photo_captured_at`, `agent_photo_sha256`, `borrower_photo_sha256`, `object_photo_sha256`, `device_id`, `agent_recording_key`, `borrower_recording_key`, `agent_recording_transcript`, `borrower_recording_transcript`, `property_type`, `occupancy_status`, `vehicle_present`, `business_running`, `ai_visit_note`, `notes`, `consent_given`, `signature_key`

payments · money received against a case · 18 columns

`case_id`, `visit_id`, `agent_id`, `amount`, `mode`, `status`, `receipt_number`, `upi_reference`, `cheque_number`, `bank_reference`, `receipt_photo_key`, `payment_date`, `verified_at`, `verified_by_id`, `receipt_sms_sent`

ptps · promise to pay · 17 columns

`case_id`, `visit_id`, `agent_id`, `committed_amount`, `committed_date`, `actual_paid_amount`, `status`, `customer_reason`, `agent_notes`, `follow_up_date`, `reminder_sent`, `reminder_sent_at`, `reschedule_count`, `parent_ptp_id`

call_logs · one phone attempt · 21 columns

`case_id`, `agent_id`, `customer_id`, `called_at`, `duration_seconds`, `outcome`, `phone_used`, `customer_response_notes`, `visit_feasible_today`, `best_time_to_visit`, `available_from`, `available_until`, `blocked_until_date`, `alternate_location_hint`, `payment_intent_signalled`, `borrower_disposition`, `verbal_payment_date`, `ai_intel_summary`

PEOPLE & ROUTING

agents · field agent · 30 columns

`user_id`, `employee_code`, `id_card_number`, `agency_id`, `gender`, `base_latitude`, `base_longitude`, `territory`, `languages_spoken`, `specialization`, `max_cases_per_day`, `vehicle_type`, `status`, `tier`, `ranking_score`, `last_known_latitude`, `last_known_longitude`, `last_location_update`, `current_month_visits`, `current_month_collections`, `current_month_ptps_set`, `current_month_ptps_honored`, `lifetime_collection_rate`, `sos_active`, `sos_triggered_at`, `fcm_token`, `manager_user_id`

users · login identity · 18 columns

`email`, `phone`, `full_name`, `date_of_birth`, `hashed_password`, `role`, `is_active`, `is_verified`, `registered_device_fingerprint`, `hashed_refresh_token`, `totp_secret`, `totp_enabled`, `last_login_at`, `failed_login_attempts`, `locked_until`

beats · an agent's routed day · 28 columns

`agent_id`, `beat_date`, `beat_number`, `ordered_case_ids`, `total_cases`, `estimated_distance_km`, `estimated_duration_minutes`, `total_target_amount`, `status`, `cases_completed`, `amount_collected`, `route_geometry`, `route_legs`, `route_source`, `actual_distance_km`, `actual_duration_minutes`, `is_ml_generated`, `ml_model_version`, `geo_cluster_id`, `manually_modified`, `modified_by_id`, `is_leave_day`, `leave_type`, `leave_remarks`, `allocation_run_id`

agent_locations · GPS trail · 10 columns

`agent_id`, `latitude`, `longitude`, `accuracy_metres`, `recorded_at`, `received_at`, `source`, `is_sos`, `battery_pct`

agent_performance · monthly KPI archive · 13 columns

`agent_id`, `month`, `total_visits`, `customer_met`, `total_collected`, `ptps_set`, `ptps_honored`, `collection_rate`, `ranking_score`, `tier`

ALLOCATION

allocation_runs · one nightly allocation · 14 columns

`manager_user_id`, `plan_date`, `strategy`, `status`, `total_cases_evaluated`, `total_cases_allocated`, `total_cases_deferred`, `total_cases_blocked`, `total_agents_planned`, `expected_recovery_total`, `summary_metadata`

allocation_decisions · why each case landed where it did · 13 columns

run_id, case_id, previous_agent_id, allocated_agent_id, outcome, reason, visit_priority_score, fit_score, score_breakdown, model_prediction_id

allocation_settings · manager's allocator preferences · 8 columns

manager_user_id, objective, max_territory_radius_km, max_daily_stops_per_agent, custom_weights

SCORING & ML

repayment_score_snapshots · point-in-time features + scorecard outputs per loan/day · 36 columns

loan_id, customer_id, case_id, as_of_date, scored_at, trigger, is_backfill, source, model_version, likelihood, risk_score, band, risk_category, evidence_coverage, features, contributions, outcome, outcome_amount, outcome_source, outcome_observed_at, outcome_horizon_days, feature_age_days, recovery_potential, recovery_rate_30, recovery_rate_60, recovery_rate_90, recovery_speed_index, recovery_evidence_coverage, recovery_source, recovery_model_version, recovery_contributions, recovered_amount_30, recovered_amount_60, recovered_amount_90, recovery_labelled_through_days

model_predictions · every served model score · 28 columns

model_name, model_version, artifact_sha256, entity_type, entity_id, loan_id, case_id, agent_id, as_of_date, scored_at, probability, points, band, is_modelled, fallback_reason, features, feature_coverage, reason_codes, scoring_versions, contributions, outcome_baseline, outcome_definition_version, outcome_status, actual_outcome, outcome_attached_at, outcome_horizon_days, label_comparison

model_candidates · retraining lifecycle · 31 columns

model_name, candidate_version, incumbent_version, state, monitoring_run_id, trigger_reasons, monitoring_report, training_cohort, cohort_rows, outcome_definition_version, feature_set, code_versions, training_metrics, validation_run_id, gate_results, gates_passed, comparison_run_id, comparison_results, comparison_passed, gini_uplift, decided_by_id, decided_at, decision_note, promoted_at, promoted_from_version, rejection_reason, error, state_history

GOVERNANCE

fraud_reviews · anomaly verdicts · 8 columns

visit_id, finding_type, agent_id, verdict, note, reviewed_by_user_id, reviewed_at

audit_logs · append-only trail · 14 columns

user_id, action, entity_type, entity_id, ip_address, user_agent, device_fingerprint, details, old_values, new_values, success, failure_reason

used_quick_login_tokens · single-use tokens · 2 columns

jti, used_at

MODEL INPUTS

Served model — recovery_risk 2.2.0 (champion), 15 features: arrears_ratio, cibil_score, no_answer_streak, overdue_amount, intent_calls_3m, calls_3m, paid_ratio_3m, ptp_amount_to_emi, days_since_last_contact, interest_rate, latest_disposition, last_commit_status, recent_ptp_status, employment_type, disposition_recency_class

Previous champion — recovery_risk 1.1.0, 4 features: dpd, cibil_score, ptp_kept_ratio, overdue_amount

Logged on every prediction (64 candidate features): adverse_visit_ratio_6m, age, arrears_ratio, branch_code, call_answer_rate_3m, call_answer_rate_6m, calls_3m, cibil_score, city, contact_rate_6m, days_since_disposition, days_since_last_answered_call, days_since_last_call, days_since_last_contact, days_since_last_payment, disposition_recency_class, dispute_visits_6m, distinct_agents_6m, dpd, dpd_bucket, emi_amount, employment_type, fraud_flag, hardship_visits_6m, intent_calls_3m, intent_rate_6m, interest_rate, is_hostile, is_secured, last_call_intent, last_commit_status, last_payment_to_emi, last_visit_outcome, latest_disposition, loan_type, months_on_book, no_answer_streak, outstanding_principal, outstanding_to_sanction, overdue_amount, paid_momentum, paid_ratio_12m, paid_ratio_1m, paid_ratio_3m, paid_ratio_6m, partial_payment_share_6m, pay_amount_cv_6m, payment_gap_cv_12m, payments_6m, penal_charges, penal_ratio, ptp_amount_to_emi, ptp_broken_6m, ptp_kept_6m, ptp_kept_ratio, ptp_rescheduled_6m, ptp_set_6m, recent_ptp_status, rtp_visits_6m, sanction_amount, tenure_months, total_outstanding, visits_3m, visits_6m

Deliberately not used — feed-only (a real lender has them; this product does not store them): address_vintage_months, bounce_count_6m, credit_vintage_months, dti_ratio, mail_returned_count, monthly_income, num_enquiries_6m, num_open_loans, other_lender_delinq, phone_verified, residence_type, sourcing_channel, thin_file, utilization_pct

Deliberately not used — no history (loans.dpd is overwritten in place): consecutive_misses, max_dpd_12m, months_since_first_delinq, times_30plus_12m, times_60plus_12m

SCORECARDS (hand-weighted, not models)

Repayment likelihood (loan): delinquency depth 30, promise history 20, payment track 15, contactability 12, arrears burden 10, bureau 8, conduct 8, legal posture 6, security 6, last payment size 5, segment 4.

Recovery potential (loan): ageing .18, security .16, payment recency .14, payment momentum .12, arrears share .10, legal posture .08, penal drag .06, NPA status .06 → recovery_rate_30/60/90, expected_recoverable_amount.

Visit priority (case): recoverable value ±37.5, urgency ±12, effort already spent -25 → priority 0–100.

Agent competency (agent × loan type × DPD bucket): empirical-Bayes shrunk win rate → eb_multiplier 0.75–1.25 in the allocator.

Allocator (case × agent): expected_recovery 0.45 (collectable × model probability × eb_multiplier), proximity 0.40, skills, continuity, workload; hard gates DNC, hostility, female-agent, 16 km territory, PTP fatigue.