```c
#include <stdio.h>

int main() {
    int first, second, temp;

    printf("Enter first number: ");
    scanf("%d", &first);
    printf("Enter second number: ");
    scanf("%d", &second);

    temp = first;
    first = second;
    second = temp;

    printf("\nAfter swapping:\nFirst number: %d\nSecond number: %d\n",
        first, second);
    return 0;
}
```

```
Enter first number: 57
Enter second number: 32

After swapping:
First number: 32
Second number: 57


=== Code Execution Successful ===
```

main.cpp

Share Run

```c
#include <stdio.h>

int main() {
    int first, second, temp;

    printf("Enter first number: ");
    scanf("%d", &first);
    printf("Enter second number: ");
    scanf("%d", &second);

    temp = first;
    first = second;
    second = temp;

    printf("\nAfter swapping:\nFirst number: %d\nSecond number: %d\n",
        first, second);
    return 0;
}
```

Output

Clear

```
Enter first number: 57
Enter second number: 32

After swapping:
First number: 32
Second number: 57


=== Code Execution Successful ===
```

main.cpp

Share Run

```c
#include <stdio.h>

int main() {
    int num1, num2, sum;

    printf("Enter the first number: ");
    scanf("%d", &num1);

    printf("Enter the second number: ");
    scanf("%d", &num2);

    sum = num1 + num2;

    printf("The sum of %d and %d is: %d\n", num1, num2, sum);

    return 0;
}
```

Output

Clear

```
Enter the first number: 665
Enter the second number:
33
The sum of 665 and 33 is: 698


=== Code Execution Successful ===
```

main.cpp

Share Run

```c
#include <stdio.h>

int main() {
    int n, i, sum = 0;

    printf("Enter a positive integer: ");
    scanf("%d", &n);

    for (i = 1; i <= n; ++i) {
        sum += i;
    }

    printf("Sum of first %d natural numbers = %d\n", n, sum);

    return 0;
}
```

Output

Clear

```
Enter a positive integer: 46
Sum of first 46 natural numbers = 1081


=== Code Execution Successful ===
```

main.cpp

```c
#include <stdio.h>

int main() {
    float principal, rate, time, simple_interest;

    printf("Enter principal amount: ");
    scanf("%f", &principal);

    printf("Enter rate of interest: ");
    scanf("%f", &rate);

    printf("Enter time period (in years): ");
    scanf("%f", &time);

    simple_interest = (principal * rate * time) / 100;

    printf("\nSimple Interest = %.2f\n", simple_interest);

    return 0;
}
```

Output

```
Enter principal amount: 5000
Enter rate of interest: 13
Enter time period (in years): 1

Simple Interest = 650.00


=== Code Execution Successful ===
```

main.cpp

```c
#include <stdio.h>

int main() {
    int n, i;
    unsigned long long factorial = 1;

    printf("Enter an integer: ");
    scanf("%d", &n);

    if (n < 0) {
        printf("Error! Factorial of a negative number doesn't exist.\n");
    } else {
        for (i = 1; i <= n; ++i) {
            factorial *= i;
        }
        printf("Factorial of %d = %llu\n", n, factorial);
    }

    return 0;
}
```

Output

```
Enter an integer: 56
Factorial of 56 = 6908521828386340864


=== Code Execution Successful ===
```

main.cpp

Share Run

```c
#include <stdio.h>

int main() {
    int num;

    printf("Enter an integer: ");
    scanf("%d", &num);

    if (num % 2 == 0) {
        printf("%d is even.\n", num);
    } else {
        printf("%d is odd.\n", num);
    }

    return 0;
}

```

Output

Clear

```
Enter an integer: 15
15 is odd.


=== Code Execution Successful ===
```