

# Introduction to Quantum Computing

K. Grover

# Outline

- 1 History and Motivation
- 2 Classical vs Quantum Computing
- 3 A small example
- 4 Quantum > Classical
- 5 Cool Things

## Disclaimer

**I am STILL not an expert on quantum stuff.**

## History and Motivation

# History of Quantum Mechanics

- It all started in late 19th and early 20th century.

# History of Quantum Mechanics

- It all started in late 19th and early 20th century.
- Light behaves like particles (Photoelectric effect [1905]).

# History of Quantum Mechanics

- It all started in late 19th and early 20th century.
- Light behaves like particles (Photoelectric effect [1905]).
- Classical theories are not applicable, new theories required.

# History of Quantum Mechanics

- It all started in late 19th and early 20th century.
- Light behaves like particles (Photoelectric effect [1905]).
- Classical theories are not applicable, new theories required.
- Quantum mechanics was born.



# History of Quantum Mechanics

- It all started in late 19th and early 20th century.
- Light behaves like particles (Photoelectric effect [1905]).
- Classical theories are not applicable, new theories required.
- Quantum mechanics was born.
- Most theories in classical physics can be derived from quantum mechanics as an approximation valid at large (macroscopic) scale.

# History of Quantum Computing

1980 Paul Benioff proposed quantum mechanical model of a Turing machine.

# History of Quantum Computing

1980 Paul Benioff proposed quantum mechanical model of a Turing machine.

1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .

# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.

# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.
- 1996 Grover's algorithm.

# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.
- 1996 Grover's algorithm.
- 1997 I was born.

# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.
- 1996 Grover's algorithm.
- 1997 I was born.
- 2019 Google proved quantum supremacy. (200 seconds vs 10,000 years)

# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.
- 1996 Grover's algorithm.
- 1997 I was born.
- 2019 Google proved quantum supremacy. (200 seconds vs 10,000 years)
- 2019 IBM said bullshit!



# History of Quantum Computing

- 1980 Paul Benioff proposed quantum mechanical model of a Turing machine.
- 1982 Richard Feynman and Yuri Manin suggested:  $QC > CC$ .
- 1994 Shor's factoring algorithm.
- 1996 Grover's algorithm.
- 1997 I was born.
- 2019 Google proved quantum supremacy. (200 seconds vs 10,000 years)
- 2019 IBM said bullshit!
- 2021 USTC proved quantum supremacy. Boson sampling with 76 photons. (20 seconds vs 600 million years)

## Why is QC important?

- Classical computers are getting smaller and more powerful day by day.

## Why is QC important?

- Classical computers are getting smaller and more powerful day by day.
- Transistors (5 nm) are approaching the size of an atom (0.1 nm).

## Why is QC important?

- Classical computers are getting smaller and more powerful day by day.
- Transistors (5 nm) are approaching the size of an atom (0.1 nm).
- Quantum tunneling -> bad transistors.

# Why is QC important?

- Classical computers are getting smaller and more powerful day by day.
- Transistors (5 nm) are approaching the size of an atom (0.1 nm).
- Quantum tunneling -> bad transistors.
- Use Shor's algorithm.

# Why is QC important?

- Classical computers are getting smaller and more powerful day by day.
  - Transistors (5 nm) are approaching the size of an atom (0.1 nm).
  - Quantum tunneling -> bad transistors.
- 
- Use Shor's algorithm.
  - Use Grover's algorithm.

# Why is QC important?

- Classical computers are getting smaller and more powerful day by day.
  - Transistors (5 nm) are approaching the size of an atom (0.1 nm).
  - Quantum tunneling -> bad transistors.
- 
- Use Shor's algorithm.
  - Use Grover's algorithm.
  - Simulate quantum mechanical systems. Speed up biological research by giving new insights on proteins.

## Classical vs Quantum Computing



# Representing bits as vectors

- Dirac delta notation:

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

# Representing bits as vectors

- Dirac delta notation:

$$|0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \quad |1\rangle = \begin{pmatrix} 0 \\ 1 \end{pmatrix}$$

- What are the operations on a single bit?

# Operations on a single bit

## ■ Identity:

0  $\longrightarrow$  0

1  $\longrightarrow$  1

## ■ Negation:

0  $\longrightarrow$  1  
1  $\longrightarrow$  0

## ■ Constant 0:

0  $\longrightarrow$  0  
1  $\longrightarrow$  0

## ■ Constant 1:

0  $\longrightarrow$  1  
1  $\longrightarrow$  1

# Operations on a single bit using matrices

## ■ Identity:

$$\begin{array}{l} |0\rangle \rightarrow |0\rangle \\ |1\rangle \rightarrow |1\rangle \end{array} \quad \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$$

## ■ Negation:

$$\begin{array}{l} |0\rangle \rightarrow |1\rangle \\ |1\rangle \rightarrow |0\rangle \end{array} \quad \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$$

## ■ Constant 0:

$$\begin{array}{l} |0\rangle \rightarrow |0\rangle \\ |1\rangle \rightarrow |0\rangle \end{array} \quad \begin{pmatrix} 1 & 0 \\ 1 & 0 \end{pmatrix}$$

## ■ Constant 1:

$$\begin{array}{l} |0\rangle \rightarrow |1\rangle \\ |1\rangle \rightarrow |1\rangle \end{array} \quad \begin{pmatrix} 0 & 1 \\ 0 & 1 \end{pmatrix}$$

# Operations on a single bit using matrices

## ■ Identity:

$$\begin{array}{l} |0\rangle \rightarrow |0\rangle \\ |1\rangle \rightarrow |1\rangle \end{array} \quad \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$$

## ■ Negation:

$$\begin{array}{l} |0\rangle \xrightarrow{\text{X}} |1\rangle \\ |1\rangle \xrightarrow{\text{X}} |0\rangle \end{array} \quad \begin{pmatrix} 0 & 1 \\ 1 & 0 \end{pmatrix}$$

## ■ Constant 0:

$$\begin{array}{l} |0\rangle \xrightarrow{\text{0}} |0\rangle \\ |1\rangle \xrightarrow{\text{0}} |0\rangle \end{array} \quad \begin{pmatrix} 1 & 1 \\ 0 & 0 \end{pmatrix} \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \begin{pmatrix} 1 \\ 0 \end{pmatrix}$$

## ■ Constant 1:

$$\begin{array}{l} |0\rangle \xrightarrow{\text{1}} |1\rangle \\ |1\rangle \xrightarrow{\text{1}} |1\rangle \end{array} \quad \begin{pmatrix} 0 & 0 \\ 1 & 1 \end{pmatrix}$$

## 2 bits

$$|00\rangle = |0\rangle \otimes |0\rangle = \begin{pmatrix} 1 \\ 0 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} 1 & \begin{pmatrix} 1 \\ 0 \end{pmatrix} \\ 0 & \begin{pmatrix} 1 \\ 0 \end{pmatrix} \end{pmatrix} = \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} = |0\rangle$$

## 2 bits

$$|00\rangle = |0\rangle \otimes |0\rangle = \begin{pmatrix} 1 \\ 0 \\ 0 \\ 0 \end{pmatrix} = |0\rangle$$

$$|01\rangle = |0\rangle \otimes |1\rangle = \begin{pmatrix} 0 \\ 1 \\ 0 \\ 0 \end{pmatrix} = |1\rangle$$

$$|10\rangle = |1\rangle \otimes |0\rangle = \begin{pmatrix} 0 \\ 0 \\ 1 \\ 0 \end{pmatrix} = |2\rangle$$


$$|11\rangle = |1\rangle \otimes |1\rangle = \begin{pmatrix} 0 \\ 0 \\ 0 \\ 1 \end{pmatrix} = |3\rangle$$

# Operations on 2 bits

CNOT operation:

$|00\rangle \longrightarrow |00\rangle$   
 $|01\rangle \longrightarrow |01\rangle$   
 $|10\rangle \longrightarrow |11\rangle$   
 $|11\rangle \longrightarrow |10\rangle$

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{pmatrix}$$





$n$  bits

$$|010\dots 01\rangle = |i\rangle = \begin{pmatrix} 0 \\ 0 \\ \vdots \\ 1 \\ \vdots \\ 0 \\ 0 \end{pmatrix} \leftarrow (i-1)\text{th index}$$

# Qubits

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha|0\rangle + \beta|1\rangle$$

$$|\alpha|^2 + |\beta|^2 = 1$$

# Qubits

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha|0\rangle + \beta|1\rangle$$

$$|\alpha|^2 + |\beta|^2 = 1$$

Some examples:  $\begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \quad \begin{pmatrix} \frac{\sqrt{3}}{2} \\ \frac{1}{2} \end{pmatrix} \quad \begin{pmatrix} -\frac{\sqrt{3}}{2}i \\ \frac{1}{2}i \end{pmatrix}$

# Qubits

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} = \alpha \begin{pmatrix} 1 \\ 0 \end{pmatrix} + \beta \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \alpha|0\rangle + \beta|1\rangle$$

$$|\alpha|^2 + |\beta|^2 = 1$$

Some examples:  $\begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \quad \begin{pmatrix} \frac{\sqrt{3}}{2} \\ \frac{1}{2} \end{pmatrix} \quad \begin{pmatrix} -\frac{\sqrt{3}}{2} \\ \frac{1}{2} \end{pmatrix}$

- Polarization of a photon.
- Current in a superconductor.
- Spin of an electron.
- Collection of anyons.

# n Qubits

$$\begin{pmatrix} \alpha_{11} \\ \alpha_{12} \end{pmatrix} \otimes \begin{pmatrix} \alpha_{21} \\ \alpha_{22} \end{pmatrix} \otimes \cdots \otimes \begin{pmatrix} \alpha_{n1} \\ \alpha_{n2} \end{pmatrix} = \begin{pmatrix} \beta_0 \\ \beta_1 \\ \vdots \\ \beta_{2^n-1} \end{pmatrix}$$
$$\begin{pmatrix} \gamma_0 \\ \gamma_1 \\ \vdots \\ \gamma_{2^n-1} \end{pmatrix} \neq \begin{pmatrix} \delta_{11} \\ \delta_{12} \end{pmatrix} \otimes \begin{pmatrix} \delta_{21} \\ \delta_{22} \end{pmatrix} \otimes \cdots \otimes \begin{pmatrix} \delta_{n1} \\ \delta_{n2} \end{pmatrix}$$

# Recap

- History and Motivation.

Quantum Supremacy.

# Recap

- History and Motivation.
- Dirac delta notation for representing cbits and qubits.

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} \equiv e^{i\phi} \begin{pmatrix} \alpha \\ \beta \end{pmatrix}$$

$$\begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} -\frac{\sqrt{3}}{2}l \\ \frac{1}{2}l \end{pmatrix}$$

# Recap

- History and Motivation.
- Dirac delta notation for representing cbits and qubits.
- Superposition.

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} \equiv e^{i\phi} \begin{pmatrix} \alpha \\ \beta \end{pmatrix}$$

$$\begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} -\frac{\sqrt{3}}{2}l \\ \frac{1}{2}l \end{pmatrix}$$



# Recap


- History and Motivation.
- Dirac delta notation for representing cbits and qubits.
- Superposition.
- Tensor product for multiple qubits.

$$\begin{pmatrix} \alpha \\ \beta \end{pmatrix} \otimes \begin{pmatrix} \gamma \\ \delta \end{pmatrix} = \begin{pmatrix} \alpha \begin{pmatrix} \gamma \\ \delta \end{pmatrix} \\ \beta \begin{pmatrix} \gamma \\ \delta \end{pmatrix} \end{pmatrix} \\ = \begin{pmatrix} \alpha\gamma \\ \alpha\delta \\ \beta\gamma \\ \beta\delta \end{pmatrix}$$

# Recap

- History and Motivation.
- Dirac delta notation for representing cbits and qubits.
- Superposition.
- Tensor product for multiple qubits.
- Only reversible operations in QC e.g CNOT.

$$\begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 1 \\ 0 & 0 & 1 & 0 \end{pmatrix}$$



## A small example

# Hadamard Gate

$$H|0\rangle = \begin{pmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} 1 \\ 0 \end{pmatrix} = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} = |+\rangle$$



$$H|+\rangle = \begin{pmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} = \begin{pmatrix} 1 \\ 0 \end{pmatrix} = |0\rangle$$

# A state machine example


1 Qubit and only "bit-flip" and "hadamard" operator.

# A state machine example


1 Qubit and only "bit-flip" and "hadamard" operator.



# A state machine example



# A state machine example






Quantum > Classical


# Deutsch Oracle problem

How many queries to find the one-bit operation?



# Deutsch Oracle problem


How many queries to find the one-bit operation?



How many queries to find if the one-bit operation was a constant function or not?

# Deutsch Oracle problem

How many queries to find the one-bit operation?




How many queries to find if the one-bit operation was a constant function or not?

How to do it in a single query?

# Deutsch Oracle problem

How many queries to find the one-bit operation?



How many queries to find if the one-bit operation was a constant function or not?

How to do it in a single query?

Let's take a look at how these operations look on a quantum computer.

# Non-reversible computing on quantum computer


Identify input by looking at the output.

# Non-reversible computing on quantum computer

Identify input by looking at the output.  
Output the input also.


# Non-reversible computing on quantum computer

Identify input by looking at the output.  
Output the input also.







# Constant-0





New \_\_\_\_\_

Old \_\_\_\_\_



# Constant-1




# Identity



# Negation




# Deutsch oracle problem



**Output:**  $|11\rangle \rightarrow$  Constant operation  
 $|01\rangle \rightarrow$  Variable operation

**Notation:**  $|old, new\rangle$

# Constant 0





New \_\_\_\_\_

Old \_\_\_\_\_



Output:  $|11\rangle$

# Constant 1



Output:  $|11\rangle$

# Identity





Output:  $|01\rangle$



# Identity

$$C\left(\begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix} \otimes \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix}\right) = C\begin{pmatrix} \frac{1}{2} \\ -\frac{1}{2} \\ -\frac{1}{2} \\ \frac{1}{2} \end{pmatrix} = \begin{pmatrix} \frac{1}{2} \\ -\frac{1}{2} \\ \frac{1}{2} \\ -\frac{1}{2} \end{pmatrix} = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \otimes \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix}$$


# Negation




Output:  $|01\rangle$

## Cool Things

# Mach-Zehnder Interferometer




# Mach-Zehnder Interferometer




$$\begin{pmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix}$$

# Mach-Zehnder Interferometer




$$\begin{pmatrix} -\frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix} = \begin{pmatrix} -1 \\ 0 \end{pmatrix}$$

# Mach-Zehnder Interferometer




# Mach-Zehnder Interferometer




$$\begin{pmatrix} \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & -\frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} 0 \\ 1 \end{pmatrix} = \begin{pmatrix} \frac{1}{\sqrt{2}} \\ -\frac{1}{\sqrt{2}} \end{pmatrix}$$



# Mach-Zehnder Interferometer



# Mach-Zehnder Interferometer




$$\begin{pmatrix} -\frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} & \frac{1}{\sqrt{2}} \end{pmatrix} \begin{pmatrix} \frac{1}{\sqrt{2}} \\ 0 \end{pmatrix} = \begin{pmatrix} -\frac{1}{2} \\ \frac{1}{2} \end{pmatrix}$$


# Elitzur-Vaidman Bombs



# Bomb doesn't work




# Bomb works



$$\mathcal{P}(\text{Photon detected at bomb}) = \frac{1}{2}$$

Bomb explodes (Works)

# Bomb works




$$\mathcal{P}(\text{Photon detected at bomb}) = \frac{1}{2}$$

$$\mathcal{P}(\text{Photon detected at } D_0) = \frac{1}{4}$$

Bomb explodes (Works)

Bomb doesn't explode (Don't know)

# Bomb works



$$\mathcal{P}(\text{Photon detected at bomb}) = \frac{1}{2}$$

$$\mathcal{P}(\text{Photon detected at } D_0) = \frac{1}{4}$$

$$\mathcal{P}(\text{Photon detected at } D_1) = \frac{1}{4}$$

Bomb explodes (Works)

Bomb doesn't explode (Don't know)

Bomb doesn't explode (Works)

# Quantum Entanglement

- If we cannot factor two bits, they are said to be **entangled**.



# Quantum Entanglement

- If we cannot factor two bits, they are said to be **entangled**.

e.g. 
$$\begin{pmatrix} \frac{1}{\sqrt{2}} \\ 0 \\ 0 \\ \frac{1}{\sqrt{2}} \end{pmatrix} = \begin{pmatrix} a \\ b \end{pmatrix} \otimes \begin{pmatrix} c \\ d \end{pmatrix}$$


$$ac = \frac{1}{\sqrt{2}}$$

$$ad = 0$$

$$bc = 0$$

$$bd = \frac{1}{\sqrt{2}}$$

# Quantum Entanglement



$$CH_1 \left( \begin{pmatrix} 1 \\ 0 \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} \right) = C \left( \begin{pmatrix} \frac{1}{\sqrt{2}} \\ \frac{1}{\sqrt{2}} \end{pmatrix} \otimes \begin{pmatrix} 1 \\ 0 \end{pmatrix} \right) = C \begin{pmatrix} \frac{1}{\sqrt{2}} \\ 0 \\ \frac{1}{\sqrt{2}} \\ 0 \end{pmatrix}$$

## Spooky action at a distance!

## Spooky action at a distance!

- Einstein, Podolsky and Rosen gave the idea of Quantum entanglement.

## Spooky action at a distance!


- Einstein, Podolsky and Rosen gave the idea of Quantum entanglement.
- Principle of locality would be violated.

# Spooky action at a distance!

- Einstein, Podolsky and Rosen gave the idea of Quantum entanglement.
- Principle of locality would be violated.
- Experiments show that Quantum entanglement happens.

# Quantum Teleportation

Transferring (state of) a qubit from one location to other.



# Quantum Teleportation

- No cloning theorem.
- Not faster than light.



# Next time?

- Better understanding of quantum state machines.
- Verification of quantum systems.
- What can we do?

## Sources:

- Youtube video titled "Quantum computing for computer scientists" by Microsoft Research.
- John Preskill's (Caltech) lectures on quantum computing.
- Model Checking Quantum Systems by M. Ying and Y. Feng.
- A lot of other youtube videos and wikipedia pages on quantum stuff.