



IIIT Hyderabad
ICPC2**

Arya Mahendraker, Kushal Balabhadruni, Sriteja Pashya

2025-12-29

Contents

- 1 Stress
- 2 Contest
- 3 Data structures
- 4 Graph
- 5 Number theory
- 6 Numerical
- 7 Strings
- 8 Geometry

Stress (1)

check.h

d41d8c, 29 lines

```
/*
#!/bin/bash
for ((t=1; ; t++)); do
    echo "Test $t"
    ./gen 50 > in/in${t}.txt
    ./brute < in/in${t}.txt > out1.txt
    ./sol < in/in${t}.txt > out2.txt
    if ! diff -q out1.txt out2.txt >/dev/null; then
        echo "Mismatch found on test $t!"
        cat in/in${t}.txt
        diff out1.txt out2.txt
        break
    fi
done
# also for times, use this:
# #ifndef ONLINE_JUDGE
```

```
1 # clock_t tStart = clock();
1 # #endif
# void runtime() {
1 # #ifndef ONLINE_JUDGE
#     double elapsed =
2 #         (double)(clock() - tStart) / CLOCKS_PER_SEC;

10 #     fprintf(stderr,
#         ">> Runtime: %.10fs\n",
19 #         elapsed);
# #endif
22 # }
*/
```

25 Contest (2)

27

template.h

<bits/stdc++.h>, <ext/pb_ds/assoc_container.hpp>, <ext/pb_ds/tree_policy.hpp> 90c829, 24 lines

```
using namespace std;
using namespace __gnu_pbds;
typedef tree<int, null_type, less_equal<int>, rb_tree_tag
    ,
        tree_order_statistics_node_update>
    ordered_multiset;
typedef tree<int, null_type, less<int>, rb_tree_tag,
    tree_order_statistics_node_update>
    ordered_set;
// find_by_order returns iterator to kth largest (0-
// indexed)
// order_of_key returns number of elements strictly less
// than given value -->
// basically index (0-indexed) for multiset, to erase use
// upper_bound.
// Upper_bound lower_bound exchange their roles
#define ONLINE_JUDGE
#ifndef ONLINE_JUDGE
#define db(x) cerr << #x << " == " << x << endl
```

```

#define dbs(x) cerr << x << endl
#else
#define db(x) ((void)0)
#define dbs(x) ((void)0)
#endif

#define int long long
#define fast() ios_base::sync_with_stdio(0); cin.tie(NULL)
);

```

```

\
#define prDouble(x) cout << fixed << setprecision(10) <<
x

```

rng.h

e7e903, 9 lines

```

mt19937_64 rng(chrono::steady_clock::now().
time_since_epoch().count());

int random(int a, int b) {
    if (a > b) return 0;
    return a + rng() % (b - a + 1);
}

double random_double(double a, double b) {
    return a + (b - a) * (rng() / (double)rng.max());
}

```

Data structures (3)

SegTree.h

Description: SegTree

b79e63, 23 lines

```

struct segtree {
    typedef int T;
    // for max segtree, set unit = INT_MIN and f(a,b) = max
    (a,b)
    static constexpr T unit = 0; // identity for sum
    T f(T a, T b) { return a + b; } // (any associative fn)

```

```

vector<T> s;
int n;
segtree(int n = 0, T def = unit) : s(2 * n, def), n(n)
{}

void update(int pos, T val) {
    for (s[pos += n] = val; pos /= 2;)
        s[pos] = f(s[pos * 2], s[pos * 2 + 1]);
}

T query(int b, int e) { // query [b, e)
    T ra = unit, rb = unit;
    for (b += n, e += n; b < e; b /= 2, e /= 2) {
        if (b % 2)
            ra = f(ra, s[b++]);
        if (e % 2)
            rb = f(s[--e], rb);
    }
    return f(ra, rb);
}
};

```

LazySegTree.h

Description: LazySegTree

9376a1, 97 lines

```

template <typename T, typename U> struct seg_tree_lazy {
    int S, H;
    T zero;
    vector<T> value;
    U noop;
    vector<bool> dirty;
    vector<U> prop;
    seg_tree_lazy(int _S, T _zero = T(), U _noop = U()) {
        zero = _zero, noop = _noop;
        for (S = 1, H = 1; S < _S;)
            S *= 2, H++;
        value.resize(2 * S, zero);
        dirty.resize(2 * S, false);
        prop.resize(2 * S, noop);
    }

```

```

void set_leaves(vector<T> &leaves) {
    copy(leaves.begin(), leaves.end(), value.begin() + S)
    ;
    for (int i = S - 1; i > 0; i--)
        value[i] = value[2 * i] + value[2 * i + 1];
}
void apply(int i, U &update) {
    value[i] = update(value[i]);
    if (i < S) {
        prop[i] = prop[i] + update;
        dirty[i] = true;
    }
}
void rebuild(int i) {
    for (int l = i / 2; l; l /= 2) {
        T combined = value[2 * l] + value[2 * l + 1];
        value[l] = prop[l](combined);
    }
}
void propagate(int i) {
    for (int h = H; h > 0; h--) {
        int l = i >> h;
        if (dirty[l]) {
            apply(2 * l, prop[l]);
            apply(2 * l + 1, prop[l]);
            prop[l] = noop;
            dirty[l] = false;
        }
    }
}
void upd(int i, int j, U update) {
    i += S, j += S;
    propagate(i), propagate(j);
    for (int l = i, r = j; l <= r; l /= 2, r /= 2) {
        if ((l & 1) == 1)
            apply(l++, update);
        if ((r & 1) == 0)

```

```

            apply(r--, update);
    }
    rebuild(i), rebuild(j);
}
T query(int i, int j) {
    i += S, j += S;
    propagate(i), propagate(j);
    T res_left = zero, res_right = zero;
    for (; i <= j; i /= 2, j /= 2) {
        if ((i & 1) == 1)
            res_left = res_left + value[i++];
        if ((j & 1) == 0)
            res_right = value[j--] + res_right;
    }
    return res_left + res_right;
};
struct node {
    int sum, width;
    node operator+(const node &n) {
        // change 1
        return {sum + n.sum, width + n.width};
    }
};
struct update {
    bool type; // 0 for add, 1 for reset
    int value;
    node operator()(const node &n) {
        // change 2
        if (type)
            return {n.width * value, n.width};
        else
            return {n.sum + n.width * value, n.width};
    }
    update operator+(const update &u) {
        // change 3
        if (u.type)

```

```

        return u;
    return {type, value + u.value};
}
};
// Example Initialization
// seg_tree_lazy<node, update> lst(size, {0, 1}, {0, 0});
// lst.set_leaves(leaves);
// lst.upd(l, r, {0, value});
// auto result = lst.query(l, r);

```

DSU.h

Description: DSU

7f85c5, 21 lines

```

struct DSU {
    int n;
    vi parent, size;
    DSU(int _n) : n(_n), parent(n), size(n, 1) { iota(
        parent.begin(), parent.end(), 0); }
    int find_set(int x) {
        if (parent[x] == x) return x;
        return parent[x] = find_set(parent[x]);
    }
    int getSize(int x) { return size[find_set(x)]; }
    void union_sets(int x, int y) {
        x = find_set(x); y = find_set(y);
        if (x == y) return;
        if (size[x] > size[y]) {
            parent[y] = x;
            size[x] += size[y];
        } else {
            parent[x] = y;
            size[y] += size[x];
        }
    }
};

```

RMQ.h

Description: RMQ

7bc356, 16 lines

```

template <class T>
struct RMQ {
    vector<vector<T>> jmp;
    RMQ(const vector<T>& V) : jmp(1, V) {
        for (int pw = 1, k = 1; pw * 2 <= sz(V); pw *= 2, ++k)
        {
            jmp.emplace_back(sz(V) - pw * 2 + 1);
            for (int j = 0; j < sz(jmp[k]); j++)
                jmp[k][j] = min(jmp[k - 1][j], jmp[k - 1][j + pw
                    ]);
        }
    }
    T query(int a, int b) {
        assert(a <= b); // tie(a, b) = minimax(a, b)
        int dep = 63 - __builtin_clzll(b - a + 1);
        return min(jmp[dep][a], jmp[dep][b - (1 << dep) + 1]);
    }
};

```

Treap.h

Description: Treap

1048b8, 68 lines

*/*A short self-balancing tree. It acts as a sequential container with log-time splits/joins, and is easy to augment with additional data.*

*Time: $\mathcal{O}(\log N)$ */*

```

struct Node {
    Node *l = 0, *r = 0;
    int val, y, c = 1;
    Node(int val) : val(val), y(rand()) {}
    void recalc();
};

```

```

int cnt(Node* n) { return n ? n->c : 0; }
void Node::recalc() { c = cnt(l) + cnt(r) + 1; }

template <class F>
void each(Node* n, F f) {
    if (n) {
        each(n->l, f);
        f(n->val);
        each(n->r, f);
    }
}

pair<Node*, Node*> split(Node* n, int k) {
    if (!n) return {};
    if (cnt(n->l) >= k) { // "n->val >= k" for lower_bound(k)
        auto pa = split(n->l, k);
        n->l = pa.second;
        n->recalc();
        return {pa.first, n};
    } else {
        auto pa = split(n->r, k - cnt(n->l) - 1); // and just "k"
        n->r = pa.first;
        n->recalc();
        return {n, pa.second};
    }
}

Node* merge(Node* l, Node* r) {
    if (!l) return r;
    if (!r) return l;
    if (l->y > r->y) {
        l->r = merge(l->r, r);
        l->recalc();
        return l;
    } else {

```

```

        r->l = merge(l, r->l);
        r->recalc();
        return r;
    }
}

Node* ins(Node* t, Node* n, int pos) {
    auto [l, r] = split(t, pos);
    return merge(merge(l, n), r);
}

// Example application: move the range [l, r) to index k
void move(Node*& t, int l, int r, int k) {
    Node *a, *b, *c;
    tie(a, b) = split(t, l);
    tie(b, c) = split(b, r - l);
    if (k <= l)
        t = merge(ins(a, b, k), c);
    else
        t = merge(a, ins(c, b, k - r));
}

```

cht.h

b46218, 33 lines

```

struct Line {
    mutable i64 m, c, p;
    bool operator<(const Line& o) const { return m < o.m; }
    bool operator<(i64 x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    // (for doubles, use inf = 1/.0, div(a,b) = a/b)
    static const i64 inf = LONG_LONG_MAX;
    i64 div(i64 a, i64 b) { // floored division
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) return x->p = inf, 0;

```

```

    if (x->m == y->m)
        x->p = x->c > y->c ? inf : -inf;
    else
        x->p = div(y->c - x->c, x->m - y->m);
    return x->p >= y->p;
}
void add(i64 m, i64 c) {
    auto z = insert({m, c, 0}), y = z++, x = y;
    while (isect(y, z)) z = erase(z);
    if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
    while ((y = x) != begin() && (--x)->p >= y->p)
        isect(x, erase(y));
}
i64 query(i64 x) {
    assert(!empty());
    auto l = *lower_bound(x);
    return l.m * x + l.c;
}
};

```

Mos.h

Description: Mos

1cb2c0, 38 lines

```

int BLOCK = DO_NOT_FORGET_TO_CHANGE_THIS;
struct Query {
    int l, r, id;
    Query(int _l, int _r, int _id) : l(_l), r(_r), id(_id) {}
}
bool operator<(Query &o) {
    int mblock = l / BLOCK, oblock = o.l / BLOCK;
    return (mblock < oblock) or
        (mblock == oblock and mblock % 2 == 0 and r < o.r) or
        (mblock == oblock and mblock % 2 == 1 and r > o.r);
};
};

```

```

void solve() {
    vector<Query> queries;
    queries.reserve(q);
    for (int i = 0; i < q; i++) {
        int l, r;
        cin >> l >> r;
        l--, r--;
        queries.emplace_back(l, r, i);
    }
    sort(all(queries));
    int ans = 0;
    auto add = [&](int v) {};
    auto rem = [&](int v) {};
    vector<int> out(q); // Change out type if necessary
    int cur_l = 0, cur_r = -1;
    for (auto &[l, r, id] : queries) {
        while (cur_l > l)
            add(--cur_l);
        while (cur_l < l)
            rem(cur_l++);
        while (cur_r < r)
            add(++cur_r);
        while (cur_r > r)
            rem(cur_r--);
        out[id] = ans;
    }
}

```

MosUpdate.h

Description: Mos with Updates

9bb5d0, 75 lines

```

// Set BLOCK_SIZE to N^(2/3) for Mo's with updates
int BLOCK_SIZE = CHANGE;

struct Query {
    int l, r, t, id;
    bool operator<(const Query& o) const {
        int l_block = l / BLOCK_SIZE;

```

```

    int o_l_block = o.l / BLOCK_SIZE;
    if (l_block != o_l_block) return l_block <
        o_l_block;
    int r_block = r / BLOCK_SIZE;
    int o_r_block = o.r / BLOCK_SIZE;
    if (r_block != o_r_block) return r_block <
        o_r_block;
    return t < o.t;
}

};

struct Update {
    int pos, prev_val, new_val;
};

void solve_mo_with_updates() {
    // BLOCK_SIZE = pow(n, 2.0/3.0);

    vector<Query> queries;
    vector<Update> updates;
    // for (int i = 0; i < q; i++) {
    //     int type; cin >> type;
    //     if (type == 1) { // Query
    //         int l, r; cin >> l >> r; l--, r--;
    //         queries.push_back({l, r, (int)updates.size
    //             (), (int)queries.size()});
    //     } else { // Update
    //         int pos, val; cin >> pos >> val; pos--;
    //         updates.push_back({pos, 0, val}); //
    //         prev_val can be filled later
    //     }
    // }

    sort(all(queries));

    int ans = 0;
    auto add = [&](int idx) {};

```

```

    auto rem = [&](int idx) {};
    auto apply_update = [&](int update_idx, int current_l
        , int current_r) {
        auto& upd = updates[update_idx];
        // If update position is within current range [l,
            r], adjust answer
        if (upd.pos >= current_l && upd.pos <= current_r)
            {
                rem(upd.pos);
                a[upd.pos] = upd.new_val;
                add(upd.pos);
            } else {
                a[upd.pos] = upd.new_val;
            }
    };

    auto undo_update = [&](int update_idx, int current_l,
        int current_r) {
        auto& upd = updates[update_idx];
        if (upd.pos >= current_l && upd.pos <= current_r)
            {
                rem(upd.pos);
                a[upd.pos] = upd.prev_val;
                add(upd.pos);
            } else {
                a[upd.pos] = upd.prev_val;
            }
    };

    vector<int> out(queries.size());
    int cur_l = 0, cur_r = -1, cur_t = 0;
    for (auto& [l, r, t, id] : queries) {
        while (cur_t < t) apply_update(cur_t++, cur_l,
            cur_r);
        while (cur_t > t) undo_update(--cur_t, cur_l,
            cur_r);
        while (cur_l > l) add(--cur_l);
        while (cur_r < r) add(++cur_r);
    }

```



```

        while (cur_l < l) rem(cur_l++);
        while (cur_r > r) rem(cur_r--);
        out[id] = ans;
    }
}

```

RangeUpdateTree.h

Description: Range update tree for range updates and point queries

Time: $\mathcal{O}(\log N)$

a653e9, 32 lines

```

template <typename T, typename F> struct RangeUpdateTree
{
    int n;
    vector<T> tree;
    T identity;
    F merge;
    RangeUpdateTree(const vector<T> &arr, T id, F _m)
        : n((int)arr.size()), tree(2 * n), identity(id),
          merge(_m) {
        for (int i = 0; i < n; i++)
            tree[n + i] = arr[i];
        for (int i = n - 1; i >= 1; i--)
            tree[i] = merge(tree[2 * i], tree[2 * i + 1]);
    }
    void update(int l, int r, T value) {
        assert(l >= 0 && r < n && l <= r);
        for (l += n, r += n; l <= r; l >>= 1, r >>= 1) {
            if (l & 1)
                tree[l] = merge(value, tree[l]), l++;
            if (!(r & 1))
                tree[r] = merge(value, tree[r]), r--;
        }
        if (l == r)
            tree[l] = merge(value, tree[l]);
    }
    T query(int v) {
        T res = tree[v += n];
        for (; v > 1; v >>= 1)

```

```

            res = merge(res, tree[v >> 1]);
        return res;
    }
};
// ex: RangeUpdateTree<int, decltype(join)> v(vi(n, 1e9)
//      , 1e9, join); use auto
// func for join

```

segtreeFaisal.h

Description: LazySegTree

282af9, 49 lines

```

template <typename T, typename F>
struct SegTree {
    int n, off, ct;
    vector<T> t;
    const T id;
    F f;
    SegTree(const vector<T> &a, T _id, F _f)
        : n(sz(a)), off(1 << 32 - __builtin_clz(n)), ct(n ^
          off >> 1), t(2 * n), id(_id), f(_f) {
        for (int i = 0; i < 2 * ct; i++) t[off + i] = a[i];
        for (int i = 2 * ct; i < n; i++) t[i + off - n] = a[i];
    }
    for (int i = n - 1; i >= 1; i--) t[i] = f(t[2 * i], t
        [2 * i + 1]);
}
int i2leaf(int i) { return i + off - (i < 2 * ct ? 0 :
    n); }
int leaf2i(int l) { return l - off + (l < off ? n : 0);
    }
T query(int l, int r) {
    l = (l < 2 * ct) ? (l + off) : 2 * (l + off - n);
    r = (r < 2 * ct) ? (r + off) : 2 * (r + off - n);
    r += (r >= 2 * n);
    T resl(id), resr(id);
    for (; l <= r; l >>= 1, r >>= 1) {
        if (l == r) {
            resl = f(resl, t[l]);

```

```

        break;
    }
    if (l & 1) resl = f(resl, t[l++]);
    if (!(r & 1)) resr = f(t[r--], resr);
}
return f(resl, resr);
}
void update(int v, T value) {
    for (t[v = i2leaf(v)] = value; v >>= 1; )
        t[v] = f(t[2 * v], t[2 * v + 1]);
}
int lower_bound(int k) {
    if (t[1] < k) return n;
    T rem = id;
    int v = 1;
    while (v < n) {
        T resl = f(rem, t[2 * v]);
        if (resl >= k) {
            v = 2 * v;
        } else {
            rem = resl;
            v = 2 * v + 1;
        }
    }
    return leaf2i(v);
}
};

```

mergesorttree1.h

Description: Merge sort tree 1, for Static Count of Lesser Elements range queries.

<bits/stdc++.h>

25ca75, 55 lines

// We are given an array $a_1, a_2, a_3 \dots a_n$ and an integer q .
 // The i -th of the next q lines has three integers l_i, r_i, x_i .
 // The answer for this query is how many a_j such that $l_i \leq j \leq r_i$ and $a_j < x_i$.
 using namespace std;

```

const int N=1e5+5;
int n,q,a[N];
vector<int> seg[4*N+5];
//build merge sort tree
void build(int node,int l,int r){
    //if range length is 1 there's only one element to
    //add and no children
    if (l==r){
        seg[node].push_back(a[l]);
        return;
    }int mid=(l+r)/2;
    build(node*2,l,mid);
    build(node*2+1,mid+1,r);
    int i=0,j=0;
    // use two pointers to merge the two vectors in O(r-l+1)
    while (i<seg[node*2].size() && j<seg[node*2+1].size())
    {
        if (seg[node*2][i]<seg[node*2+1][j]) seg[node].
            push_back(seg[node*2][i++]);
        else seg[node].push_back(seg[node*2+1][j++]);
    }
    while (i<seg[node*2].size()) seg[node].push_back(seg[
        node*2][i++]);
    while (j<seg[node*2+1].size()) seg[node].push_back(
        seg[node*2+1][j++]);
    return;
}
//query
int query(int node,int l,int r,int lx,int rx,int x){
    //if outside -> 0
    if (l>rx || r<lx) return 0;
    //if inside do binary search
    if (l>=lx && r<=rx){
        int L=0,R=seg[node].size()-1,mid,ans=0;
        while (L<=R){
            mid=(L+R)/2;

```

```

        if (seg[node][mid]<x) {
            ans=mid+1;
            L=mid+1;
        }else R=mid-1;
    }return ans;
}
int mid=(l+r)/2;
return query(node*2,l,mid,lx,rx,x)+query(node*2+1,mid
+1,r,lx,rx,x);
}
signed main(){
    cin>>n>>q;
    for (int i=1;i<=n;i++) cin>>a[i];
    build(1,1,n);
    while (q--){
        int l,r,x;
        cin>>l>>r>>x;
        cout<<query(1,1,n,l,r,x)<<endl;
    }
    return 0;
}

```

Graph (4)

2sat.h

Description: 2sat

386ce8, 75 lines

```

/*
ts.either(x, y);
ts.either(~x, ~y); these two do x xor y

ts.setValue(x, x); assert x is true

use ~x to denote not x

call ts.solve() to run the solver, returns if a solution
exists
if exists: ts.values[i] contains the assignments

```

```

*/
struct TwoSat {
    int N;
    vector<vi> gr;
    vi values; // 0 = false, 1 = true

    TwoSat(int n = 0) : N(n), gr(2 * n) {}

    int addVar() { // (optional)
        gr.emplace_back();
        gr.emplace_back();
        return N++;
    }

    void either(int f, int j) {
        f = max(2 * f, -1 - 2 * f);
        j = max(2 * j, -1 - 2 * j);
        gr[f].push_back(j ^ 1);
        gr[j].push_back(f ^ 1);
    }

    void setValue(int x) { either(x, x); }

    void atMostOne(const vi& li) { // (optional)
        if (sz(li) <= 1) return;
        int cur = ~li[0];
        for (int i = 2; i < sz(li); i++) {
            int next = addVar();
            either(cur, ~li[i]);
            either(cur, next);
            either(~li[i], next);
            cur = ~next;
        }
        either(cur, ~li[1]);
    }

    vi val, comp, z;

```

```

int time = 0;
int dfs(int i) {
    int low = val[i] = ++time, x;
    z.push_back(i);
    for (int e : gr[i])
        if (!comp[e])
            low = min(low, val[e] ?: dfs(e));
    if (low == val[i]) do {
        x = z.back();
        z.pop_back();
        comp[x] = low;
        if (values[x >> 1] == -1)
            values[x >> 1] = x & 1;
    } while (x != i);
    return val[i] = low;
}

bool solve() {
    values.assign(N, -1);
    val.assign(2 * N, 0);
    comp = val;
    for (int i = 0; i < 2 * N; i++)
        if (!comp[i]) dfs(i);
    for (int i = 0; i < N; i++)
        if (comp[2 * i] == comp[2 * i + 1]) return 0;
    return 1;
}
};

```

bridges.h

Description: bridges

a17c69, 34 lines

```

// arya bridges
void findBridges_dfs(int u, int p, int &time, vector<
    vector<int>> &adj,
    vector<int> &disc, vector<int> &low,
    vector<pair<int, int>> &bridges) {
    disc[u] = low[u] = time++;

```

```

    for (int v : adj[u]) {
        if (v == p)
            continue;

        if (disc[v] != -1) {
            low[u] = min(low[u], disc[v]);
        } else {
            findBridges_dfs(v, u, time, adj, disc, low, bridges);
            low[u] = min(low[u], low[v]);
            if (low[v] > disc[u]) {
                bridges.push_back({u, v});
            }
        }
    }
}

vector<pair<int, int>> findBridges(int n, vector<vector<
    int>> &adj) {
    vector<int> disc(n, -1), low(n, -1);
    vector<pair<int, int>> bridges;
    int time = 0;

    for (int i = 0; i < n; ++i) {
        if (disc[i] == -1) {
            findBridges_dfs(i, -1, time, adj, disc, low,
                bridges);
        }
    }
    return bridges;
}

```

Dinic.h

Description: Dinic

00944d, 49 lines

```

// Flow algorithm with complexity  $O(VE \log U)$  where  $U$ 
=  $\max | \text{text} \{ \text{cap} \} |$ .

```

```
//  $O(\min(E^{\{1/2\}}, V^{\{2/3\}})E)$  if  $U = 1$ ;  $O(\sqrt{V}E)$ 
// for bipartite matching.
using ll = long long;
#define rep(i, j, k) for (int i = j; i < k; i++)
struct Dinic {
    struct Edge {
        int to, rev;
        ll c, oc;
        ll flow() { return max(oc - c, 0LL); } // if you
        need flows
    };
    vi lvl, ptr, q;
    vector<vector<Edge>> adj;
    Dinic(int n) : lvl(n), ptr(n), q(n), adj(n) {}
    void addEdge(int a, int b, ll c, ll rcap = 0) {
        adj[a].push_back({b, sz(adj[b]), c, c});
        adj[b].push_back({a, sz(adj[a]) - 1, rcap, rcap});
    }
    ll dfs(int v, int t, ll f) {
        if (v == t || !f) return f;
        for (int& i = ptr[v]; i < sz(adj[v]); i++) {
            Edge& e = adj[v][i];
            if (lvl[e.to] == lvl[v] + 1)
                if (ll p = dfs(e.to, t, min(f, e.c))) {
                    e.c -= p, adj[e.to][e.rev].c += p;
                    return p;
                }
        }
        return 0;
    }
    ll calc(int s, int t) {
        ll flow = 0;
        q[0] = s;
        rep(L, 0, 31) do { // 'int L=30' maybe faster for
            random data
            lvl = ptr = vi(sz(q));
            int qi = 0, qe = lvl[s] = 1;
```

```
while (qi < qe && !lvl[t]) {
    int v = q[qi++];
    for (Edge e : adj[v])
        if (!lvl[e.to] && e.c >> (30 - L))
            q[qi++] = e.to, lvl[e.to] = lvl[v] + 1;
    while (ll p = dfs(s, t, LLONG_MAX)) flow += p;
}
while (lvl[t])
    ;
return flow;
}
bool leftOfMinCut(int a) { return lvl[a] != 0; }
};
```

EdgeColoring.h

Description: Given a simple, undirected graph with max degree D , computes a $(D+1)$ -coloring of the edges such that no neighboring edges share a color. (D -coloring is NP-hard, but can be done for bipartite graphs by repeated matchings of max-degree nodes.)

Time: $\mathcal{O}(NM)$

e210e2, 31 lines

```
vi edgeColoring(int N, vector<pii> eds) {
    vi cc(N + 1), ret(sz(eds)), fan(N), free(N), loc;
    for (pii e : eds) ++cc[e.first], ++cc[e.second];
    int u, v, ncols = *max_element(all(cc)) + 1;
    vector<vi> adj(N, vi(ncols, -1));
    for (pii e : eds) {
        tie(u, v) = e;
        fan[0] = v;
        loc.assign(ncols, 0);
        int at = u, end = u, d, c = free[u], ind = 0, i = 0;
        while (d = free[v], !loc[d] && (v = adj[u][d]) != -1)
            loc[d] = ++ind, cc[ind] = d, fan[ind] = v;
        cc[loc[d]] = c;
        for (int cd = d; at != -1; cd ^= c ^ d, at = adj[at][cd])
            swap(adj[at][cd], adj[end = at][cd ^ c ^ d]);
        while (adj[fan[i]][d] != -1) {
```

```

    int left = fan[i], right = fan[++i], e = cc[i];
    adj[u][e] = left;
    adj[left][e] = u;
    adj[right][e] = -1;
    free[right] = e;
}
adj[u][d] = fan[i];
adj[fan[i]][d] = u;
for (int y : {fan[0], u, end})
    for (int& z = free[y] = 0; adj[y][z] != -1; z++);
}
rep(i, 0, sz(eds))
    for (tie(u, v) = eds[i]; adj[u][ret[i]] != v;) ++ret[i];
return ret;
}

```

EulerWalk.h

Description: Eulerian undirected/directed path/cycle algorithm. Input should be a vector of (dest, global edge index), where for undirected graphs, forward/backward edges have the same index. Returns a list of nodes in the Eulerian path/cycle with src at both start and end, or empty list if no cycle/path exists. To get edge indices back, add .second to s and ret.

Time: $\mathcal{O}(V + E)$

780b64, 15 lines

```

vi eulerWalk(vector<vector<pii>>& gr, int nedges, int src
=0) {
    int n = sz(gr);
    vi D(n), its(n), eu(nedges), ret, s = {src};
    D[src]++; // to allow Euler paths, not just cycles
    while (!s.empty()) {
        int x = s.back(), y, e, &it = its[x], end = sz(gr[x])
        ;
        if (it == end) { ret.push_back(x); s.pop_back();
            continue; }
        tie(y, e) = gr[x][it++];
        if (!eu[e]) {
            D[x]--, D[y]++;

```

```

        eu[e] = 1; s.push_back(y);
    }
}
for (int x : D) if (x < 0 || sz(ret) != nedges+1)
    return {};
return {ret.rbegin(), ret.rend()};
}

```

HLD.h

Description: HLD

7f333e, 55 lines

```

struct HLD {
    int n, timer = 0;
    vi top, tin, p, sub;
    HLD(vvi &adj) : n(sz(adj)), top(n), tin(n), p(n, -1),
        sub(n, 1) {
        vi ord(n + 1);
        for (int i = 0, t = 0, v = ord[i]; i < n; v = ord[++i]
        ])
            for (auto &to : adj[v])
                if (to != p[v])
                    p[to] = v, ord[++t] = to;
        for (int i = n - 1, v = ord[i]; i > 0; v = ord[--i])
            sub[p[v]] += sub[v];
        for (int v = 0; v < n; v++)
            if (sz(adj[v]))
                iter_swap(begin(adj[v]), max_element(all(adj[v]),
                    [&](int a, int b) {
                        return make_pair(a != p[v], sub[a]) <
                            make_pair(b != p[v], sub[b]);
                    }));
        function<void(int)> dfs = [&](int v) {
            tin[v] = timer++;
            for (auto &to : adj[v])
                if (to != p[v]) {
                    top[to] = (to == adj[v][0] ? top[v] : to);
                    dfs(to);
                }
        };
    };
}

```

```

    dfs(0);
}
int lca(int u, int v) {
    return process(u, v, [](int, int) {});
}
template <class B> int process(int a, int b, B op, bool
    ignore_lca = false) {
    for (int v;; op(tin[v], tin[b]), b = p[v]) {
        if (tin[a] > tin[b])
            swap(a, b);
        if ((v = top[b]) == top[a])
            break;
    }
    if (int l = tin[a] + ignore_lca, r = tin[b]; l <= r)
        op(l, r);
    return a;
}
template <class B> void subtree(int v, B op, bool
    ignore_lca = false) {
    if (sub[v] > 1 or !ignore_lca)
        op(tin[v] + ignore_lca, tin[v] + sub[v] - 1);
}

template <class B>
void go_up(int node, int anc, B op) {
    while(top[node] != top[anc]) {
        op(tin[top[node]], tin[node]);
        node = p[top[node]];
    }
    op(tin[anc], tin[node]);
}
};

```

KthAnc.h

Description: KthAnc

28228d, 60 lines

```

// O(log n) LCA with Kth anc
struct LCA {

```

```

    int n;
    vvi &adjLists;
    int lg;
    vvi up;
    vi depth;
    LCA(vvi &_adjLists, int root = 0) : n(sz(_adjLists)),
        adjLists(_adjLists) {
        lg = 1;
        int pw = 1;
        while (pw <= n)
            pw <<= 1, lg++;
        // lg = 20
        up = vvi(n, vi(lg));
        depth.assign(n, -1);
        function<void(int, int)> parentDFS = [&](int from,
            int parent) {
            depth[from] = depth[parent] + 1;
            up[from][0] = parent;
            for (auto to : adjLists[from]) {
                if (to == parent)
                    continue;
                parentDFS(to, from);
            }
        };
        parentDFS(root, root);
        for (int j = 1; j < lg; j++) {
            for (int i = 0; i < n; i++) {
                up[i][j] = up[up[i][j - 1]][j - 1];
            }
        }
    }
    int kthAnc(int v, int k) {
        int ret = v;
        int pw = 0;
        while (k) {
            if (k & 1)
                ret = up[ret][pw];

```

```

        k >>= 1;
        pw++;
    }
    return ret;
}

int lca(int u, int v) {
    if (depth[u] > depth[v])
        swap(u, v);
    v = kthAnc(v, depth[v] - depth[u]);
    if (u == v)
        return v;
    while (up[u][0] != up[v][0]) {
        int i = 0;
        for (; i < lg - 1; i++) {
            if (up[u][i + 1] == up[v][i + 1])
                break;
        }
        u = up[u][i], v = up[v][i];
    }
    return up[u][0];
};

int dist(int u, int v) { return depth[u] + depth[v] - 2
    * depth[lca(u, v)]; }
};

```

LCA.h

Description: LCA

993da6, 27 lines

```

// O(1) LCA
struct LCA {
    int T = 0;
    vi st, path, ret;
    vi en, d;
    RMQ<int> rmq;
    LCA(vector<vi> &C)
        : st(sz(C)), en(sz(C)), d(sz(C)), rmq((dfs(C, 0,
            -1), ret)) {}
    void dfs(vvi &adj, int v, int par) {

```

```

        st[v] = T++;
        for (auto to : adj[v])
            if (to != par) {
                path.pb(v), ret.pb(st[v]);
                d[to] = d[v] + 1;
                dfs(adj, to, v);
            }
        en[v] = T - 1;
    }
    bool anc(int p, int c) { return st[p] <= st[c] and en[p]
        ] >= en[c]; }
    int lca(int a, int b) {
        if (a == b)
            return a;
        tie(a, b) = minmax(st[a], st[b]);
        return path[rmq.query(a, b - 1)];
    }
    int dist(int a, int b) { return d[a] + d[b] - 2 * d[lca
        (a, b)]; }
};

```

MinCostMaxFlow.h

Description: MinCostMaxFlow

9a3690, 179 lines

```

template <const int MAX_N, typename flow_t,
    typename cost_t, flow_t FLOW_INF,
    cost_t COST_INF, const int SCALE = 16>
struct CostScalingMCMF {
#define sz(a) a.size()
#define zero_stl(v, sz) fill(v.begin(), v.begin() + (sz),
    0)
    struct Edge {
        int v;
        flow_t c;
        cost_t d;
        int r;
        Edge() = default;

```



```

Edge(int v, flow_t c, cost_t d, int r) : v(v), c(c),
    d(d), r(r) {}
};
vector<Edge> g[MAX_N];
cost_t negativeSelfLoop;
array<cost_t, MAX_N> pi, excess;
array<int, MAX_N> level, ptr;
CostScalingMCMF() { negativeSelfLoop = 0; }
void clear() {
    negativeSelfLoop = 0;
    for (int i = 0; i < MAX_N; i++) g[i].clear();
}
void addEdge(int s, int e, flow_t cap, cost_t cost) {
    if (s == e) {
        if (cost < 0) negativeSelfLoop += cap * cost;
        return;
    }
    g[s].push_back(Edge(e, cap, cost, sz(g[e])));
    g[e].push_back(Edge(s, 0, -cost, sz(g[s]) - 1));
}
flow_t getMaxFlow(int V, int S, int T) {
    auto BFS = [&]() {
        zero_stl(level, V);
        queue<int> q;
        q.push(S);
        level[S] = 1;
        for (q.push(S); !q.empty(); q.pop()) {
            int v = q.front();
            for (const auto &e : g[v])
                if (!level[e.v] && e.c) q.push(e.v), level[e.v]
                    = level[v] + 1;
        }
        return level[T];
    };
};
function<flow_t(int, flow_t)> DFS = [&](int v, flow_t
    fl) {
    if (v == T || fl == 0) return fl;

```

```

    for (int &i = ptr[v]; i < (int)g[v].size(); i++) {
        Edge &e = g[v][i];
        if (level[e.v] != level[v] + 1 || !e.c) continue;
        flow_t delta = DFS(e.v, min(fl, e.c));
        if (delta) {
            e.c -= delta;
            g[e.v][e.r].c += delta;
            return delta;
        }
    }
    return flow_t(0);
};
flow_t maxFlow = 0, tmp = 0;
while (BFS()) {
    zero_stl(ptr, V);
    while ((tmp = DFS(S, FLOW_INF))) maxFlow += tmp;
}
return maxFlow;
}
pair<flow_t, cost_t> maxflow(int N, int S, int T) {
    flow_t maxFlow = 0;
    cost_t eps = 0, minCost = 0;
    stack<int, vector<int>> stk;
    auto c_pi = [&](int v, const Edge &edge) { return
        edge.d + pi[v] - pi[edge.v]; };
    auto push = [&](int v, Edge &edge, flow_t delta, bool
        flag) {
        delta = min(delta, edge.c);
        edge.c -= delta;
        g[edge.v][edge.r].c += delta;
        excess[v] -= delta;
        excess[edge.v] += delta;
        if (flag && 0 < excess[edge.v] && excess[edge.v] <=
            delta) stk.push(edge.v);
    };
};
auto relabel = [&](int v, cost_t delta) { pi[v] -=
    delta + eps; };

```

```

auto lookAhead = [&](int v) {
    if (excess[v]) return false;
    cost_t delta = COST_INF;
    for (auto &e : g[v]) {
        if (e.c <= 0) continue;
        cost_t cp = c_pi(v, e);
        if (cp < 0)
            return false;
        else
            delta = min(delta, cp);
    }
    relabel(v, delta);
    return true;
};

auto discharge = [&](int v) {
    cost_t delta = COST_INF;
    for (int i = 0; i < sz(g[v]); i++) {
        Edge &e = g[v][i];
        if (e.c <= 0) continue;
        cost_t cp = c_pi(v, e);
        if (cp < 0) {
            if (lookAhead(e.v)) {
                i--;
                continue;
            }
            push(v, e, excess[v], true);
            if (excess[v] == 0) return;
        } else
            delta = min(delta, cp);
    }
    relabel(v, delta);
    stk.push(v);
};

zero_stl(pi, N);
zero_stl(excess, N);
for (int i = 0; i < N; i++)

```

```

        for (auto &e : g[i]) minCost += e.c * e.d, e.d *=
            MAX_N + 1, eps = max(eps, e.d);
    maxFlow = getMaxFlow(N, S, T);
    while (eps > 1) {
        eps /= SCALE;
        if (eps < 1) eps = 1;
        stk = stack<int, vector<int>>>();
        for (int v = 0; v < N; v++)
            for (auto &e : g[v])
                if (c_pi(v, e) < 0 && e.c > 0) push(v, e, e.c,
                    false);
        for (int v = 0; v < N; v++)
            if (excess[v] > 0) stk.push(v);
        while (stk.size()) {
            int top = stk.top();
            stk.pop();
            discharge(top);
        }
    }
    for (int v = 0; v < N; v++)
        for (auto &e : g[v]) e.d /= MAX_N + 1, minCost -= e
            .c * e.d;
    minCost = minCost / 2 + negativeSelfLoop;
    return {maxFlow, minCost};
}

};

void solve() {
    CostScalingMCMF<102, int, int, 100, 100> flow;
    int n, m;
    cin >> n >> m;
    int start = 0;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            int inp;
            cin >> inp;
            if (inp) {

```

```

        flow.addEdge(i + 1, n + 1 + j, 1, 0);
        start++;
    } else
        flow.addEdge(i + 1, n + 1 + j, 1, 1);
    }
}
int counta = 0, countb = 0;
for (int i = 0; i < n; i++) {
    int inp;
    cin >> inp;
    counta += inp;
    flow.addEdge(0, i + 1, inp, 0);
}
for (int i = 0; i < m; i++) {
    int inp;
    cin >> inp;
    countb += inp;
    flow.addEdge(n + i + 1, n + m + 1, inp, 0);
}
if (counta != countb) {
    cout << -1 << endl;
    return;
}
pii t = flow.maxflow(102, 0, n + m + 1);
if (t.first != counta) {
    cout << -1 << endl;
    return;
}
cout << t.second + start + t.second - counta << endl;
}

```

MinimumVertexCover.h

Description: Finds a minimum vertex cover in a bipartite graph. The size is the same as the size of a maximum matching, and the complement is a maximum independent set.

"DFSMatching.h"

da4196, 20 lines

```
vi cover(vector<vi>& g, int n, int m) {
```

```

vi match(m, -1);
int res = dfsMatching(g, match);
vector<bool> lfound(n, true), seen(m);
for (int it : match) if (it != -1) lfound[it] = false;
vi q, cover;
rep(i, 0, n) if (lfound[i]) q.push_back(i);
while (!q.empty()) {
    int i = q.back(); q.pop_back();
    lfound[i] = 1;
    for (int e : g[i]) if (!seen[e] && match[e] != -1) {
        seen[e] = true;
        q.push_back(match[e]);
    }
}
rep(i, 0, n) if (!lfound[i]) cover.push_back(i);
rep(i, 0, m) if (seen[i]) cover.push_back(n+i);
assert(sz(cover) == res);
return cover;
}

```

SCC.h

Description: SCC

d54e21, 30 lines

```

struct SCC {
    int n;
    vi val, cc, z;
    vvi comps;
    SCC(vvi& adj) : n(sz(adj)), val(n), cc(n, -1) {
        int timer = 0;
        function<int(int)> dfs = [&](int x) {
            int low = val[x] = ++timer, b;
            z.push_back(x);
            for (auto y : adj[x])
                if (cc[y] < 0)
                    low = min(low, val[y] ?: dfs(y));
            if (low == val[x]) {
                comps.push_back(vi());
            }
        };
    }
};

```

```

    do {
        b = z.back();
        z.pop_back();
        comps.back().push_back(b);
        cc[b] = sz(comps) - 1;
    } while (x != b);
}
return val[x] = low;
};
for (int i = 0; i < n; i++)
    if (cc[i] < 0) dfs(i);
}
int operator[](int i) { return cc[i]; }
int size(int i) { return sz(comps[cc[i]]); }
};

```

Number theory (5)

ModularArithmetic.h

683ef1, 54 lines

```

#define LL int
const long long mod = M;
int euclid(int a, int b, int &x, int &y) {
    if (!b)
        return x = 1, y = 0, a;
    int d = euclid(b, a % b, y, x);
    return y -= a / b * x, d;
}
LL mod_mul(LL a, LL b) {
    a = a % mod;
    b = b % mod;
    return ((a * b) % mod + mod) % mod;
}
LL mod_add(LL a, LL b) {
    a = a % mod;
    b = b % mod;
    return ((a + b) % mod + mod) % mod;
}

```

```

const int MX = 5e5 + 1;
vector<int> inv(MX + 1), fci(MX + 1), fc(MX + 1);
const int Mod = 1e9 + 7;
void Inverses() {
    inv[1] = 1;
    for (int i = 2; i <= MX; i++) {
        inv[i] = Mod - Mod / i * inv[Mod % i] % Mod;
    }
}
void Factorials() {
    fc[0] = fc[1] = 1;
    for (int i = 2; i <= MX; i++) {
        fc[i] = fc[i - 1] * i % Mod;
    }
}
void InverseFactorials() {
    Inverses();
    Factorials();
    fci[1] = fci[0] = 1;
    for (int i = 2; i <= MX; i++) {
        fci[i] = fci[i - 1] * inv[i] % Mod;
    }
}
int nck(int num, int k) {
    if (num < 0 || k < 0 || num < k) return 0;
    else return fc[num] * fci[k] % Mod * fci[num - k] %
        Mod;
}
int BinExpItermod(int a, int b) {
    int ans = 1;
    while (b > 0) {
        if (b & 1) ans = (ans * a) % mod;
        a = (a * a) % mod;
        b = b >> 1;
    }
    return ans;
}

```

MillerRabin.h

Description: MillerRabin

71e4cd, 22 lines

```
u64 mult(u64 a, u64 b, u64 m = M) {
    i64 ret = a * b - m * (u64)(l.L / m * a * b);
    return ret + m * (ret < 0) - m * (ret >= (i64)m);
}

u64 pw(u64 b, u64 e, u64 m = M) {
    u64 ret = 1;
    for (; e; b = mult(b, b, m), e >>= 1)
        if (e & 1) ret = mult(ret, b, m);
    return ret;
}

bool isPrime(u64 n) { // determistic upto 7e^18
    if (n < 2 || n % 6 % 4 != 1) return (n | 1) == 3;
    u64 A[] = {2, 325, 9375, 28178, 450775, 9780504,
        1795265022},
        s = __builtin_ctzll(n - 1), d = n >> s;
    for (u64 a : A) {
        u64 p = pw(a % n, d, n), i = s;
        while (p != 1 && p != n - 1 && a % n && i--)
            p = mult(p, p, n);
        if (p != n - 1 && i != s) return 0;
    }
    return 1;
}
```

Factor.h

Description: Pollard-rho randomized factorization algorithm. Returns prime factors of a number, in arbitrary order (e.g. 2299 -> {11, 19, 11}).

Time: $\mathcal{O}(n^{1/4})$, less for numbers with small factors.

"ModMultLL.h", "MillerRabin.h"

d8d98d, 18 lines

```
ull pollard(ull n) {
    ull x = 0, y = 0, t = 30, prd = 2, i = 1, q;
    auto f = [&](ull x) { return modmul(x, x, n) + i; };
    while (t++ % 40 || __gcd(prd, n) == 1) {
        if (x == y) x = ++i, y = f(x);
```

```
        if ((q = modmul(prd, max(x, y) - min(x, y), n)) prd =
            q;
        x = f(x), y = f(f(y));
    }
    return __gcd(prd, n);
}

vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), all(r));
    return l;
}
```

phiFunction.h

Description: Euler's ϕ function is defined as $\phi(n) := \#$ of positive integers $\leq n$ that are coprime with n . $\phi(1) = 1$, p prime $\Rightarrow \phi(p^k) = (p-1)p^{k-1}$, m, n coprime $\Rightarrow \phi(mn) = \phi(m)\phi(n)$. If $n = p_1^{k_1} p_2^{k_2} \dots p_r^{k_r}$ then $\phi(n) = (p_1-1)p_1^{k_1-1} \dots (p_r-1)p_r^{k_r-1}$. $\phi(n) = n \cdot \prod_{p|n} (1 - 1/p)$.

$\sum_{d|n} \phi(d) = n$, $\sum_{1 \leq k \leq n, \gcd(k, n) = 1} k = n\phi(n)/2, n > 1$

Euler's thm: a, n coprime $\Rightarrow a^{\phi(n)} \equiv 1 \pmod{n}$.

Fermat's little thm: p prime $\Rightarrow a^{p-1} \equiv 1 \pmod{p} \forall a$.

cf7d6d, 8 lines

```
const int LIM = 5000000;
int phi[LIM];

void calculatePhi() {
    rep(i, 0, LIM) phi[i] = i & 1 ? i : i/2;
    for (int i = 3; i < LIM; i += 2) if (phi[i] == i)
        for (int j = i; j < LIM; j += i) phi[j] -= phi[j] / i;
}
```

CRT.h

Description: Chinese Remainder Theorem.

crt(a, m, b, n) computes x such that $x \equiv a \pmod{m}, x \equiv b \pmod{n}$. If $|a| < m$ and $|b| < n$, x will obey $0 \leq x < \text{lcm}(m, n)$. Assumes $mn < 2^{62}$.

Time: $\log(n)$

```
"euclid.h" 04d93a, 7 lines
ll crt(ll a, ll m, ll b, ll n) {
    if (n > m) swap(a, b), swap(m, n);
    ll x, y, g = euclid(m, n, x, y);
    assert((a - b) % g == 0); // else no solution
    x = (b - a) % n * x % n / g * m + a;
    return x < 0 ? x + m*n/g : x;
}
```

spf.h

Description: spf

```
1e547d, 20 lines
int MX = 1e7 + 1;
vi spf(MX + 1, INT32_MAX);
vector<int> is_prime(MX + 1, 1);
void sieve(int n = MX) {
    for (int i = 1; i <= n; i++)
        spf[i] = i;
    is_prime[0] = is_prime[1] = 0;
    int cnt = 1;
    for (int i = 2; i <= n; i++) {
        if (is_prime[i]) {
            for (int j = i * i; j <= n; j += i) {
                is_prime[j] = 0;
                spf[j] = min(i, spf[j]);
            }
            is_prime[i] = cnt;
            cnt++;
        }
    }
    return;
}
```

BitBNS.h

Description: BitBNS

```
793511, 16 lines
// --- Bit Binary Search in  $o(\log(n))$  ---
```

```
const int M = 20;
const int N = 1 << M;

int lower_bound(int val)
{
    int ans = 0, sum = 0;
    for (int i = M - 1; i >= 0; i--)
    {
        int x = ans + (1 << i);
        if (sum + bit[x] < val)
            ans = x, sum += bit[x];
    }

    return ans + 1;
}
```

SomeDP.h

Description: SomeDP

```
ac57b7, 21 lines
// LIS
int lis(vector<int> const &a) {
    int n = a.size();
    const int INF = 1e9;
    vector<int> d(n + 1, INF);
    d[0] = -INF;

    for (int i = 0; i < n; i++) {
        int l = upper_bound(d.begin(), d.end(), a[i]) - d.begin();
        if (d[l - 1] < a[i] && a[i] < d[l])
            d[l] = a[i];
    }

    int ans = 0;
    for (int l = 0; l <= n; l++) {
        if (d[l] < INF)
            ans = l;
    }
}
```

```

    return ans;
}
// or segtree lol

```

sos.h

Description: sos dp

bc3748, 12 lines

```

vector<int> sos_dp(const vector<int>& A) {
    int n = __builtin_ctz(A.size());
    vector<int> F(A.begin(), A.end());
    for(int i = 0; i < n; ++i) {
        for(int mask = 0; mask < (1 << n); ++mask) {
            if(mask & (1 << i)) {
                F[mask] += F[mask ^ (1 << i)];
            }
        }
    }
    return F;
}

```

dnc.h

Description: dnc dp with cost func

d87640, 37 lines

```

auto add = [&](int v) {
    cnt[a[v]]++;
    ans += cnt[a[v]] - 1;
};
auto rem = [&](int v) {
    cnt[a[v]]--;
    ans -= cnt[a[v]];
};

auto getcost = [&](int expl, int expr) {
    while (l > expl) add(--l);
    while (l < expl) rem(l++);
    while (r < expr) add(++r);
    while (r > expr) rem(r--);
    return ans;
}

```

```

};

function<void(int, int, int, int)> calc = [&](int l, int
    r, int optl, int optr) {
    if (l > r) return;
    int mid = (l + r) / 2;
    array<int, 2> best = {LLONG_MAX, -1};
    for (int i = optl; i <= min(mid, optr); i++) {
        int inval = dp1[i] + getcost(i, mid);
        array<int, 2> cur = {inval, i};
        best = min(best, cur);
    }
    int opt = best[1];
    dp2[mid + 1] = best[0];
    calc(l, mid - 1, optl, opt);
    calc(mid + 1, r, opt, optr);
};

fr(i, 0, k) {
    calc(0, n-1, 0, n-1);
    dp1 = dp2;
    dp2 = vi(n+1, 1e15);
}
cout << dp1[n] << endl;

```

Numerical (6)

Determinant.h

Description: Calculates determinant of a matrix. Destroys the matrix.

bd5cec, 15 lines

```

double det(vector<vector<double>>& a) {
    int n = sz(a); double res = 1;
    rep(i, 0, n) {
        int b = i;
        rep(j, i+1, n) if (fabs(a[j][i]) > fabs(a[b][i])) b = j;
        ;
        if (i != b) swap(a[i], a[b]), res *= -1;
        res *= a[i][i];
        if (res == 0) return 0;
    }
}

```

```

    rep(j,i+1,n) {
        double v = a[j][i] / a[i][i];
        if (v != 0) rep(k,i+1,n) a[j][k] -= v * a[i][k];
    }
}
return res;
}

```

FastFourierTransform.h

Description: FastFourierTransform

00ced6, 36 lines

```

typedef complex<double> C;
typedef vector<double> vd;
void fft(vector<C>& a) {
    int n = sz(a), L = 31 - __builtin_clz(n);
    static vector<complex<long double>> R(2, 1);
    static vector<C> rt(2, 1); // (^ 10% faster if double)
    for (static int k = 2; k < n; k *= 2) {
        R.resize(n);
        rt.resize(n);
        auto x = polar(1.0L, acos(-1.0L) / k);
        rep(i, k, 2 * k) rt[i] = R[i] = i & 1 ? R[i / 2] * x
            : R[i / 2];
    }
    vi rev(n);
    rep(i, 0, n) rev[i] = (rev[i / 2] | (i & 1) << L) / 2;
    rep(i, 0, n) if (i < rev[i]) swap(a[i], a[rev[i]]);
    for (int k = 1; k < n; k *= 2)
        for (int i = 0; i < n; i += 2 * k) rep(j, 0, k) {
            C z = rt[j+k] * a[i+j+k]; // (25% faster if hand-
                rolled)
            a[i + j + k] = a[i + j] - z;
            a[i + j] += z;
        }
}
vd conv(const vd& a, const vd& b) {
    if (a.empty() || b.empty()) return {};
    vd res(sz(a) + sz(b) - 1);

```

```

int L = 32 - __builtin_clz(sz(res)), n = 1 << L;
vector<C> in(n), out(n);
copy(all(a), begin(in));
rep(i, 0, sz(b)) in[i].imag(b[i]);
fft(in);
for (C& x : in) x *= x;
rep(i, 0, n) out[i] = in[-i & (n - 1)] - conj(in[i]);
fft(out);
rep(i, 0, sz(res)) res[i] = imag(out[i]) / (4 * n);
return res;
}

```

NTT.h

Description: NTT

f9d990, 49 lines

```

/* Description: Can be used for convolutions modulo
    specific nice primes of the form 2^a b+1, where the
    convolution result has size at most 2^a
    * (125000001 << 3) + 1 = 1e9 + 7, therefore do not use
    this for M = 1e9 + 7.
*/
// Requires mod func
const int M = 998244353;
const int root = 3;
// (119 << 23) + 1, root = 3; // for M = 998244353
void ntt(int* x, int* temp, int* roots, int N, int skip)
{
    if (N == 1) return;
    int n2 = N / 2;
    ntt(x, temp, roots, n2, skip * 2);
    ntt(x + skip, temp, roots, n2, skip * 2);
    for (int i = 0; i < N; i++) temp[i] = x[i * skip];
    for (int i = 0; i < n2; i++) {
        int s = temp[2 * i], t = temp[2 * i + 1] * roots[skip
            * i];
        x[skip * i] = (s + t) % M;
        x[skip * (i + n2)] = (s - t) % M;
    }
}

```



```

}
void ntt(vi& x, bool inv = false) {
    int e = pw(root, (M - 1) / sz(x));
    if (inv) e = pw(e, M - 2);
    vi roots(sz(x), 1), temp = roots;
    for (int i = 1; i < sz(x); i++) roots[i] = roots[i - 1]
        * e % M;
    ntt(&x[0], &temp[0], &roots[0], sz(x), 1);
}
// Usage: just pass the two coefficients list to get a*b
// (modulo M)
vi conv(vi a, vi b) {
    int s = sz(a) + sz(b) - 1;
    if (s <= 0) return {};
    int L = s > 1 ? 32 - __builtin_clzll(s - 1) : 0, n = 1
        << L;
    if (s <= 200) { // (factor 10 optimization for |a|, |b|
        = 10)
        vi c(s);
        for (int i = 0; i < sz(a); i++)
            for (int j = 0; j < sz(b); j++)
                c[i + j] = (c[i + j] + a[i] * b[j]) % M;
        return c;
    }
    a.resize(n);
    ntt(a);
    b.resize(n);
    ntt(b);
    vi c(n);
    int d = pw(n, M - 2);
    for (int i = 0; i < n; i++) c[i] = a[i] * b[i] % M * d
        % M;
    ntt(c, true);
    c.resize(s);
    return c;
}

```

Polynomial.h

c9b7b0, 17 lines

```

struct Poly {
    vector<double> a;
    double operator()(double x) const {
        double val = 0;
        for (int i = sz(a); i--;) (val *= x) += a[i];
        return val;
    }
    void diff() {
        rep(i, 1, sz(a)) a[i-1] = i*a[i];
        a.pop_back();
    }
    void divroot(double x0) {
        double b = a.back(), c; a.back() = 0;
        for (int i=sz(a)-1; i--;) c = a[i], a[i] = a[i+1]*x0+b
            , b=c;
        a.pop_back();
    }
};

```

LinearRecurrence.h

Description: Generates the k 'th term of an n -order linear recurrence $S[i] = \sum_j S[i-j-1]tr[j]$, given $S[0 \dots \geq n-1]$ and $tr[0 \dots n-1]$. Faster than matrix multiplication. Useful together with Berlekamp–Massey.

Usage: linearRec({0, 1}, {1, 1}, k) // k 'th Fibonacci number

Time: $\mathcal{O}(n^2 \log k)$

f4e444, 22 lines

```

typedef vector<ll> Poly;
ll linearRec(Poly S, Poly tr, ll k) {
    int n = sz(tr);
    auto combine = [&](Poly a, Poly b) {
        Poly res(n * 2 + 1);
        rep(i, 0, n+1) rep(j, 0, n+1)
            res[i + j] = (res[i + j] + a[i] * b[j]) % mod;
        for (int i = 2 * n; i > n; --i) rep(j, 0, n)
            res[i - 1 - j] = (res[i - 1 - j] + res[i] * tr[j])
                % mod;
    };
}

```

```

    res.resize(n + 1);
    return res;
};
Poly pol(n + 1), e(pol);
pol[0] = e[1] = 1;
for (++k; k; k /= 2) {
    if (k % 2) pol = combine(pol, e);
    e = combine(e, e);
}
ll res = 0;
rep(i, 0, n) res = (res + pol[i + 1] * S[i]) % mod;
return res;
}

```

Strings (7)

hash.h

Description: hash

52553f, 19 lines

```

template <int MOD, int P> struct RH {
    // using H1 = RH<1000000007, 91138233>;
    // using H2 = RH<1000000009, 97266353>;
    vector<long long> h, p;
    RH(const string &s) {
        int n = s.size();
        h.resize(n + 1, 0);
        p.resize(n + 1, 0);
        p[0] = 1;
        for (int i = 0; i < n; i++) {
            h[i + 1] = (h[i] * P + s[i]) % MOD;
            p[i + 1] = p[i] * P % MOD;
        }
    }
    long long get(int l, int r) { // [l, r]
        long long res = (h[r + 1] - h[l] * p[r - l + 1]) %
            MOD;
        return res < 0 ? res + MOD : res;
    }
}

```

```
};
```

kmp.h

Description: kmp

1c4d12, 28 lines

```

vector<int> prefix_function(string s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j])
            j = pi[j - 1];
        if (s[i] == s[j])
            j++;
        pi[i] = j;
    }
    return pi;
}

vector<int> KMP(string text, string pattern) {
    string s = pattern + "#" + text;
    vector<int> pi = prefix_function(s);
    vector<int> matches;
    int p = pattern.length();

    for (int i = 0; i < s.length(); i++) {
        if (pi[i] == p) {
            int match_pos = i - 2 * p;
            matches.push_back(match_pos); // 0-based index in
                text
        }
    }
    return matches;
}

```

Trie.h

Description: Trie

009545, 77 lines

```

class TrieNode {
public:
    unordered_map<char, TrieNode *> children;
    bool isEndOfWord;

    TrieNode() : isEndOfWord(false) {}
};

class Trie {
private:
    TrieNode *root;

public:
    Trie() { root = new TrieNode(); }
    void insert(const string &word) {
        TrieNode *node = root;
        for (char ch : word) {
            if (node->children.find(ch) == node->children.end())
                node->children[ch] = new TrieNode();
            node = node->children[ch];
        }
        node->isEndOfWord = true;
    }
    bool search(const string &word) {
        TrieNode *node = root;
        for (char ch : word) {
            if (node->children.find(ch) == node->children.end())
                return false;
            node = node->children[ch];
        }
        return node->isEndOfWord;
    }
    bool startsWith(const string &prefix) {
        TrieNode *node = root;

```

```

        for (char ch : prefix) {
            if (node->children.find(ch) == node->children.end())
                return false;
            node = node->children[ch];
        }
        return true;
    }
};

// for bits
struct trieobject {
    trieobject() {
        children[0] = NULL;
        children[1] = NULL;
        numelems = 0;
    };

    struct trieobject* children[2];
    int numelems;
};

struct trie {
    trieobject base;
    trie() {
        trieobject base;
    }
    void add(int x) {
        int pow2 = (1ll << 31ll);
        trieobject* temp = &base;
        while (pow2 > 0) {
            if (temp->children[1 && (x & pow2)] == NULL) {
                temp->children[1 && (x & pow2)] = new trieobject;
            }
            temp->children[1 && (x & pow2)]->numelems++;
            temp = temp->children[1 && (x & pow2)];
        }
    }
};

```

```

        pow2 /= 2;
    }
}
// ADD FUNCTION BELOW

};

```

Manacher.h

Description: Manacher

cd719d, 16 lines

```

/* Description: p[0][i] = half length of longest even
palindrome behind pos i,
p[1][i] = longest odd with center at pos i (half rounded
down). */
array<vi, 2> manacher(const string& s) {
    int n = sz(s);
    array<vi, 2> p = {vi(n + 1), vi(n)};
    for (int z = 0; z < 2; z++) {
        for (int i = 0, l = 0, r = 0; i < n; i++) {
            int t = r - i + !z;
            if (i < r) p[z][i] = min(t, p[z][l + t]);
            int L = i - p[z][i], R = i + p[z][i] - !z;
            while (L >= 1 && R + 1 < n && s[L - 1] == s[R + 1])
                p[z][i]++, L--, R++;
            if (R > r) l = L, r = R;
        }
        return p;
    }
}

```

SuffixArray.h

Description: SuffixArray

c54b5a, 32 lines

```

/* Builds suffix array for a string.
\texttt{sa[i]} is the starting index of the suffix which
is $i$'th in the sorted suffix array.
The returned vector is of size $n+1$, and \texttt{sa[0]} =
n}.

```

The `\texttt{lcp}` array contains longest common prefixes for neighbouring strings in the suffix array:
`\texttt{lcp[i] = lcp(sa[i], sa[i-1])}`, `\texttt{lcp[0] = 0}` }.

The input string must not contain any zero bytes.
Time: $O(n \log n)$ */

```

#define rep(i, j, k) for (int i = j; i < k; i++)
struct SuffixArray {
    vi sa, lcp;
    SuffixArray(string& s, int lim = 256) { // or
        basic_string<int>
        int n = sz(s) + 1, k = 0, a, b;
        vi x(all(s)), y(n), ws(max(n, lim));
        x.push_back(0), sa = lcp = y, iota(all(sa), 0);
        for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim
            = p) {
            p = j, iota(all(y), n - j);
            rep(i, 0, n) if (sa[i] >= j) y[p++] = sa[i] - j;
            fill(all(ws), 0);
            rep(i, 0, n) ws[x[i]]++;
            rep(i, 1, lim) ws[i] += ws[i - 1];
            for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
            swap(x, y), p = 1, x[sa[0]] = 0;
            rep(i, 1, n) a = sa[i - 1], b = sa[i], x[b] = (y[a]
                == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
        for (int i = 0, j; i < n - 1; lcp[x[i++]] = k)
            for (k && k--, j = sa[x[i] - 1];
                s[i + k] == s[j + k]; k++)
                ;
    }
};

```

Geometry (8)

8.1 Geometric primitives

Point.h

Description: Class to handle points in the plane. T can be e.g. double or long long. (Avoid int.)

```

47ec0a, 28 lines
template <class T> int sgn(T x) { return (x > 0) - (x < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) < tie(p.x,p.y); }
    bool operator==(P p) const { return tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
    T cross(P a, P b) const { return (a-*this).cross(b-*this); }
    T dist2() const { return x*x + y*y; }
    double dist() const { return sqrt((double)dist2()); }
    // angle to x-axis in interval [-pi, pi]
    double angle() const { return atan2(y, x); }
    P unit() const { return *this/dist(); } // makes dist() = 1
    P perp() const { return P(-y, x); } // rotates +90 degrees
    P normal() const { return perp().unit(); }
    // returns point rotated 'a' radians ccw around the origin

```

```

P rotate(double a) const {
    return P(x*cos(a)-y*sin(a), x*sin(a)+y*cos(a)); }
friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};

```

ConvexHull.h

Description:

Returns a vector of the points of the convex hull in counter-clockwise order. Points on the edge of the hull between two other points are not considered part of the hull.

Time: $\mathcal{O}(n \log n)$



```

"Point.h"
310954, 13 lines
typedef Point<ll> P;
vector<P> convexHull(vector<P> pts) {
    if (sz(pts) <= 1) return pts;
    sort(all(pts));
    vector<P> h(sz(pts)+1);
    int s = 0, t = 0;
    for (int it = 2; it--; s = --t, reverse(all(pts)))
        for (P p : pts) {
            while (t >= s + 2 && h[t-2].cross(h[t-1], p) <= 0)
                t--;
            h[t++] = p;
        }
    return {h.begin(), h.begin() + t - (t == 2 && h[0] == h[1])};
}

```

ClosestPair.h

Description: Finds the closest pair of points.

Time: $\mathcal{O}(n \log n)$

```

"Point.h"
ac41a6, 17 lines
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;

```

```
sort(all(v), [](P a, P b) { return a.y < b.y; });
pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
int j = 0;
for (P p : v) {
    P d{1 + (ll)sqrt(ret.first), 0};
    while (v[j].y <= p.y - d.x) S.erase(v[j++]);
    auto lo = S.lower_bound(p - d), hi = S.upper_bound(p
        + d);
    for (; lo != hi; ++lo)
        ret = min(ret, {(*lo - p).dist2(), {*lo, p}});
    S.insert(p);
}
return ret.second;
}
```