Features

10-Port Industrial-grade USB 3.2 SuperSpeed hub

Compatible with Windows 10 and Windows 11

Plug and play, no drivers required

Supports USB 3.2 Gen 1 SuperSpeed

Backwards compatible with USB 2.0 devices

ESD and Surge protection

Mountable on or under a desk, to a wall, or DIN rail

10-Port USB Hub

Avtec offers the 10-Port USB Hub, providing increased connectivity and reduced cable clutter.

The industrial-grade 10-Port USB Hub expands connectivity by providing 10 separate USB connections. The hub mounts easily to the dispatcher's desk or to a backroom rack using the included mounting hardware.

Product includes the following:

- 10-Port industrial-grade USB 3.2 Gen 1 SuperSpeed hub
- Terminal block power adapter with 4-foot cord
- 5-foot power cord
- 6-foot USB 3.2 cable
- DIN rail-mounting hardware
- Wall-mounting hardware

NOTE
To ensure adequate power for Avtec peripherals, Avtec does not recommend battery charging on any USB Hub which connects Avtec USB peripherals to a PC using Avtec dispatching software.

Phone: 1-803.358.3600 • Fax: 1-803.358.3636
100 Innovation Place • Lexington SC 29072 USA
avtecinc.com • sales@avtecinc.com

SPECIFICATIONS

GENERAL SPECIFICATIONS

USB Interface: USB 3.2 Gen 1 high-speed (rates up to 5 Gbps or 640 MBps), backwards compatible with USB 2.0 and USB 1.1 devices

Power Mode: External power supply (USB power not recommended)

Power Supply: 20Vdc 1.4A 65W 2-pin terminal block power adapter with 4-foot cable, 5-foot power cord

Compatibility: Windows 10, Windows 11

Box Contents: 10-Port industrial-grade USB 3.2 SuperSpeed hub, 20Vdc 1.4A 65W power adapter with 4-foot cable, 5-foot power cord, 6-foot USB 3.2 A to B cable to connect hub and host computer, DIN rail brackets and mounting hardware

Performance: ESD and Surge protection (350W)

UASP Support: Yes

POWER SPECIFICATIONS

Input Voltage: 100 - 240 AC

Input Current: 1.4A

Output Voltage: 20Vdc

Output Current: 3.25A

Plug Type: Terminal Block 2-Wire

Power Consumption: 65W

PHYSICAL SPECIFICATIONS

Color: Black

Material: Steel

Form Factor: Industrial

Weight: 12.4 oz (352 g)

Dimensions (L × W × H): 7.8 in × 2.2 in × 1.2 in (19.8 cm × 5.5 cm × 3 cm)

ENVIRONMENTAL

Operating Temperature Range: 32°F to 158°F (0°C to 70°C)

Storage Temperature Range: -4°F to 185°F (-20°C to 85°C)

Relative Humidity: 5% to 95% RH, non-Condensing

COMPLIANCE

TAA, CE (Europe), RCM, RoHS, FCC, REACH, FCC (USA), WEEE, DOC

Phone: 1-803.358.3600 • Fax: 1-803.358.3636
100 Innovation Place • Lexington SC 29072 USA
avtecinc.com • sales@avtecinc.com