

CPSC 240: Computer Organization and Assembly Language

Assignment 07, Fall Semester 2023

CWID: 885857847 Name: Kush
Patel

1. Download the "CPSC-240 Assignment07.docx" document.
2. Design the "input.asm" program, input 9 values from 1 to 9 from the keyboard, find out the multiples of 3 from the input values, and display the multiples of 3 in the terminal emulator window. The corresponding C/C++ code is as follows:

```
char msg1[] = "Input a number (1~9): ";
char msg2[] = " is Multiple of 3.";
char buffer;
char num;
char ascii[10];

register int r10 = 0;
do {
    cout << msg1;
    cin >> buffer;
    ascii[r10] = buffer;
    r10++;
} while(r10 < 9);
r10 = 0;
do {
    num = atoi(ascii[r10]);
    if(num%3 == 0) {
        cout << ascii[r10] << msg2;
    }
    r10++;
} while(r10 < 9);
```

3. Assemble the "input.asm" file and link the "input.o" file to get the "input" executable file.
4. Run the "input" file to display the input **value** and **multiple of 3** in Terminal Emulator window.
5. Insert source code (input.asm) and simulation results (Terminal Emulator window) at the bottom of the document. Write an analysis to verify the simulation results.
6. Save the file in pdf format and submit the pdf file to Canvas before 23:59 pm on 11/02/2023.

Sample output:

```
899486336@vclvm011515-225-235: ~/Desktop/ex7
File Edit View Search Terminal Help
899486336@vclvm011515-225-235:~/Desktop/ex7$ ./ex7
Input a number (1~9) : 1
Input a number (1~9) : 2
Input a number (1~9) : 3
Input a number (1~9) : 4
Input a number (1~9) : 5
Input a number (1~9) : 6
Input a number (1~9) : 7
Input a number (1~9) : 8
Input a number (1~9) : 9
3 is multiple of 3
6 is multiple of 3
9 is multiple of 3
899486336@vclvm011515-225-235:~/Desktop/ex7$
```

Alternatively, the corresponding C/C++ code can be replaced as follows:

```
char num;
char buffer;
char msg1[] = "Input a number (1~9): ";
char msg2[] = " is multiple of 3.";

register int r10 = 0;
do {
    cout << msg1;
    cin >> buffer;
    num = atoi(buffer);
    if(num%3 == 0) {
        cout << buffer << msg2;
    }
    r10++;
} while(r10 < 9);
```

Sample output:

```
899486336@vclvm011515-225-235: ~/Desktop/ex7
File Edit View Search Terminal Help
899486336@vclvm011515-225-235:~/Desktop/ex7$ ./ex7
Input a number (1~9) : 1
Input a number (1~9) : 2
Input a number (1~9) : 3
3 is multiple of 3
Input a number (1~9) : 4
Input a number (1~9) : 5
Input a number (1~9) : 6
6 is multiple of 3
Input a number (1~9) : 7
Input a number (1~9) : 8
Input a number (1~9) : 9
9 is multiple of 3
899486336@vclvm011515-225-235:~/Desktop/ex7$
```

[Insert input.asm here]

```

1
2 section .bss
3     num    resb    1                ;reserve 1-byte for num
4     buffer resb    2                ;reserve 1-byte for buffer
5
6 section .data
7     msg     db      "Input a number (0~9): "    ;input message
8     mul_3    db      " is an multiple of 3", 10 ;even message
9
10
11 section .text
12     global _start
13 _start:
14     mov     r10, 0
15 a_loop:
16     ; cout << msg
17     mov     rax, 1                ;SYS_write
18     mov     rdi, 1                ;write to STD_OUT
19     mov     rsi, msg              ;address of msg
20     mov     rdx, 22               ;22 character to write
21     syscall                       ;calling system services
22
23     ; cin >> num
24     mov     rax, 0                ;SYS_read
25     mov     rdi, 0                ;read from STD_IN
26     mov     rsi, buffer           ;address of the buffer
27     mov     rdx, 2                ;input length = 1
28     syscall                       ;calling system services
29     mov     al, byte[buffer]       ;al = buffer (ex: '5'=35h)
30     and     al, 0fh               ;al = block bit7~4 (ex: 05h)
31     mov     byte[num], al         ;num = al (ex: num=05h)
32
33     ; if(num%2 == 0)
34     mov     ah, 0
35     mov     al, byte[num]
36     mov     bl, 3
37     div     bl
38     cmp     ah, 0
39     jnz     done
40     ; cout << num
41     mov     rax, 1                ;SYS_write
42     mov     rdi, 1                ;where to write
43     mov     rsi, buffer           ;address of buffer
44     mov     rdx, 1                ;1 character to write
45     syscall                       ;calling system services
46     ; cout << even
47     mov     rax, 1                ;SYS_write

```

16	; cout << msg	
17	mov rax, 1	;SYS_write
18	mov rdi, 1	;write to STDOUT
19	mov rsi, msg	;address of msg
20	mov rdx, 22	;22 character to write
21	syscall	;calling system services
22		
23	; cin >> num	
24	mov rax, 0	;SYS_read
25	mov rdi, 0	;read from STD_IN
26	mov rsi, buffer	;address of the buffer
27	mov rdx, 2	;input length = 1
28	syscall	;calling system services
29	mov al, byte[buffer]	;al = buffer (ex: '5'=35h)
30	and al, 0fh	;al = block bit7~4 (ex: 05h)
31	mov byte[num], al	;num = al (ex: num=05h)
32		
33	; if(num%2 == 0)	
34	mov ah, 0	;ah=0
35	mov al, byte[num]	;al=num
36	mov bl, 3	;bl=2
37	div bl	;ah=ax%bl, al=ax/bl
38	cmp ah, 0	;compare ah,0
39	jnz done	;if(rem!=0) goto odd_num
40	; cout << num	
41	mov rax, 1	;SYS_write
42	mov rdi, 1	;where to write
43	mov rsi, buffer	;address of buffer
44	mov rdx, 1	;1 character to write
45	syscall	;calling system services
46	; cout << even	
47	mov rax, 1	;SYS_write
48	mov rdi, 1	;where to write
49	mov rsi, mul_3	;address of num
50	mov rdx, 22	;18 character to write
51	syscall	;calling system services
52	jmp done	;jump to done
53	; else	
54		
55	done:	
56	inc r10	
57	cmp r10, 9	
58	jl a_loop	
59	mov rax, 60	;terminate excuting process
60	mov rdi, 0	;exit status
61	syscall	;calling system services

[Insert input simulation result here]

```

Warning: Cannot convert string "-*-symbol-*-*-*-*-*120-*-*-*-*adobe-*" to type
FontStruct
Warning: Could not load font "-*-lucidatypewriter-medium-*-*-*-*120-*-*-*-*iso
8859-*", using font "fixed" instead
Warning: Could not load font "-*-lucidatypewriter-medium-r-*-*-*-*120-*-*-*-*iso
8859-*", using font "fixed" instead
Warning: Could not load font "-*-lucidatypewriter-bold-*-*-*-*120-*-*-*-*iso88
59-*", using font "fixed" instead
student@tuffix-vm:~/Desktop/input$ ./input
Input a number (0~9): 0
Input a number (0~9): 1
Input a number (0~9): 2
Input a number (0~9): 3
3 is an multiple of 3
Input a number (0~9): 4
Input a number (0~9): 5
Input a number (0~9): 6
6 is an multiple of 3
Input a number (0~9): 7
Input a number (0~9): 8
student@tuffix-vm:~/Desktop/input$ 9
9: command not found
student@tuffix-vm:~/Desktop/input$

```

```

student@tuffix-vm:~$ cd Desktop
student@tuffix-vm:~/Desktop$ cd input
student@tuffix-vm:~/Desktop/input$ ./input
Input a number (0~9): 9
9 is an multiple of 3
Input a number (0~9): 10
Input a number (0~9): Input a number (0~9): 12
Input a number (0~9): Input a number (0~9): 16
Input a number (0~9): Input a number (0~9): 16
Input a number (0~9): student@tuffix-vm:~/Desktop/input$
4: command not found
student@tuffix-vm:~/Desktop/input$

```

[Insert input simulation result verification here]

```

15 {
16 char num;
17 char buffer;
18 char msg1[] = "Input a number (1~9): ";
19 char msg2[] = " is multiple of 3.";
20
21 register int r10 = 0;
22 do {
23     cout << msg1;
24     cin >> buffer;
25     num = buffer;
26     if(num%3 == 0) {
27         cout << buffer << msg2;
28     }
29     r10++;
30 } while(r10 < 9);
31
32     return 0;
33 }
34

```



```

nput a number (1~9): 1
nput a number (1~9): 2
nput a number (1~9): 3
 is multiple of 3.Input a number (1~9): 4
nput a number (1~9): 5
nput a number (1~9): 6

```

```

19 char msg2[] = " is multiple of 3.";
20
21 register int r10 = 0;
22 do {
23     cout << msg1;
24     cin >> buffer;
25     num = buffer;
26     if(num%3 == 0) {
27         cout << buffer << msg2;
28     }
29     r10++;
30 } while(r10 < 9);
31
32     return 0;
33 }
34

```

Input a number (1~9): 6
 6 is multiple of 3. Input a number (1~9): 7
 Input a number (1~9): 8
 Input a number (1~9): 9
 9 is multiple of 3.