
MODULE *P4RuntimeElection*

EXTENDS *Naturals, FiniteSets, Sequences, TLC*

The set of all *ONOS* nodes

CONSTANTS *Nodes*

Stream states

CONSTANTS *Open, Closed*

Master arbitration message types

CONSTANTS *MasterArbitrationUpdate*

Write message types

CONSTANTS *WriteRequest, WriteResponse*

Response status constants

CONSTANTS *Ok, AlreadyExists, PermissionDenied*

Empty value

CONSTANT *Nil*

The current state of mastership elections

VARIABLES *term, master, backups*

The current mastership event queue for each node

VARIABLE *events*

The current mastership state for each node

VARIABLE *masterships*

Whether the node has received a *MasterArbitrationUpdate* indicating it is the current master

VARIABLE *isMaster*

The state of all streams and their requests and responses

VARIABLE *streams, requests, responses*

The current set of elections for the switch, the greatest of which is the current master

VARIABLE *elections*

Counting variables used to enforce state constraints

VARIABLES *mastershipChanges, streamChanges, messageCount*

A sequence of successful writes to the switch used for model checking

VARIABLE *writes*

Mastership/consensus related variables

mastershipVars \triangleq $\langle term, master, backups, mastershipChanges \rangle$

Node related variables

$nodeVars \triangleq \langle events, masterships, isMaster \rangle$

Stream related variables

$streamVars \triangleq \langle streams, streamChanges \rangle$

Message related variables

$messageVars \triangleq \langle requests, responses, messageCount \rangle$

Device related variables

$deviceVars \triangleq \langle elections, writes \rangle$

A sequence of all variables

$vars \triangleq \langle mastershipVars, nodeVars, streamVars, messageVars, deviceVars \rangle$

Helpers

Returns a sequence with the head removed

$Pop(q) \triangleq SubSeq(q, 2, Len(q))$

Returns a sequences with the element at the given index removed

$Drop(q, i) \triangleq SubSeq(q, 1, i - 1) \circ SubSeq(q, i + 1, Len(q))$

Returns the set of values in f

$Range(f) \triangleq \{f[x] : x \in \text{DOMAIN } f\}$

Returns the maximum value from a set or undefined if the set is empty

$Max(s) \triangleq \text{CHOOSE } x \in s : \forall y \in s : x \geq y$

Messaging between the *Nodes* and the device are modelled on *TCP*. For each node, a request and response sequence provides ordered messaging between the two points. Requests and responses are always received from the head of the queue and are never duplicated or reordered, and request and response queues only last the lifetime of the stream. When a stream is closed, all that stream's requests and responses are lost.

Sends request 'm' on the stream for node 'n'

$SendRequest(n, m) \triangleq$
 $\wedge requests' = [requests \text{ EXCEPT } ![n] = Append(requests[n], m)]$
 $\wedge messageCount' = messageCount + 1$

Indicates whether any requests are in the queue for node 'n'

$HasRequest(n, t) \triangleq Len(requests[n]) > 0 \wedge requests[n][1].type = t$

Returns the next request in the queue for node 'n'

$NextRequest(n) \triangleq requests[n][1]$

Discards the request at the head of the queue for node 'n'

$DiscardRequest(n) \triangleq requests' = [requests \text{ EXCEPT } ![n] = Pop(requests[n])]$

Sends response 'm' on the stream for node 'n'

$$\text{SendResponse}(n, m) \triangleq$$

$$\wedge \text{responses}' = [\text{responses} \text{ EXCEPT } ![n] = \text{Append}(\text{responses}[n], m)]$$

$$\wedge \text{messageCount}' = \text{messageCount} + 1$$

Indicates whether any responses are in the queue for node 'n'

$$\text{HasResponse}(n, t) \triangleq \text{Len}(\text{responses}[n]) > 0 \wedge \text{responses}[n][1].\text{type} = t$$

Returns the next response in the queue for node 'n'

$$\text{NextResponse}(n) \triangleq \text{responses}[n][1]$$

Discards the response at the head of the queue for node 'n'

$$\text{DiscardResponse}(n) \triangleq \text{responses}' = [\text{responses} \text{ EXCEPT } ![n] = \text{Pop}(\text{responses}[n])]$$

This section models mastership arbitration on the controller side. Mastership election occurs in two distinct types of state changes. One state change occurs to change the mastership in the consensus layer, and the other occurs when a node actually learns of the mastership change. Nodes will always learn of mastership changes in the order in which they occur, and nodes will always learn of a mastership change. This, of course, is not representative of practice but is sufficient for modelling the mastership election algorithm.

Adds a node to the mastership election

$$\text{JoinMastershipElection}(n) \triangleq$$

$$\wedge \vee \wedge \text{master} = \text{Nil}$$

$$\wedge \text{term}' = \text{term} + 1$$

$$\wedge \text{master}' = n$$

$$\wedge \text{backups}' = \langle \rangle$$

$$\wedge \text{events}' = [i \in \text{Nodes} \mapsto \text{Append}(\text{events}[i], [$$

$$\text{term} \mapsto \text{term}',$$

$$\text{master} \mapsto \text{master}',$$

$$\text{backups} \mapsto \text{backups}'])]$$

$$\vee \wedge \text{master} \neq \text{Nil}$$

$$\wedge \text{master} \neq n$$

$$\wedge n \notin \text{Range}(\text{backups})$$

$$\wedge \text{backups}' = \text{Append}(\text{backups}, n)$$

$$\wedge \text{events}' = [i \in \text{Nodes} \mapsto \text{Append}(\text{events}[i], [$$

$$\text{term} \mapsto \text{term},$$

$$\text{master} \mapsto \text{master},$$

$$\text{backups} \mapsto \text{backups}'])]$$

$$\wedge \text{UNCHANGED } \langle \text{term}, \text{master} \rangle$$

$$\wedge \text{mastershipChanges}' = \text{mastershipChanges} + 1$$

$$\wedge \text{UNCHANGED } \langle \text{masterships}, \text{isMaster}, \text{streamVars}, \text{messageVars}, \text{deviceVars} \rangle$$

Removes a node from the mastership election

$$\text{LeaveMastershipElection}(n) \triangleq$$

$$\wedge \vee \wedge \text{master} = n$$

$$\wedge \vee \wedge \text{Len}(\text{backups}) > 0$$

$$\begin{aligned}
& \wedge term' = term + 1 \\
& \wedge master' = backups[1] \\
& \wedge backups' = Pop(backups) \\
& \wedge events' = [i \in Nodes \mapsto Append(events[i], [\\
& \qquad \qquad \qquad term \mapsto term', \\
& \qquad \qquad \qquad master \mapsto master', \\
& \qquad \qquad \qquad backups \mapsto backups'])] \\
& \vee \wedge Len(backups) = 0 \\
& \wedge master' = Nil \\
& \wedge UNCHANGED \langle term, backups, events \rangle \\
& \vee \wedge n \in Range(backups) \\
& \wedge backups' = Drop(backups, CHOOSE j \in DOMAIN backups : backups[j] = n) \\
& \wedge UNCHANGED \langle term, master, events \rangle \\
& \wedge mastershipChanges' = mastershipChanges + 1 \\
& \wedge UNCHANGED \langle masterships, isMaster, streamVars, messageVars, deviceVars \rangle
\end{aligned}$$

Sets the current master to node 'n' if it's not already set

$$\begin{aligned}
SetMastership(n) & \triangleq \\
& \vee \wedge master = n \\
& \wedge UNCHANGED \langle mastershipVars \rangle \\
& \vee \wedge master \neq n \\
& \wedge term' = term + 1 \\
& \wedge master' = n \\
& \wedge \vee \wedge n \in Range(backups) \\
& \wedge backups' = Drop(backups, CHOOSE j \in DOMAIN backups : backups[j] = n) \\
& \vee \wedge n \notin Range(backups) \\
& \wedge UNCHANGED \langle backups \rangle \\
& \wedge mastershipChanges' = mastershipChanges + 1
\end{aligned}$$

Receives a mastership change event from the consensus layer on node 'n'

$$\begin{aligned}
LearnMastership(n) & \triangleq \\
& \wedge Len(events[n]) > 0 \\
& \wedge LET e \triangleq events[n][1] \\
& \qquad m \triangleq masterships[n] \\
& IN \\
& \vee \wedge e.term > m.term \\
& \wedge masterships' = [masterships EXCEPT ![n] = [\\
& \qquad \qquad \qquad term \mapsto e.term, \\
& \qquad \qquad \qquad master \mapsto e.master, \\
& \qquad \qquad \qquad backups \mapsto e.backups, \\
& \qquad \qquad \qquad sent \mapsto FALSE]] \\
& \vee \wedge e.term = m.term \\
& \wedge masterships' = [masterships EXCEPT ![n] = [\\
& \qquad \qquad \qquad term \mapsto e.term, \\
& \qquad \qquad \qquad master \mapsto e.master,
\end{aligned}$$

$$\begin{aligned}
& \text{backups} \mapsto e.\text{backups}, \\
& \text{sent} \mapsto m.\text{sent}] \\
& \wedge \text{events}' = [\text{events} \text{ EXCEPT } ![n] = \text{Pop}(\text{events}[n])] \\
& \wedge \text{UNCHANGED } \langle \text{mastershipVars}, \text{isMaster}, \text{streamVars}, \text{messageVars}, \text{deviceVars} \rangle
\end{aligned}$$

Notifies the device of node 'n' mastership info if it hasn't already been sent

$\text{SendMasterArbitrationUpdateRequest}(n) \triangleq$

$$\begin{aligned}
& \wedge \text{streams}[n] = \text{Open} \\
& \wedge \text{LET } m \triangleq \text{masterships}[n] \\
& \text{IN} \\
& \quad \wedge m.\text{term} > 0 \\
& \quad \wedge \neg m.\text{sent} \\
& \quad \wedge \vee \wedge m.\text{master} = n \\
& \quad \quad \wedge \text{SendRequest}(n, [\\
& \quad \quad \quad \text{type} \mapsto \text{MasterArbitrationUpdate}, \\
& \quad \quad \quad \text{election_id} \mapsto m.\text{term} + \text{Cardinality}(\text{Nodes}), \\
& \quad \quad \quad \text{term} \mapsto m.\text{term}]) \\
& \quad \vee \wedge m.\text{master} \neq n \\
& \quad \quad \wedge n \in \text{Range}(m.\text{backups}) \\
& \quad \quad \wedge \text{SendRequest}(n, [\\
& \quad \quad \quad \text{type} \mapsto \text{MasterArbitrationUpdate}, \\
& \quad \quad \quad \text{election_id} \mapsto m.\text{term} + \text{Cardinality}(\text{Nodes}) - \text{CHOOSE } i \in \text{DOMAIN } m.\text{backups} : m.\text{backups}[i], \\
& \quad \quad \quad \text{term} \mapsto m.\text{term}]) \\
& \quad \wedge \text{masterships}' = [\text{masterships} \text{ EXCEPT } ![n].\text{sent} = \text{TRUE}] \\
& \quad \wedge \text{UNCHANGED } \langle \text{mastershipVars}, \text{events}, \text{isMaster}, \text{deviceVars}, \text{streamVars}, \text{responses} \rangle
\end{aligned}$$

Receives a master arbitration update response on node 'n'

$\text{ReceiveMasterArbitrationUpdateResponse}(n) \triangleq$

$$\begin{aligned}
& \wedge \text{streams}[n] = \text{Open} \\
& \wedge \text{HasResponse}(n, \text{MasterArbitrationUpdate}) \\
& \wedge \text{LET } m \triangleq \text{NextResponse}(n) \\
& \text{IN} \\
& \quad \vee \wedge m.\text{status} = \text{Ok} \\
& \quad \quad \wedge \text{isMaster}' = [\text{isMaster} \text{ EXCEPT } ![n] = \text{TRUE}] \\
& \quad \quad \wedge \text{SetMastership}(n) \\
& \quad \vee \wedge m.\text{status} = \text{AlreadyExists} \\
& \quad \quad \wedge \text{isMaster}' = [\text{isMaster} \text{ EXCEPT } ![n] = \text{FALSE}] \\
& \quad \quad \wedge \text{UNCHANGED } \langle \text{mastershipVars} \rangle \\
& \quad \wedge \text{DiscardResponse}(n) \\
& \quad \wedge \text{UNCHANGED } \langle \text{events}, \text{masterships}, \text{deviceVars}, \text{streamVars}, \text{requests}, \text{messageCount} \rangle
\end{aligned}$$

Sends a write request to the device from node 'n'

$\text{SendWriteRequest}(n) \triangleq$

$$\begin{aligned}
& \wedge \text{streams}[n] = \text{Open} \\
& \wedge \text{LET } m \triangleq \text{masterships}[n] \\
& \text{IN}
\end{aligned}$$

$\wedge m.term > 0$
 $\wedge m.master = n$
 $\wedge isMaster[n]$
 $\wedge SendRequest(n, [$
 $\quad type \mapsto WriteRequest,$
 $\quad election_id \mapsto m.term + Cardinality(Nodes),$
 $\quad term \mapsto m.term])$
 $\wedge UNCHANGED \langle mastershipVars, nodeVars, deviceVars, streamVars, responses \rangle$

Receives a write response on node 'n'
 $ReceiveWriteResponse(n) \triangleq$
 $\wedge streams[n] = Open$
 $\wedge HasResponse(n, WriteResponse)$
 $\wedge LET m \triangleq NextResponse(n)$
 IN
 $\quad \text{TODO: This should be used to determine whether writes from old masters are allowed}$
 $\quad \vee m.status = Ok$
 $\quad \vee m.status = PermissionDenied$
 $\wedge DiscardResponse(n)$
 $\wedge UNCHANGED \langle mastershipVars, nodeVars, deviceVars, streamVars, requests, messageCount \rangle$

This section models the P4 switch. The switch side manages stream states between the device and the controller. Streams are opened and closed in a single state transition for the purposes of this model. Switches can handle two types of messages from the controller nodes: *MasterArbitrationUpdate* and *Write*.

Returns the highest election *ID* for the given elections
 $ElectionId(e) \triangleq Max(Range(e))$

Returns the master for the given elections
 $Master(e) \triangleq$
 IF $Cardinality(\{i \in Range(e) : i > 0\}) > 0$ THEN
 $\quad CHOOSE n \in DOMAIN e : e[n] = ElectionId(e)$
 ELSE
 $\quad Nil$

Opens a new stream between node 'n' and the device

When a new stream is opened, the 'requests' and 'responses' queues for the node are cleared and the 'streams' state is set to 'Open'.

$ConnectStream(n) \triangleq$
 $\wedge streams[n] = Closed$
 $\wedge streams' = [streams \text{ EXCEPT } ![n] = Open]$
 $\wedge streamChanges' = streamChanges + 1$
 $\wedge UNCHANGED \langle mastershipVars, nodeVars, deviceVars, messageVars \rangle$

Closes the open stream between node 'n' and the device

When the stream is closed, the 'requests' and 'responses' queues for the node are cleared and a 'MasterArbitrationUpdate' is sent to all remaining connected nodes to notify them of a mastership change if necessary.

$$\begin{aligned}
\text{CloseStream}(n) &\triangleq \\
&\wedge \text{streams}[n] = \text{Open} \\
&\wedge \text{elections}' = [\text{elections} \text{ EXCEPT } ![n] = 0] \\
&\wedge \text{streams}' = [\text{streams} \text{ EXCEPT } ![n] = \text{Closed}] \\
&\wedge \text{requests}' = [\text{requests} \text{ EXCEPT } ![n] = \langle \rangle] \\
&\wedge \text{LET } \text{oldMaster} \triangleq \text{Master}(\text{elections}) \\
&\quad \text{newMaster} \triangleq \text{Master}(\text{elections}') \\
&\text{IN} \\
&\quad \vee \wedge \text{oldMaster} \neq \text{newMaster} \\
&\quad \quad \wedge \text{responses}' = [i \in \text{DOMAIN } \text{streams}' \mapsto \\
&\quad \quad \quad \text{IF } \text{streams}'[i] = \text{Open} \text{ THEN} \\
&\quad \quad \quad \quad \text{IF } i = \text{newMaster} \text{ THEN} \\
&\quad \quad \quad \quad \quad \text{Append}(\text{responses}[i], [\\
&\quad \quad \quad \quad \quad \quad \text{type} \quad \mapsto \text{MasterArbitrationUpdate}, \\
&\quad \quad \quad \quad \quad \quad \text{status} \quad \mapsto \text{Ok}, \\
&\quad \quad \quad \quad \quad \quad \text{election_id} \mapsto \text{ElectionId}(\text{elections}')] \\
&\quad \quad \quad \quad \text{ELSE} \\
&\quad \quad \quad \quad \quad \text{Append}(\text{responses}[i], [\\
&\quad \quad \quad \quad \quad \quad \text{type} \quad \mapsto \text{MasterArbitrationUpdate}, \\
&\quad \quad \quad \quad \quad \quad \text{status} \quad \mapsto \text{AlreadyExists}, \\
&\quad \quad \quad \quad \quad \quad \text{election_id} \mapsto \text{ElectionId}(\text{elections}')] \\
&\quad \quad \quad \quad \text{ELSE} \\
&\quad \quad \quad \quad \quad \langle \rangle] \\
&\quad \quad \quad \quad \wedge \text{messageCount}' = \text{messageCount} + 1 \\
&\quad \quad \vee \wedge \text{oldMaster} = \text{newMaster} \\
&\quad \quad \quad \wedge \text{responses}' = [\text{responses} \text{ EXCEPT } ![n] = \langle \rangle] \\
&\quad \quad \quad \wedge \text{UNCHANGED } \langle \text{messageCount} \rangle \\
&\quad \wedge \text{streamChanges}' = \text{streamChanges} + 1 \\
&\quad \wedge \text{UNCHANGED } \langle \text{mastershipVars}, \text{nodeVars}, \text{writes} \rangle
\end{aligned}$$

Handles a master arbitration update on the device

If the *election_id* is already present in the 'elections', send an 'AlreadyExists' response to the node. Otherwise,

$$\begin{aligned}
\text{HandleMasterArbitrationUpdate}(n) &\triangleq \\
&\wedge \text{streams}[n] = \text{Open} \\
&\wedge \text{HasRequest}(n, \text{MasterArbitrationUpdate}) \\
&\wedge \text{LET } m \triangleq \text{NextRequest}(n) \\
&\text{IN} \\
&\quad \vee \wedge m.\text{election_id} \in \text{Range}(\text{elections}) \\
&\quad \quad \wedge \text{elections}[n] \neq m.\text{election_id} \\
&\quad \quad \wedge \text{streams}' = [\text{streams} \text{ EXCEPT } ![n] = \text{Closed}] \\
&\quad \quad \wedge \text{requests}' = [\text{requests} \text{ EXCEPT } ![n] = \langle \rangle]
\end{aligned}$$

$$\begin{aligned}
& \wedge \text{responses}' = [\text{responses} \text{ EXCEPT } ![n] = \langle \rangle] \\
& \wedge \text{UNCHANGED } \langle \text{deviceVars}, \text{streamChanges}, \text{messageCount} \rangle \\
\vee & \wedge m.\text{election_id} \notin \text{Range}(\text{elections}) \\
& \wedge \text{elections}' = [\text{elections} \text{ EXCEPT } ![n] = m.\text{election_id}] \\
& \wedge \text{LET } \text{oldMaster} \triangleq \text{Master}(\text{elections}) \\
& \quad \text{newMaster} \triangleq \text{Master}(\text{elections}') \\
& \text{IN} \\
& \quad \vee \wedge \text{oldMaster} \neq \text{newMaster} \\
& \quad \quad \wedge \text{responses}' = [i \in \text{DOMAIN } \text{streams} \mapsto \\
& \quad \quad \quad \text{IF } \text{streams}[i] = \text{Open} \text{ THEN} \\
& \quad \quad \quad \quad \text{IF } i = \text{newMaster} \text{ THEN} \\
& \quad \quad \quad \quad \quad \text{Append}(\text{responses}[i], [\\
& \quad \quad \quad \quad \quad \quad \text{type} \mapsto \text{MasterArbitrationUpdate}, \\
& \quad \quad \quad \quad \quad \quad \text{status} \mapsto \text{Ok}, \\
& \quad \quad \quad \quad \quad \quad \text{election_id} \mapsto \text{ElectionId}(\text{elections}')] \\
& \quad \quad \quad \quad \text{ELSE} \\
& \quad \quad \quad \quad \quad \text{Append}(\text{responses}[i], [\\
& \quad \quad \quad \quad \quad \quad \text{type} \mapsto \text{MasterArbitrationUpdate}, \\
& \quad \quad \quad \quad \quad \quad \text{status} \mapsto \text{AlreadyExists}, \\
& \quad \quad \quad \quad \quad \quad \text{election_id} \mapsto \text{ElectionId}(\text{elections}')] \\
& \quad \quad \quad \quad \text{ELSE} \\
& \quad \quad \quad \quad \quad \text{responses}[i]] \\
& \quad \quad \quad \wedge \text{messageCount}' = \text{messageCount} + 1 \\
& \quad \vee \wedge \text{oldMaster} = \text{newMaster} \\
& \quad \quad \wedge \text{SendResponse}(n, [\\
& \quad \quad \quad \text{type} \mapsto \text{MasterArbitrationUpdate}, \\
& \quad \quad \quad \text{status} \mapsto \text{Ok}, \\
& \quad \quad \quad \text{election_id} \mapsto \text{ElectionId}(\text{elections}')] \\
& \quad \wedge \text{UNCHANGED } \langle \text{streamVars} \rangle \\
& \wedge \text{DiscardRequest}(n) \\
& \wedge \text{UNCHANGED } \langle \text{mastershipVars}, \text{nodeVars}, \text{writes} \rangle
\end{aligned}$$

Handles a write request on the device

$$\begin{aligned}
\text{HandleWrite}(n) & \triangleq \\
& \wedge \text{streams}[n] = \text{Open} \\
& \wedge \text{HasRequest}(n, \text{WriteRequest}) \\
& \wedge \text{LET } m \triangleq \text{NextRequest}(n) \\
& \text{IN} \\
& \quad \vee \wedge \text{elections}[n] = m.\text{election_id} \\
& \quad \quad \wedge \text{Master}(\text{elections}) = n \\
& \quad \quad \wedge \text{writes}' = \text{Append}(\text{writes}, [\text{node} \mapsto n, \text{term} \mapsto m.\text{term}]) \\
& \quad \quad \wedge \text{SendResponse}(n, [\\
& \quad \quad \quad \text{type} \mapsto \text{WriteResponse}, \\
& \quad \quad \quad \text{status} \mapsto \text{Ok}]) \\
& \quad \vee \wedge \vee \text{elections}[n] \neq m.\text{election_id}
\end{aligned}$$

$$\begin{aligned}
& \vee \text{Master}(\text{elections}) \neq n \\
& \wedge \text{SendResponse}(n, [\\
& \quad \text{type} \mapsto \text{WriteResponse}, \\
& \quad \text{status} \mapsto \text{PermissionDenied}]) \\
& \wedge \text{UNCHANGED } \langle \text{writes} \rangle \\
& \wedge \text{DiscardRequest}(n) \\
& \wedge \text{UNCHANGED } \langle \text{mastershipVars}, \text{nodeVars}, \text{elections}, \text{streamVars} \rangle
\end{aligned}$$

The invariant asserts that no master can write to the switch after the switch has been notified of a newer master

$$\text{TypeInvariant} \triangleq \forall i \in \text{DOMAIN } \text{writes} : i = 1 \vee \text{writes}[i-1].\text{term} \leq \text{writes}[i].\text{term}$$

$$\begin{aligned}
\text{Init} & \triangleq \\
& \wedge \text{term} = 0 \\
& \wedge \text{master} = \text{Nil} \\
& \wedge \text{backups} = \langle \rangle \\
& \wedge \text{events} = [n \in \text{Nodes} \mapsto \langle \rangle] \\
& \wedge \text{masterships} = [n \in \text{Nodes} \mapsto [\text{term} \mapsto 0, \text{master} \mapsto 0, \text{backups} \mapsto \langle \rangle, \text{sent} \mapsto \text{FALSE}]] \\
& \wedge \text{isMaster} = [n \in \text{Nodes} \mapsto \text{FALSE}] \\
& \wedge \text{streams} = [n \in \text{Nodes} \mapsto \text{Closed}] \\
& \wedge \text{requests} = [n \in \text{Nodes} \mapsto \langle \rangle] \\
& \wedge \text{responses} = [n \in \text{Nodes} \mapsto \langle \rangle] \\
& \wedge \text{elections} = [n \in \text{Nodes} \mapsto 0] \\
& \wedge \text{mastershipChanges} = 0 \\
& \wedge \text{streamChanges} = 0 \\
& \wedge \text{messageCount} = 0 \\
& \wedge \text{writes} = \langle \rangle
\end{aligned}$$

$$\begin{aligned}
\text{Next} & \triangleq \\
& \vee \exists n \in \text{Nodes} : \text{ConnectStream}(n) \\
& \vee \exists n \in \text{Nodes} : \text{CloseStream}(n) \\
& \vee \exists n \in \text{Nodes} : \text{JoinMastershipElection}(n) \\
& \vee \exists n \in \text{Nodes} : \text{LeaveMastershipElection}(n) \\
& \vee \exists n \in \text{Nodes} : \text{LearnMastership}(n) \\
& \vee \exists n \in \text{Nodes} : \text{SendMasterArbitrationUpdateRequest}(n) \\
& \vee \exists n \in \text{Nodes} : \text{HandleMasterArbitrationUpdate}(n) \\
& \vee \exists n \in \text{Nodes} : \text{ReceiveMasterArbitrationUpdateResponse}(n) \\
& \vee \exists n \in \text{Nodes} : \text{SendWriteRequest}(n) \\
& \vee \exists n \in \text{Nodes} : \text{HandleWrite}(n) \\
& \vee \exists n \in \text{Nodes} : \text{ReceiveWriteResponse}(n)
\end{aligned}$$

$$\text{Spec} \triangleq \text{Init} \wedge \Box[\text{Next}]_{\text{vars}}$$

* Modification History
* Last modified *Mon Feb 18 22:56:25 PST 2019* by *jordanhalterman*
* Created *Thu Feb 14 11:33:03 PST 2019* by *jordanhalterman*