

PESU I/O Slot 16 Assignment 1

NAME – DISHAN D

1)chmod-

In Unix operating systems, the chmod command is used to change the access mode of a file. The name is an abbreviation of change mode.

Flags-

- (i) **-f** Suppresses all error reporting except invalid permissions and usage statements.
 - (ii) **-h** Suppresses a mode change for the file or directory pointed to by the encountered symbolic link.
 - (iii) **-R** The -R flag changes the file mode bits of each directory and of all files matching the specified pattern.
-

2)init –

The init command initializes and controls processes. Its primary role is to start processes based on records.

Flags-

- (i) **-b** Boot directly into a single user shell without running any other startup scripts.
- (ii) **1-5** Runlevel to boot into.

(iii)-a The LILO boot loader adds the word "auto" to the command line if it booted the kernel with the default command line (without user intervention).

3)ping –

PING (Packet Internet Groper) command is used to check the network connectivity between host and server/host. This command takes as input the IP address or the URL and sends a data packet to the specified address with the message “PING” and get a response from the server/host this time is recorded which is called latency.

Flags-

- (i)-t Pings the specified host until stopped.
- (ii)-n Number of echo requests to send
- (iii)-l Send buffer size

4)traceroute –

traceroute command in Linux prints the route that a packet takes to reach the host. This command is useful when you want to know about the route and about all the hops that a packet takes.

Flags-

- (i) **-hops** Sets the maximum time-to-live (maximum number of hops) used in outgoing probe packets.
 - (ii) **-num** Prints hop addresses numerically rather than symbolically and numerically.
 - (iii) **-port** Sets the base UDP port number used in probes.
-

5) su-

The Unix command su, which stands for 'substitute user'[1][2] (or historically 'superuser'[3][4]), is used by a computer user to execute commands with the privileges of another user account. When executed it invokes a shell without changing the current working directory or the user environment.

Flags-

- (i) **-** Specifies that the process environment is to be set as if the user had logged in to the system using the login command.
 - (ii) **Name** Specifies user ID.
 - (iii) **Arguments** Specifies the clear text password for the bindDN that is used to bind to the LDAP server.
-

-X-