

VYSOKÉ UČENÍ TECHNICKÉ V BRNĚ

BRNO UNIVERSITY OF TECHNOLOGY

FAKULTA INFORMAČNÍCH TECHNOLOGIÍ
ÚSTAV POČÍTAČOVÉ GRAFIKY A MULTIMÉDIÍ

FACULTY OF INFORMATION TECHNOLOGY
DEPARTMENT OF COMPUTER GRAPHICS AND MULTIMEDIA

IMAGE CAPTIONING WITH RECURRENT NEURAL NETWORKS

SEMESTRÁLNÍ PROJEKT
TERM PROJECT

AUTOR PRÁCE
AUTHOR

Bc. JAKUB KVITA

BRNO 2015



VYSOKÉ UČENÍ TECHNICKÉ V BRNĚ
BRNO UNIVERSITY OF TECHNOLOGY



FAKULTA INFORMAČNÍCH TECHNOLOGIÍ
ÚSTAV POČÍTAČOVÉ GRAFIKY A MULTIMÉDIÍ

FACULTY OF INFORMATION TECHNOLOGY
DEPARTMENT OF COMPUTER GRAPHICS AND MULTIMEDIA

POPIS FOTOGRAFIÍ POMOCÍ REKURENTNÍCH NEU- RONOVÝCH SÍTÍ

IMAGE CAPTIONING WITH RECURRENT NEURAL NETWORKS

SEMESTRÁLNÍ PROJEKT

TERM PROJECT

AUTOR PRÁCE

AUTHOR

Bc. JAKUB KVITA

VEDOUcí PRÁCE

SUPERVISOR

Ing. MICHAL HRADIŠ, Ph.D.

BRNO 2015

Abstrakt

Výtah (abstrakt) práce v českém jazyce.

Abstract

Výtah (abstrakt) práce v anglickém jazyce.

Klíčová slova

Klíčová slova v českém jazyce.

Keywords

Klíčová slova v anglickém jazyce.

Citace

Jakub Kvita: Image Captioning with Recurrent Neural Networks, semestrální projekt, Brno, FIT VUT v Brně, 2015

Image Captioning with Recurrent Neural Networks

Prohlášení

Prohlašuji, že jsem tento semestrální projekt vypracoval samostatně pod vedením pana Michala Hradiše.

.....

Jakub Kvita
December 30, 2015

Poděkování

Zde je možné uvést poděkování vedoucímu práce a těm, kteří poskytli odbornou pomoc.

© Jakub Kvita, 2015.

Tato práce vznikla jako školní dílo na Vysokém učení technickém v Brně, Fakultě informačních technologií. Práce je chráněna autorským zákonem a její užití bez udělení oprávnění autorem je nezákonné, s výjimkou zákonem definovaných případů.

Contents

1	Introduction	2
2	Neural networks	3
2.1	Recurrent neural nets	3
2.1.1	LSTM – Long Short-Term Memory	4
2.1.2	GRU – Gated Recurrent Unit	5
2.1.3	Language modeling – Word level embeddings and character level . .	6
2.2	Convolutional neural nets	6
3	Experiments	8
3.1	Torch	8
3.1.1	nn, nngraph	8
3.1.2	rnn	8
3.1.3	Other packages	8
3.2	Predicting next character in sequence	8
4	Image caption generation	9
4.1	Related Work	9
4.1.1	Show and Tell	9
4.1.2	Show, Attend and Tell	9
4.1.3	From Captions to Visual Concepts and Back	9
4.1.4	Long-term Recurrent Convolutional Networks for Visual Recognition and Description	9
4.2	Datasets	10
4.3	Evaluation metrics	11
4.3.1	BLEU	11
4.3.2	CIDEr	11
4.3.3	METEOR	11
5	Model	12
5.1	Architecture	12
5.2	Training details	12
6	Conclusion	13

Chapter 1

Introduction

Klasicky popis toho co se tady bude dit, jak je to dulezite, atd.

Chapter 2

Neural networks

General idea of neural networks was slowly emerging after World War II. Perceptron, as a single neuron unit, was created in 1958 by Frank Rosenblatt¹, but became popular only after creation of backpropagation algorithm in 1975. At that time neural nets have not reached massive popularity, not because they are not working, but due to small computing power of machines back then and lack of datasets. Recently (after 2000) neural nets became popular again, rebranded as ‘Deep Learning’, because researchers realized that it is possible and very useful to stack neural nets on top of each other and create deep architectures, which are more practical than shallow ones. During this reinvention neural nets have been successfully applied in multiple fields like computer vision, speech recognition and natural language processing.

Since then various useful architectures and algorithms are now introduced almost every month. There is vast amount of various architectures and algorithms, in this chapter, I will describe only a couple – those used in this thesis.

2.1 Recurrent neural nets

Feedforward neural nets are extremely powerful models, which can be highly parallelized. Despite that, they can be only applied to problems with inputs and outputs, which have fixed dimensionality (e.g. one-hot encoding vectors). This is a serious drawback, as many of the real-world problems are defined as sequences with lengths that are unknown to us in beforehand. Soon recurrent neural networks were introduced and they proved to be very useful to this kind of task. There is vast amount of recurrent neural networks, many not suitable for sequential tasks like Hopfield network, which are very successful in specific tasks, but nevertheless not useful for us now.

Apart from classification, which can be more precise when using sequences, one of the most important tasks is next value prediction. This core task can be then extended very simply to predict arbitrary number of future values. Prediction problems are all around us, from the weather forecast and stock market prediction to the autocomplete in smartphones or web browsers.

We can understand recurrent neural networks as very deep forward nets with shared weights. It is called RNN unrolling and it is described in figure 1. Layers of this very deep net spread in time, together with the input sequence. This is very innovative idea,

¹The perceptron: A probabilistic model for information storage and organization in the brain. Rosenblatt, F. Psychological Review, Vol 65(6), Nov 1958, 386–408.




Figure 1: Unrolling of the recurrent neural net. (C. Olah 2015 [13])

which enabled training RNN with backpropagation through time. It also shows that, as very deep networks, they have vanishing or exploding gradient problem, which means that the network is not able to learn long-term dependencies, even though in theory it should. This is a serious issue, which is caused by iterating many times over the weights and the activation function with derivatives > 1 (exploding gradient) or < 1 (vanishing gradient). Gradient then dies out and learning stops for distant dependencies. Among others this problem has been solved by the LSTM unit described in part 2.1.1, which is most popular now and following research resulting in GRU described in part 2.1.2.

2.1.1 LSTM – Long Short-Term Memory

Long Short-Term Memory nets are special kind of recurrent network, capable of learning long-term dependencies. This architecture was introduced by Hochreiter & Schmidhuber (1997) in [7] after prior research of vanishing gradient problem. Later architecture was refined and popularized by other researchers and nowadays LSTM is most used and popular RNN architecture used.

The LSTM unit designed that it can remember a value for an arbitrary length of time. It contains gates that determine when the input is significant enough to remember, when it should keep or forget the value, and when it should output the value. To understand the flow of data, see the diagram of a simplified LSTM unit is on the figure 2.




Figure 2: Variation of the LSTM unit. (C. Olah 2015 [13])

Mam to tady
rozebrat vice?

All these gates can be described by series of equations (1)→(6). In each time slice the unit is using current input x_t , last stored value c_{t-1} and unit output h_{t-1} to compute next state c_t and output h_t . Variables i_t , f_t , o_t denotes value of input, forget and output gates which are used to control the information flow.

$$i_t = \sigma(W_{xi}x_t + W_{hi}h_{t-1} + W_{ci}c_{t-1} + b_i) \quad (1)$$

$$f_t = \sigma(W_{xf}x_t + W_{hf}h_{t-1} + W_{cf}c_{t-1} + b_f) \quad (2)$$

$$z_t = \tanh(W_{xc}x_t + W_{hc}h_{t-1} + b_c) \quad (3)$$

$$c_t = f_t \odot c_{t-1} + i_t \odot z_t \quad (4)$$

$$o_t = \sigma(W_{xo}x_t + W_{ho}h_{t-1} + W_{co}c_t + b_o) \quad (5)$$

$$h_t = o_t \odot \tanh(c_t) \quad (6)$$

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad (7)$$

LSTM based on these equations is using total of 11 weight matrices and 4 bias vectors for computations and sigmoid function σ defined in the equation (7) and the operation \odot denotes the element-wise vector product. Equations described in this work are not the only way how to create an LSTM unit, but they will be used later while implementing the proposed model. Some of the versions are omitting ‘peephole connections’, which allows gates to look at stored value C_{t-1} , C_t or include only some of them.

Training of the LSTM based network can be performed effectively by standard methods like stochastic gradient descend in the form of backpropagation through time. Major problem with vanishing gradients during training described earlier is not an issue as back-propagated error is fed back to each of the gates.

2.1.2 GRU – Gated Recurrent Unit

Gated Recurrent Unit is slightly more dramatic variation on the LSTM theme from 2014 paper [2]. It combines hidden state of the unit h_t with the saved value C_t , merges input and forget gates into one update gate and removes peephole connections. These changes are simplifying standard LSTM models, but not at the expense of performance, and cause rapid growth in popularity. Diagram of the GRU unit is on the figure 3.

$$r_t = \sigma(W_{xr}x_t + W_{hr}h_{t-1} + b_r) \quad (8)$$

$$z_t = \sigma(W_{xz}x_t + W_{hz}h_{t-1} + b_z) \quad (9)$$

$$\tilde{h}_t = \tanh(W_{xh}x_t + W_{hh}(h_{t-1} \odot r_t) + b_h) \quad (10)$$

$$h_t = (1 - z_t) \odot \tilde{h}_t + z_t \odot h_{t-1} \quad (11)$$

$$\sigma(x) = \frac{1}{1 + e^{-x}} \quad (12)$$

Equations (8)→(11) describe a version of GRU unit used in this work, with sigmoid function σ defined in equation (12). The operation \odot again denotes the element-wise




Figure 3: Variation of a GRU unit. (C. Olah 2015 [13])

vector product. While it is using only 4 weight matrices, 3 biases and just 1 state variable, researchers studied whether this can achieve at least same performance as previous LSTM unit.

Last year, study by Chung [3] was done, where different types of recurrent units were compared on the polyphonic music datasets. In this task LSTM and GRU were significantly better than all the other architectures, with GRU slightly in the lead. Generally, researchers agree that most of the LSTM variations, including GRU, are roughly on the same performance level. In [6] GRU is an average variation, slightly better than vanilla LSTM, with much simpler architecture.

In paper [9], which emphasized variety of tasks and the data, GRU outperformed LSTM unit on all tasks with the exception of language modeling. There are multiple approaches to model languages and in this work I will explore different type than the one mentioned in Jozefowicz's [9] paper. More will be explained in following chapters. Interestingly they also found that LSTM nearly matched the GRU's performance, when its forget gate bias was initialized to 1 and not to naive initialization around 0. It is also worth mentioning that Jozefowicz in his paper discovered several architectures similar to GRU, but with slightly better general performance. They were found by evolutionary algorithm working on candidate architectures represented by the computational graph.

2.1.3 Language modeling – Word level embeddings and character level

Popis toho jak se pracuje s textem v rnn, ze to je taky sekvence. Character level, word level, embeddings. Popis rozdilu toho jak funguji preklady a generovani dalsiho prvku sekvence.

2.2 Convolutional neural nets

Kratky uvod do toho, kde se používaji, jak se vyvinuly, jednoduchy popis toho jak funguji. Obrazek?

Asi neni potreba davat subsekce na vrstvy, staci popsat jak to funguje vsechno dohromady, jednotlivé vrstvy ve vetach v jednom odstavci. Obrazek. V diplomce rozpracovat vic.

Chapter 3

Experiments

Kapitola jen na semestrální projekt. V diplomce ji odstranim.

Jak se to implementuje, jaké knihovny se používají - Caffe, Theano, TensorFlow, Torch. Popsat ze Torch bude v této kapitole.

Budu popisovat věci co jsem zkoušel implementovat v Torch.

3.1 Torch

Torch se zrecykluje do diplomky.

Udělat tedy tabulku o různých balících co torch má

Jak fungují rekurentní sítě v Torch.

Nacítání modelu z Caffe, ukládání v Torch...

[1]

3.1.1 nn, nngraph

Linky na knihovny v poznámkách pod čarou.

3.1.2 rnn

3.1.3 Other packages

loadcaffe, optim,...

3.2 Predicting next character in sequence

Implementace sekce Language modeling, jak se to konkrétně dělá.

Jak jsem to udělal, co to dělá, ukázky.

Reference na Karpatyho char-rnn

[10]

Chapter 4

Image caption generation

Znovu uvod k tomu jak je to dulezite a tentokrat jak na tom lidi pracuji, co je potreba a jak se to hodnoti.

4.1 Related Work

Dat tomu nejake lepsi jmeno, clanky o popisovani obrazku ktere jsem cetl, pouzil.

4.1.1 Show and Tell

[17] [15]

Clanek z Coco od Googlu.

Zminit i strojovy preklad (Sequence to Sequence Learning with Neural Networks), architektura encoder, decoder

4.1.2 Show, Attend and Tell

[18]

Clanek z Coco z Montrealu/Toronta

4.1.3 From Captions to Visual Concepts and Back

[5]

Clanek z Coco od Microsoftu, mrknout se i na pokracovani v druhem clanku

4.1.4 Long-term Recurrent Convolutional Networks for Visual Recognition and Description

[4]

Clanek z Coco z berkeley

4.2 Datasets

Big datasets are necessary requirement in training recurrent neural nets, together with sufficient computing power. As access to machines and hardware suitable for training has been made extremely easy, obtaining enough data become the biggest problem. All the descriptions in the image captioning datasets have to be human generated, which is very expensive. This is one of the reasons, not many specialized datasets are created.

There are two main options how to get images and captions. First, using user-generated data from an online service, most commonly Flickr. However, captions are not made specifically for the task and could be prone to error. Second option is to create captions directly for use in the dataset. Amazon Mechanical Turk¹ is heavily used for this task. All datasets mentioned here are created this way.

Flickr8k [8] was one of the first datasets created for this purpose. It has been later expanded into Flickr30k [19]. MS COCO [12] is dataset created by Microsoft for their captioning challenge. CIDEr [16] datasets PASCAL-50S, ABSTRACT-50S are youngest mentioned, designed specifically for evaluation with the CIDEr metric.

Table 1: Image captioning datasets.

Name	Images	Captions per image	Note
Flickr8k ²	8 092	5	Focused on people or animals (mainly dogs) performing some specific action.
Flickr30k ³	31 783	5-6	An extension of Flickr8k dataset.
MS COCO ⁴	120 000	5	Images are divided - 80 000 to training and 40 000 for testing purposes.
PASCAL-50S ⁵	1 000	50	Built upon images from the UIUC Pascal Sentence Dataset.
ABSTRACT-50S ⁶	500	50	Built upon images from the Abstract Scenes Dataset. No photos.

¹Amazon Mechanical Turk is crowdsourced Internet marketplace to perform tasks that computers are currently unable to do.

²Flickr8k project page: <http://nlp.cs.illinois.edu/HockenmaierGroup/8k-pictures.html>

³Flickr30k project page: <http://shannon.cs.illinois.edu/DenotationGraph/>

⁴MS COCO project page: <http://mscoco.org/dataset/>

⁵PASCAL-50S and ABSTRACT-50S page: <http://ramakrishnavedantam928.github.io/cider/>

⁶See footnote 5.

4.3 Evaluation metrics

BLEU, cIDER, jak se pouzivaji, co delaji...

4.3.1 BLEU

[14]

4.3.2 CIDEr

[16]

4.3.3 METEOR

[11]

Chapter 5

Model

Do semestrálního projektu nebo až na diplomku?

Design modelu, co chci použít, jaké metody chci zkusit.

Položit si principiální otázku a zjistit, jestli to nějak pomůže, jak to funguje.

5.1 Architecture

Architektura modelu, jaké matematické modely jsem použil, bez implementačních detailů.

5.2 Training details

Popis pomocí jakého algoritmu jsme trénovali, s jakými parametry, minibatches, datasety.

Chapter 6

Conclusion

Udelat jeden zaver pro semestralni projekt, pak ho prepsat pro diplomku.

Bibliography

- [1] Torch – Scientific Computing for LuaJIT. <http://torch.ch/>. [Accessed: 2015-12-24].
- [2] Kyunghyun Cho, Bart van Merriënboer, Çağlar Gülçehre, Fethi Bougares, Holger Schwenk, and Yoshua Bengio. Learning Phrase Representations using RNN Encoder-Decoder for Statistical Machine Translation. *CoRR*, abs/1406.1078, 2014.
- [3] Junyoung Chung, Çağlar Gülçehre, KyungHyun Cho, and Yoshua Bengio. Empirical Evaluation of Gated Recurrent Neural Networks on Sequence Modeling. *CoRR*, abs/1412.3555, 2014.
- [4] Jeff Donahue, Lisa Anne Hendricks, Sergio Guadarrama, Marcus Rohrbach, Subhashini Venugopalan, Kate Saenko, and Trevor Darrell. Long-term Recurrent Convolutional Networks for Visual Recognition and Description. *CoRR*, abs/1411.4389, 2014.
- [5] Hao Fang, Saurabh Gupta, Forrest N. Iandola, Rupesh K. Srivastava, Li Deng, Piotr Dollár, Jianfeng Gao, Xiaodong He, Margaret Mitchell, John C. Platt, C. Lawrence Zitnick, and Geoffrey Zweig. From Captions to Visual Concepts and Back. *CoRR*, abs/1411.4952, 2014.
- [6] Klaus Greff, Rupesh Kumar Srivastava, Jan Koutník, Bas R. Steunebrink, and Jürgen Schmidhuber. LSTM: A Search Space Odyssey. *CoRR*, abs/1503.04069, 2015.
- [7] Sepp Hochreiter and Jürgen Schmidhuber. Long Short-Term Memory. *Neural Computation*, 9(8):1735–1780, November 1997.
- [8] Micah Hodosh, Peter Young, and Julia Hockenmaier. Framing Image Description as a Ranking Task: Data, Models and Evaluation Metrics. *Journal of Artificial Intelligence Research*, 47:853–899, 2013.
- [9] Rafal Józefowicz, Wojciech Zaremba, and Ilya Sutskever. An Empirical Exploration of Recurrent Network Architectures. In *Proceedings of the 32nd International Conference on Machine Learning, ICML 2015, Lille, France, 6-11 July 2015*, pages 2342–2350, 2015.
- [10] Andrej Karpathy. The Unreasonable Effectiveness of Recurrent Neural Networks. <http://karpathy.github.io/2015/05/21/rnn-effectiveness/>. [Accessed: 2015-12-30].
- [11] Alon Lavie and Abhaya Agarwal. METEOR: An Automatic Metric for MT Evaluation with High Levels of Correlation with Human Judgments. In *Proceedings of the Second Workshop on Statistical Machine Translation, StatMT '07*, pages 228–231, Stroudsburg, PA, USA, 2007. Association for Computational Linguistics.

- [12] Microsoft. Common Objects in Context. <http://mscoco.org/dataset/#download>. [Accessed: 2015-12-29].
- [13] Christopher Olah. Understanding LSTM Networks. <http://colah.github.io/posts/2015-08-Understanding-LSTMs/>. [Accessed: 2015-12-20].
- [14] Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. BLEU: A Method for Automatic Evaluation of Machine Translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*, ACL '02, pages 311–318, Stroudsburg, PA, USA, 2002. Association for Computational Linguistics.
- [15] Ilya Sutskever, Oriol Vinyals, and Quoc V. Le. Sequence to Sequence Learning with Neural Networks. *CoRR*, abs/1409.3215, 2014.
- [16] Ramakrishna Vedantam, C. Lawrence Zitnick, and Devi Parikh. CIDEr: Consensus-Based Image Description Evaluation. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2015.
- [17] Oriol Vinyals, Alexander Toshev, Samy Bengio, and Dumitru Erhan. Show and Tell: A Neural Image Caption Generator. *CoRR*, abs/1411.4555, 2014.
- [18] Kelvin Xu, Jimmy Ba, Ryan Kiros, Kyunghyun Cho, Aaron C. Courville, Ruslan Salakhutdinov, Richard S. Zemel, and Yoshua Bengio. Show, Attend and Tell: Neural Image Caption Generation with Visual Attention. *CoRR*, abs/1502.03044, 2015.
- [19] Peter Young, Alice Lai, Micah Hodosh, and Julia Hockenmaier. From image descriptions to visual denotations: New similarity metrics for semantic inference over event descriptions. *Transactions of the Association for Computational Linguistics*, 2:67–78, 2014.