


Operating Systems




Introduction (Lecture-1)

Monsoon 2014, IIIT-H

Suresh Purini


Bootstrapping (the course)

- What is an Operating System?
 - A program that acts as an intermediary between a user of a computer and the computer hardware.



- Software to manage a computer's resources for its users and applications
- What purpose(s) does it serve?
- Examples:
- **Trick Question:** Are Fedora and Ubuntu different operating systems?


Basic Processor Model





- Why is this an abstraction of the actual processor?
- **Key Question:** Given this processor abstraction, how do we build multi-user, multi-tasking and “whatever” operating systems such as Linux, Android, iOS.

Bootstrapping Problem

- When we switch-on a processor
 1. PC value gets initialized to XXX (say zero).
 2. FE/DE/EXE cycle starts with the instruction at the address XXX.
- **Issue:** Who is going to place the desired instruction (rather the bootstrap program) at the XXX memory location?
- **Idea 1:** Use ROM. What's the problem?
- **Idea 2:** Use Flash RAM. What's the problem?
- **Idea 3:** Use a FlashRAM-RAM combination.



Bootstrapping in x86 Processors




Reading Assignment

1. <http://duartes.org/gustavo/blog/post/kernel-boot-process/>
2. <http://arjunsreedharan.org/post/82710718100/kernel-101-lets-write-a-kernel>


Single Tasking Operating System (MS-DOS)

- **Definition:** A program in execution is called a process (or a task).
- **Single Tasking OS:** Only one active process (residing in memory) at any time.

Memory Map



MS-DOS Memory Map



Issues with MS-DOS kind of Operating Systems

- Resource under utilization
 - CPU:
 - Memory: ...
- Lack of robustness due to poor or no protection mechanisms
 - How to isolate the kernel?
- What if the program is buggy and gets into an infinite loop?
- Are there any advantages?
 - You cannot use Facebook as you do your assignments.
 - Almost zero overhead (gaming!)
 - Hey, I want to execute single application anyways!

[Check OSv (<http://osv.io>)]




So You Want to Fix MS-DOS!

- Kernel isolation (protection)
- Ability to terminate a program running forever.
- Better resource utilization
 - Do something else while
 - An user is typing his input on keyboard
 - Disk controller is reading a block of requested data
 -


Multiprogrammed Operating Systems

- **Idea:** Switch between multiple jobs based on I/O requests.



Multiprogramming ('65-'80)

Keep several jobs in memory and multiplex CPU between jobs




Multiprogramming

Issues

- Kernel isolation
- Program isolation
- **Scheduling:** Which job to pick next?
- Any issues with respect to memory?
- **Question:** Can you do FB and program simultaneously?

Timesharing Operating Systems ('70-)

A timer interrupt is used to multiplex CPU among jobs




Time Sharing

Issues


- Kernel isolation
- Program isolation
- **Scheduling:** Which job to pick next?
- Any issues with respect to memory?
- Context switching overheads
- **Question:** Can you do FB and program simultaneously?

Virtualization

- **Goal:** Give every program a virtual PC
- Every process
 - Gets an illusion that it has an entire processor for itself (via multiplexing CPU over time)
 - Complete memory address space available (via Virtual Memory)
- **However:** Indirect interference between processes is possible



Virtualization



OS History

