## Options

| | |
|---|---|
| `-h, --help` | Display the Artisan help |
| `-q, --quiet` | Do not output any message |
| `-n, --no-interaction` | Do not ask any interactive question |
| `--env[=ENV]` | The environment the comment should run under |
| `-v\|vv\|vvv` | Increase verbosity of messages |

## General commands

| | |
|---|---|
| `clear-compiled` | Remove compiled class file |
| `down` | Turn on maintenance mode |
| `env` | Display current environment |
| `help` | Display help for a command |
| `inspire` | Display inspiring quote |
| `list` | Lists commands |
| `migrate` | Run database migrations |
| `optimize` | Cache bootstrap files |
| `preset` | Swap front-end scaffolding |
| `serve` | Serve application on PHP dev server |
| `tinker` | Interact with your application |
| `up` | Turn off maintenance mode |

## Auth

| | |
|---|---|
| `auth:clear-resets` | Flush expired password reset tokens |

## Cache

| | |
|---|---|
| `cache:clear` | Flush application cache |
| `cache:forget` | Remove item from cache |
| `cache:table` | Create a migration for the cache table |

## Clean

| | |
|---|---|
| `clean:events` | Cleanup events |

## Config

| | |
|---|---|
| `config:cache` | create configuration cache |
| `config:clear` | clear configuration cache |

## db

| | |
|---|---|
| `db:seed` | Seed the database |
| `db:wipe` | Drop all tables,views and types |

## event

| | |
|---|---|
| `event:cache` | cache all events and listeners |
| `event:clear` | clear cached events and listeners |
| `event:generate` | generate missing events and listeners |
| `event:list` | list events and listeners |

## key

| | |
|---|---|
| `key:generate` | Generate and set the application key |

## make

| | |
|---|---|
| `make:channel` | New channel class |
| `make:command` | New Artisan command |
| `make:controller` | New controller class |
| `make:event` | New event class |
| `make:exception` | New exception class |
| `make:factory` | Create a new model factory |
| `make:job` | New job class |
| `make:listener` | New event listener class |
| `make:mail` | New email class |
| `make:middleware` | New middleware class |
| `make:migration` | New migration file |
| `make:model` | New Eloquent model class |
| `make:notification` | New notification class |
| `make:observer` | New observer class |
| `make:policy` | New policy class |
| `make:provider` | New service provider class |
| `make:request` | New form request class |
| `make:resource` | New resource |
| `make:rule` | New validation rule |
| `make:seeder` | New seeder class |
| `make:test` | New test class |

By **Auditeers - Maurice (Auditeers)**
cheatography.com/auditeers/
www.auditeers.net

Published 11th October, 2019.
Last updated 11th October, 2019.
Page 1 of 2.

| Migrate | |
|---|---|
| `migrate:fresh` | Drop tables and re-run migrations |
| `migrate:install` | Create migration repository |
| `migrate:refresh` | Rollback and re-run all migrations |
| `migrate:reset` | Rollback all migrations |
| `migrate:rollback` | Rollback the last migration |
| `migrate:status` | Show the status of each migration |