FX®-100HS(C)

Carthage Mills' FX-100HS(C) is a multipurpose nonwoven geotextile made of polypropylene staple fibers which are formed into a random network, needlepunched and heatset for dimensional stability. FX-100HS is part of the Carthage **FX-HS Series** of nonwoven geotextiles, is inert to biological degradation and resistant to naturally encountered chemicals, alkalis, and acids.

PROPERTY	TEST METHOD	DATA	
		METRIC	ENGLISH
☐ **Mechanical**			
Grab Tensile Strength	ASTM D 4632	1.11 kN	250 lbs
Grab Tensile Elongation	ASTM D 4632	50%	
Trapezoidal Tear	ASTM D 4533	0.40 kN	90 lbs
CBR Puncture	ASTM D 6241	2.67 kN	600 lbs
☐ **Endurance**			
UV Resistance	ASTM D 4355	70% @ 500 hrs	
☐ **Hydraulics / Filtration**			
Permittivity [1]	ASTM D 4491	0.70 sec^{-1}	
Water Flow Rate [1]	ASTM D 4491	2648 lpm/m^2	65 gpm/ft^2
Apparent Opening Size (AOS) [1,2]	ASTM D 4751	0.212 mm	70 US Std. Sieve
☐ **Physical**			
Mass Per Unit Area	ASTM D 5261	322 g/m^2	9.5 oz/yd^2
Standard Roll Sizes / Packaging / Weight	Measured (Typical)	4.57 m x 91.5 m 418 m^2 149.6 kg	15.0 ft x 300 ft 500 yd^2 330 lbs

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

(1) At the time of manufacturing. Handling, storage and shipping may change these properties.
(2) Maximum Average Roll Value

- Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).
- The properties reported above are effective 01-01-26 and are subject to change without notice.

Carthage Mills
4243 Hunt Road
Cincinnati, OH 45242
www.carthagemills.com

513-794-1600 TELEPHONE
800-543-4430 TOLL FREE
513-794-3434 FACSIMILE
info@carthagemills.com