Carthage Mills **Product Data**

Geotextiles | Erosion Control | Geogrids | Geomembranes

FX®-665MF

Carthage Mills' FX-665MF is a woven High-Performance geotextile produced from high-tenacity polypropylene yarns. FX-665MF is part of the Carthage **FX® High-Performance Series** of woven geotextiles, is inert to biological degradation, and resistant to naturally encountered chemicals, alkalis and acids.

PROPERTY	TEST METHOD	DATA	
		METRIC	**ENGLISH**
☐ **Mechanical/Performance/Design**			
Wide Width Tensile Ultimate	ASTM D 4595	78.8 x 109.4 kN/m	5400 x 7500 lbs/ft
Wide Width Tensile @ 5% Strain		17.5 x 61.3 kN/m	1200 x 4200 lbs/ft
☐ **Mechanical/Index**			
Grab Tensile Strength	ASTM D 4632	2.670 x 3.115 kN/m	650 x 700 lbs
Grab Tensile Elongation		15 x 15%	
CBR Puncture	ASTM D 6241	8.900 kN/m	2000 lbs
☐ **Endurance**			
UV Resistance	ASTM D 4355	80% @ 500 hrs	
☐ **Hydraulics/Filtration**			
Permittivity[1]	ASTM D 4491	0.26 sec^{-1}	
Water Flow Rate[1]		815 lpm/m^2	20 gpm/ft^2
Apparent Opening Size (AOS) [1,2]	ASTM D 4751	0.425 mm	40 US Std. Sieve
☐ **Physical**			
Standard Roll Sizes / Packaging / Weight	Measured (Typical)	4.57 m x 91.4 m 418 m^2 256 kg	15.0 ft x 300 ft 500 yd^2 565 lbs

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

(1) At the time of manufacturing. Handling, storage and shipping may change these properties.
(2) Maximum Average Roll Value

- Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).
- The properties reported above are effective 01-01-2026 and are subject to change without notice.

Carthage Mills
4243 Hunt Road
Cincinnati, OH 45242
www.carthagemills.com

513-794-1600 TELEPHONE
800-543-4430 TOLL FREE
513-794-3434 FACSIMILE
info@carthagemills.com

Since 1958: America's *First* Geotextile Company