PVC

PVC has been used for geomembrane applications for over 60 years. It is one of the most flexible geomembranes available, with a formulation that can provide oil resistance, UV stability, low-temperature resistance, and other specific properties. Layfield's PVC materials meet the requirements of ASTM D7176 Standard Specification for Non-reinforced Polyvinyl Chloride (PVC) Geomembranes.

April 2023

PVC

Material Properties

Style	**ASTM**	**PVC 20**	**PVC 30**	**PVC 40**
Thickness (Minimum)	D7176	19 mil 0.48 mm	28.5 mil 0.72 mm	38 mil 0.95 mm
Tensile Strength	D7176	48 ppi 8.4 N/mm	73 ppi 12.8 N/mm	97 ppi 17.0 N/mm
Elongation	D7176	360%	380%	430%
Tear Strength	D7176	6.0 lbs 27 N	8.0 lbs 35 N	10.0 lbs 44 N
Low Temperature	D7176	-15°F -26°C	-20°F -29°C	-20°F -29°C
Dimensional Stability	D7176	4%	3%	3%
Water Extraction	D7176	0.15%	0.15%	0.2%
Volatile Loss	D7176	0.9%	0.7%	0.5%
Hydrostatic Resistance	D7176	68 psi 470 kPa	100 psi 690 kPa	120 psi 830 kPa
Resistance to Soil Burial				
Breaking Factor	D7176	5%	5%	5%
Elongation at Break	D7176	20%	20%	20%
Modulus @ 100%	D7176	20%	20%	20%