Carthage Mills **Product Data**

Geotextiles | Erosion Control | Geogrids | Geomembranes

# FX®- 2400HSE

Carthage Mills' FX-2400HSE is a nonwoven geotextile designed specifically for the environmental market, is constructed of polypropylene staple fibers which are formed into a random network, needle-punched and heatset for dimensional stability. FX-2400HSE is part of the Carthage **FX®-HSE Series** of nonwoven geotextiles, is inert to biological degradation and resistant to naturally encountered chemicals, alkalis, and acids.

The Carthage Mills' FX-HSE Series of environmental nonwoven geotextiles designates "Mass Per Unit Area" or "Weight Per Square Yard" as a true Minimum value.

| PROPERTY | TEST METHOD | DATA | |
|---|---|---|---|
| | | METRIC | ENGLISH |
| ☐ **Mechanical** | | | |
| Grab Tensile Strength | ASTM D 4632 | 2.225 kN | 500 lbs |
| Grab Tensile Elongation | ASTM D 4632 | 50% | |
| Trapezoidal Tear | ASTM D 4533 | 0.890 kN | 200 lbs |
| CBR Puncture | ASTM D 6241 | 8.01 kN | 1800 lbs |
| ☐ **Endurance** | | | |
| UV Resistance | ASTM D 4355 | 70% @ 500 hrs | |
| ☐ **Hydraulics / Filtration** | | | |
| Apparent Opening Size (AOS) (1,2) | ASTM D 4751 | 0.15 mm | 100 US Std. Sieve |
| ☐ **Physical** | | | |
| Mass Per Unit Area | ASTM D 5261 | 814 g/m$^2$ | 24.0 oz/yd$^2$ |
| Thickness | ASTM D 5199 | 5.1 mm | 200 mils |
| Standard Roll Sizes / Packaging / Weight | Measured (Typical) | 4.5 m x 46 m<br>209 m$^2$ | 15 ft x 150 ft<br>250 yd$^2$ |

NOTES: Mullen Burst Strength ASTM D 3786 is no longer recognized by ASTM D35 on Geosynthetics. Puncture Strength ASTM D 4833 is not recognized by AASHTO M 288 and has been replaced with CBR Puncture ASTM D 6241.

(1) At the time of manufacturing. Handling, storage and shipping may change these properties.
(2) Maximum Average Roll Value
- Unless otherwise stated, all values stated here are Minimum Average Roll Values (MARV).
- The properties reported above are effective 01-01-26 and are subject to change without notice.

Carthage Mills assumes no liability for the accuracy or completeness of this information or for the ultimate use by the purchaser. Carthage Mills disclaims any and all express, implied, or statutory standards, warranties or guarantees, including without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to any equipment, materials, or information furnished herewith. This document should not be construed as engineering advice.

Carthage Mills
4243 Hunt Road
Cincinnati, OH 45242
www.carthagemills.com

513-794-1600 TELEPHONE
800-543-4430 TOLL FREE
513-794-3434 FACSIMILE
info@carthagemills.com

Since 1958: America's *First* Geotextile Company