



ACECell™ are geocells with three-dimensional structures to confine filling materials to stabilize soils/ aggregate sand to enhance structural stability. ACECell™ geocells are made of high density polyethylene (HDPE) material with high stiffness and dimensional stability.

Product Properties

Test Method	Unit	Smooth Structure with / without Perforation
-------------	------	---

Mechanical Index Properties

Material			HDPE
Density, -5%	ASTM D792	g/cm ³	0.94
Carbon Black Content	ASTM D1603	%	1.5

Cell Depth Properties

Cell Depth		mm	75	100	150	200	250
Seam Peel Strength, -10%	ASTM D6392	N	900	1200	1800	2400	3000
Sheet Thickness, Smooth, -10%		mm	1.2				

Dimensional Characteristics

Bonded Ranges		mm	330	400	450	500	660
Cell Depth		mm	75, 100, 150, 200, 250				
Expanded Cell Dimension		mm	233x213	282.5x257	318x289.5	353.6x322	466.5x424.5
Expanded Section Size		m	4.06x4.04	4.06x4.89	4.24x5.50	4.34x6.11	4.30x8.07
Expanded Section Area		m ²	16.40	19.85	23.32	26.52	34.70

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>