



ACECompo™ GB are geocomposites constructed by a high-tenacity fiberglass grid, a lightweight polyester nonwoven geotextile and bitumen coating which can provide a good bonding property with asphalt layers. The fiberglass grids offer high strength, high modulus and high temperature resistance for performing high reinforcement ability, and raise the resistance of ACECompo™ GB against the damages from installation. Moreover, the nonwoven geotextiles increase the liquid asphalt retention capacity of the product. With the ACECompo™ GB geocomposites to reinforce asphalt layers, the pavements can extend their service life and reduce the occurrence rate of reflective cracking under cyclic traffic load. Therefore, ACECompo™ GB is a highly effective and economical solution for road rehabilitation.

Product Properties

Test Method	Unit	GB 50-II	GB 100-II
-------------	------	----------	-----------

Mechanical Properties

Material			Glassfiber Geogrid + Polyester Thermally Bonded Nonwoven Geotextile Coated with Bitumen	
Mesh Size, -10%	Measured	mm	25.4 × 25.4	25.4 × 25.4
Tensile Strength-MD, -10%	ASTM D6637	kN/m	50	100
Tensile Strength-CD, -10%	ASTM D6637	kN/m	50	100
Tensile Elongation-MD	ASTM D6637	%	4	4
Tensile Elongation-CD	ASTM D6637	%	4	4

Dimensional Characteristics

Length		m	50	50
Width		m	3.9	3.9

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: salas@geoace.com <http://www.geoace.com>