



ACECompo™ GC are geocomposites made of a high-tenacity polyester grid, a thermally-bonded polyester nonwoven geotextile and bitumen coating. ACECompo™ GC geocomposites are highly flexible with bituminous coating to adhere to asphalt layers or base layers, so the laying of ACECompo™ GC can be very easy and rapid. By the incorporation of the polyester grids and nonwoven geotextiles, the geocomposites offer high strength, high modulus and high liquid asphalt retention capacity. With the installation of ACECompo™ GC geocomposites in the road pavement systems, they can have longer service life and fewer reflective cracks under cyclic traffic load. Therefore, ACECompo™ GC is a highly cost-efficient solution for road repair and construction.

Product Properties

Test Method	Unit	GC 50-II	GC 100-II
-------------	------	----------	-----------

Mechanical Properties

Material			Polyester Geogrid + Polyester Thermally Bonded Nonwoven Geotextile Coated with Bitumen	
Mesh Size, -10%	Measured	mm	40 × 40	40 × 40
Tensile Strength-MD, -10%	ASTM D6637	kN/m	50	100
Tensile Strength-CD, -10%	ASTM D6637	kN/m	50	100
Tensile Elongation-MD	ASTM D6637	%	16	16
Tensile Elongation-CD	ASTM D6637	%	16	16

Dimensional Characteristics

Length		m	50	50
Width		m	3.9	3.9

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>