



ACEDrain™ G geomesh is made of high impact polymer with 4mm to 6mm thick range. It can maintain a constant thickness under high load pressure and provide excellent conductivity. It extensively used in civil structures such as embankment, landfill and roadway.

Product Properties

	Test Method	Unit	G04	G05	G06
Geonet Drainage					
Material			High-density Polyethylene		
Carbon Black	ASTM D4218	%	2~3		
Density	ASTM D1505	g/cm ³	> 0.94		
Thickness at 2kPa, -1mm	ISO 9863-1	mm	4.2	5.2	6
Mass per Unit Area, -10%	ISO 9864	g/cm ²	450	600	790
Mechanical Index Properties					
Tensile Strength-MD/CD, -10%	ISO 10319	kN/m	5.5/1.5	6.0/2.0	7.0/2.5
Tensile Elongation-MD/CD	ISO 10319	%	20/90		
CBR, -10%	ISO 12236	N	360	550	550
Hydraulic Properties					
Flow Capacity in The Plane-MD (i=1.0, σ=200kPa), -30%	ISO 12958	L/m.s	1.17	1.44	1.74
Dimensional Characteristics					
Length		m	50	50	42
Width		m	3.9	3.9	3.9

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.

We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>