



ACEDrain™ S is a drainage geocomposite consisting of a planar core wrapped with a gray polyester nonwoven geotextile. The core of ACEDrain™ S is a board with regular dimples made of high-impact polystyrene to maintain the invariable thickness under high loading pressure and provide excellent flow conductivity. The nonwoven geotextiles cover each dimple to prevent soil penetration into the water channel as well as to allow water flow into the drain core. ACEDrain™ S can be used horizontally or vertically to provide full coverage drainage. Horizontal applications include plaza decks or athletic fields, while vertical applications include seeping soil slope and retaining walls.

Product Properties

Test Method	Unit	SV-100	SV-100
-------------	------	--------	--------

Geonet Drainage

Material			High-impact Polystyrene (HIPS) and Polyester Nonwoven Geotextile	
Compressive Strength, -10%	ASTM D1621	kPa	980	980
Thickness, - 2mm	Measured	mm	10	10
Water Flow Rate, 200kPa, -30%	ASTM D4716	L/m/s	5.0	5.0

Filter Fabric

Permittivity, -30%	ASTM D4491	1/s	0.01	0.01
--------------------	------------	-----	------	------

Dimensional Characteristics

Length		m	20	20
Width		m	0.2	0.2

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>