



ACEGrid® GA are bitumen coated fiberglass geogrids designed for road asphalt layer reinforcement. As an asphalt interlayer, ACEGrid® GA can evenly distribute stress resulted from upward load and reduce the deformation of the asphalt layer. Therefore, the occurrence of surface cracks is delayed and the service life of road is significantly extended, allowing pavement maintenance cost to be saved.

Product Properties

	Test Method	Unit	GA 50-II(a)	GA 100-II(a)
--	-------------	------	-------------	--------------

Material Glassfiber Geogrid Coated With Bitumen

Mesh Size, -10%	Measured	mm	25.4 x 25.4	25.4 x 25.4
-----------------	----------	----	-------------	-------------

Mechanical Index Properties

Tensile Strength -MD, -5%	ASTM D6637	kN/m	50	100
Tensile Strength -CD, -5%	ASTM D6637	kN/m	50	100
Tensile Elongation -MD	ASTM D6637	%	≤ 4	≤ 4
Tensile Elongation -CD	ASTM D6637	%	≤ 4	≤ 4

Dimensional Characteristics

Width		m	3.9	3.9
Length		m	50	50

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>