



ACELiner™ Geosynthetic Clay Liners (GCLs) are hydraulic barriers consisting of three or four layers of materials. The three-layer product consists of a layer of nonwoven geotextile, a layer of woven geotextile and a core layer of natural or processed sodium bentonite. The four-layer product has an extra layer of geomembrane in comparison to the three-layer product. ACELiner™ geosynthetic clay liners have extremely low permeability and excellent self-healing capacity to prevent oozing of water, leachate or other liquids. ACELiner™ geosynthetic clay liners can be used for both barrier and containment requirements, such as landfill liners and caps, channel liners and artificial ponds, etc.

Product Properties

	Test Method	Unit	H 3600	H 4000	H 4500	H 5000
Geotextile Layer						
Material			Nonwoven Geotextile + Bentonite + Woven Geotextile			
Polypropylene Nonwoven Geotextile, -10%	ASTM D5261	g/cm ²	200			
Polypropylene Woven Geotextile, -10%	ASTM D5261	g/cm ²	100			
Bentonite Layer						
Bentonite Mass per Area, -10%	ASTM D5993	g/cm ²	3600	4000	4500	5000
Bentonite Swell Index	ASTM D5890	ml/2g	≥ 24			
Bentonite Fluid Loss	ASTM D5891	ml	≤ 18			
Geosynthetic Clay Liner						
Peel Strength-MD, -10%	ASTM D6496	N/m	400			
Index Flux, +30%	ASTM D5887	m ³ /m ² /sec	5.0 × 10 ⁻⁶	5.0 × 10 ⁻⁶	5.0 × 10 ⁻⁶	5.0 × 10 ⁻⁹
Dimensional Characteristics						
Length		m	42	40	38	35
Width, -0.2(value)		m	5.8	5.8	5.8	5.8

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
We can customize the product to fulfill different project requirement. If you require more detail information,
please feel free to contact us directly at sales@geoace.com.
We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
E-mail: sales@geoace.com <http://www.geoace.com>