



ACELoop Tex™ is a fabric consisting of a woven geotextile which forms a base fabric and a numerous loops standing perpendicular on the base fabric. The standing loops can penetrate into the base of concrete blocks during casting process. After curing, these are bonding each other to form an integral mattress system of Loop Pile Fabric - Concrete Block. It can be used as a cost saved erosion control armor in hydraulic engineering.

Product Properties

Mechanical Index Properties	Unit	Data	Tolerance	Test Method
Material		Polypropylene		
Thickness under 2 kPa	mm	8	±1	EN 9863-1
Weight	g/m ²	500	±500	EN 9864
Loop Pile length	mm	8	±1	
Loop Pile density	loops/10cm ²	26	±4	

Mechanical Properties

Tensile strength - MD	kN/m	80	-10	EN ISO 10319
Tensile strength - CD	kN/m	70	-10	EN ISO 10319
Elongation - MD	%	20	+5	EN ISO 10319
Elongation - CD	%	15	+5	EN ISO 10319
Static Puncture resistance (CBR)	kN	9	-1.5	EN ISO 12236
Dynamic perforation resistance (cone drop)	mm	9	+2	EN ISO 13433

Hydraulic properties

Flow velocity index	m/sec	36x10 ⁻³	10x10 ⁻³	EN ISO 11058
Flow rate	l/m ² /sec	36	-10	EN ISO 11058
Characteristic opening size (O ₉₀)	mm	0.3	±0.09	EN ISO 11058

Dimension

Width	m	2.6	
Length	m	70	

Notes:

1. The value of performance tests are the typical value which are tested by international accredited laboratory.
2. The value of performance tests are the typical value which are tested by international accredited laboratory.

Disclaimer: This document is provided solely for general information, and shall not be construed as engineering advice, or part of the contract with any customer not withstanding anything to the contrary in the contract. We hereby disclaim any liability in connection with any use of the information herein.

Thank you for your interests in our products,
 We can customize the product to fulfill different project requirement. If you require more detail information,
 please feel free to contact us directly at sales@geoace.com.
 We'll be pleased to provide our best assistance.

Accurate, Collaborative, Efficient

TEL: 886-4-26595926 FAX: 886-4-26595935
 E-mail: sales@geoace.com <http://www.geoace.com>