

DESCRIPTIVE SHEET



LANDSCAPING GEOTEXTILES

FLOWERBED / GARDEN / POND / RESIDENTIAL ENTRANCE / LOW WALL / WINTER PROTECTION FOR TREES AND PLANTS

Solutions for professional practitioners			TEX-500	TEX-700	SX-90T ⁽¹⁾	SX-130T ⁽¹⁾	TEX-R RC6 PRO*	TEX-700N	Soltex	Arbotex	Arbotex Plastified
Description			Non-woven geotextile, grey		Woven geotextile, black		Non-woven geotextile, copper-coated	Non-woven geotextile, black	Non-woven geotextile, green	Non-woven geotextile, white	Non-woven geotextile, white, with white plastic liner
Application			Weed control in flowerbeds				Anti-root	Protection	Algae control	Winter protection	
			Separation of soils for private entrance and behind low walls				Commercial and industrial	Water garden	Lake	Grass	Trees and plants
Composition ⁽²⁾			PP	PP-PET	PP	PP	PP-cooper	PP-PET	PP-PET	PP-PET	PP-PET-LDPE
Property	Test Method	Unit	Technical informations								
Weight	ASTM D5261	g/m2	125	145	-	-	150-210	145	95-125	125-155	130-150
Thickness	ASTM D5199	mm	1.0	1.2	-	-	0.6-1.0	1.2	0.5-0.9	0.9-1.2	-
Amount of copper	MENVIQ.89.0	g/m2	-	-	-	-	5	-	-	-	-
Mechanical											
Tensile strength	ASTM D4632	N	260	300	890	1402	-	370	-	200	-
Elongation at break	ASTM D4632	%	45	45	15	15	-	45	-	-	-
Trapezoid tear	ASTM D4533	N	110	130	333	533	-	165	-	100	-
CBR puncture	ASTM D6241	N	760	880	3115	4005	-	1050	-	700	-
Dimensions											
Width and length	-	m	Variable ⁽³⁾								

The values entered are values obtained at the time of manufacture. Handling and storage conditions may change some properties.
1- SX-90T / SX-130T products used such as Tex-Pro 100, but not lined./ 2- PET = Polyester; PP = Polypropylene; LDPE = Low Density Polyethylene / 3- Several lengths and widths available depending on the model. Contact our customer service for more details.
*Patented product, Health Canada registration number under the Pest Control Products Act: TEX-R RC6 PRO: 29716 / Spin Out 260 Copper Coating: 29255