

Descriptive Sheet



Geotextiles for Plants Production Areas

FOR FIELD, GREENHOUSE AND NURSERY PRODUCTION

Solutions for Producers			Bench Matting	Bench Matting Plus	SX-90T ⁽¹⁾	SX-130T ⁽¹⁾	Arbo-Pro ⁽²⁾	Arbo-Mat	Arbo-Pro Plus ⁽²⁾
Description			Non-woven geotextile	Non-woven geotextile with a woven geotextile	Woven geotextile,black		Non-woven geotextile, white		
Application			Irrigation - Capillary rise / Water retention (Plastic liner not included)		Weed control		Permeable winter protection for dormant plants (Plastic liner not included)		
			Growth table	Pedestrian traffic			Bush, nursery and pot	Replaces the straw	Winery ⁽³⁾
Composition ⁽⁴⁾			PET	PET - PP	PP		PET - PP	PP	PET - PP
Property	Test Method	Unit	Technical informations						
Weight	ASTM D5261	g/m2	230 - 270	360 - 440	-	-	160 - 200	440 - 510	195 - 235
Thickness	ASTM D5199	mm	1.8 - 2.2	2.4 - 3.0	-	-	1.6 - 2.1	5.5 - 6.5	1.7 - 2.3
Amount of copper	MENVIQ.89.0	g/m2	-	-	-	-	-	-	-
Mechanical									
Tensile strength	ASTM D4632	N	-	-	890	1 402	-	-	450
Elongation at break	ASTM D4632	%	-	-	15	15	-	-	50
Trapezoid tear	ASTM D4533	N	-	-	355	533	-	-	250
CBR puncture	ASTM D6241	N	-	-	3 115	4 005	-	-	-
Hydraulic									
Hydraulic conductivity	In-house test Conductivity probe	sec	10.0	60	-	-	-	-	-
Capillary rise (24h)	In-house test	mm	15.0	30	-	-	-	-	-
Water retention	In-house test	L/m²	1.5	2.5	-	-	-	-	-
Dimensions									
Width and length	-	m	Variable ⁽⁵⁾						

The values entered are values obtained at the time of manufacture. Handling and storage conditions may change some properties.

1- SX-90T / SX-130T products used such as Tex-Pro 100, but not lined. / 2- These products can be offered with cables along the length to facilitate installation: Arbo-Pro Duraline and Arbo-Pro Plus Duraline. / 3- Used for vineyards but also for other fruit trees. / 4- PET = Polyester; PP = Polypropylene; LDPE = Low Density Polyethylene / 5- Several lengths and widths available depending on the model. Contact our customer service for more details.

Revision : 2025-07-02

Texel reserves the right to modify existing properties contingent on the evolution of technical knowledge. Each user is invited to verify if this document represents the most recent update. Texel offers no guarantee and assumes no responsibility regarding usage, installation and/or convenience of usage. Texel must be informed of all product nonconformity prior to installation. Responsibility is limited to replacement of non-compliant or defective product.

ALKEGEN