



ProFab® MONOWEAVE

PREMIUM FILTER GEOTEXTILE
FOR HIGH FLOW DRAINAGE, FILTRATION, SEPARATION

DESCRIPTION

ProFab monoweave geotextiles are comprised of UV stabilized polypropylene monofilament and tape yarns that provide excellent physical and hydraulic properties. ProFab monoweave geotextile has a unique, dimensionally stable filtration weave.

APPLICATION

ProFab monoweave woven geotextiles are particularly suited to soils that are poorly graded, sands, soils are that are high in iron content and for applications such as in land fills where leachates may crystallise on the surface of the geotextile (such as nonwoven geotextiles) and cause potential clogging problems. ProFab monoweave woven geotextiles are ideal for subsurface drainage applications, leachate drains, retention pit lining, transpiration trenches and as a filter behind retaining walls.

TYPICAL PROPERTIES

PROPERTY	UNITS	MONOWEAVE PPMONO/140/2/50 WOVEN PREMIUM GRADE
Polymer		Polypropylene
Mass	g/m ²	130
Wide Width Tensile Strength	kN/m	40 warp 10 weft
Pore Size	microns	300
Flow Rate	l / m ² / s	170
Roll Dimensions	m	2.0 x 50

DISTRIBUTORS OF :

Geotextiles
Geogrids
Dewatering Tubes
Subsoil Drainage
Wick Drains
Erosion Control
Gabions & Rock Mattresses
Industrial Fabrics
Lining Systems

ProFab is a registered trademark of Global Synthetics Pty Ltd.

Polypropylene is one of the most highly durable polymers known to man. It is resistant to all natural occurring soil acids and alkalis. Polypropylene geotextiles are unaffected by bacteria and fungi. Properties of ProFab geotextiles are typical values and correspond to average values derived from in house and independent laboratory testing.

DISCLAIMER : All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd and Global Synthetics QLD Pty Ltd have a policy of continuous development so information and product specifications may change without notice.

APRIL 16



Global Synthetics
Australian Company – Global Expertise

SYDNEY

P: (02) 9725 4321

F: (02) 9725 4304

E: info@globalsynthetics.com.au | www.globalsynthetics.com.au

BRISBANE

P: (07) 3865 7000

F: (07) 3865 4444

PERTH

P: (08) 9459 4300

F: (08) 9459 4311

MELBOURNE

P: (03) 9791 1772

F: (03) 9791 1776

ADELAIDE

P: (08) 8384 8894

F: (08) 8384 3886