

ProFab® Nonwoven Mini Rolls

Geotextile Mini Rolls Packaged for Small Projects

For drainage, filtration and soil separation



Product Information

ProFab® nonwoven geotextiles are manufactured from the extrusion of fibres which are then laid down on a manufacturing “bed” and then needle punched to entangle the fibres such that a dimensionally stable product is formed. Some additional thermal treatment is then applied to further improve the strength of the geotextile. Because of this manufacturing process nonwoven geotextiles are generally best used in applications of drainage, filtration and protection.

Global Synthetics offers the ProFab® nonwoven geotextile in the AS140 grade in conveniently packaged roll roll sizes for the small project, building or landscaping works.

Profan AS140 grade of nonwoven geotextile provides all of the strength and porosity of bulk geotextile rolls retaining soil particles whilst allowing water to freely drain through.

it is an ideal separation and filtration geotextile for use in paths, behind retaining walls and in subsoil drainage trenches to name a few.

Applications

Due to the manufacturing process and their permeable properties, ProFab® non woven geotextiles are generally best used in applications of drainage, filtration and separation.

Applications may include uses of separation and drainage in situations such as :

- retaining walls
- under paths
- planter boxes
- subsoil drainage trenches
- leachate trenches

ProFab® Nonwoven Mini Roll Geotextile

Benefits

Drainage

ProFab® nonwoven Geotextiles will efficiently collect surplus water from structures, such as rainwater or surplus water, from the soil and discharge it.

Filtration

ProFab® nonwoven geotextiles provide superior hydraulic flow and soil retention, which makes them well suited for filtration in subsurface drainage applications and under hard armour systems.

Separation

ProFab® nonwoven geotextiles are used for paved and unpaved roads, where ground conditions have been compromised. As a separation layer, geotextiles can aid preventing the intermixing of dissimilar materials, add to the performance life of the road and reduce the overall thickness of the road section by requiring less aggregate during construction.

Features

- Drainage
- Filtration
- Separation
- Quality Certified
- Stocked in Australian warehouses
- Easy to handle
- Various convenient roll sizes available



Product Data Sheet

Property	Test Method	Unit	Typical Value
Typical Mass	AS3706.1	g/m ²	140
Grab Tensile	AS3706.2	N	400
Pore Size	AS3706.7	mm	0.2
Flow Rate	AS3706.9	l / m ² / s	300
Roll Dimensions	n/a	m	0.6 x 50
			1.0 x 50
			1.2 x 50
			2.0 x 50
			2.0 x 100
			4.0 x 100

Bulk rolls, 6m wide are also available in a range of product grades to suit all filtration applications.

About Us

Leaders in Geosynthetics

Global Synthetics is a 100% Australian-owned company, proud to offer a complete range of high-quality geosynthetic products backed by over 200 years of combined staff experience in the industry.

We have supplied products to some of the largest recent infrastructure works in Australia. Global Synthetics provides major benefits to any geotechnical engineering project with the right products and our technical expertise.

Global Synthetics products are used in the following applications:

- Pavement Stabilisation
- Ground Improvement
- Soil Reinforcement and Retaining Structures
- Water Management
- Drainage Systems & Hydraulic Works
- Landfills
- Coastal Erosion Structures

Get in Touch

AUSTRALIA

Website

globalsynthetics.com.au

Email

info@globalsynthetics.com.au

New South Wales

(02) 9725 4321

North Qld

(04) 5921 1692

Victoria/Tasmania

(03) 9791 1772

Queensland

(07) 3865 7000

South Australia

(08) 8384 8894

Western Australia

(08) 9459 4300

NEW ZEALAND

Website

globalsynthetics.co.nz

Email

info@globalsynthetics.co.nz

Auckland

0800 510 120

Christchurch

0800 510 120



All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd have a policy of continuous development so information and product specifications may change without notice.



Global Synthetics
LEADERS IN GEOSYNTHETICS