

ProFab[®] Polypropylene (PP) Woven Geotextile

Woven Stabilisation Geotextile

Suitable for separation and stabilisation applications



Product Information

ProFab[®] woven geotextiles are manufactured from the extrusion of polypropylene into either a flat tape or bundled tape fabric. These geotextiles have a defined strength in both the roll and cross roll direction. These geotextiles develop strength at relatively low strains.

Applications

ProFab[®] woven geotextiles are ideally suited for applications of separation of dissimilar materials with an additional benefit of reinforcement. ProFab woven geotextiles are ideally suitable for the construction of paved and unpaved roads.

ProFab® Polypropylene (PP) Woven Geotextile

Product Data Sheet

Product Grade

Mechanical Properties	Test Method	Units	PP30	PP80
Wide Width Tensile Strength XD	ISO 10319	kN/m	30	80
Wide Width Tensile Strength MD	ISO 10319	kN/m	30	80
Strain XD	ISO 10319	%	15	14
Strain MD	ISO 10319	%	20	19
CBR Burst Strength	ISO 12236	kN	3.5	10

Hydraulic Properties

Pore Size	ISO 12956	mm	0.3	0.3
Nominal Flow Rate	ISO 11058	litres/m ² /s	23	20

Physical Properties

Mass		g/m ²	150	360
Roll Size		m	5.85 x 160	5.85 x 100
Nominal Roll Mass		kg	170	235

Polypropylene is one of the most highly durable polymers known to man. It is resistant to all natural occurring soil acids and alkalis. Polypropylene geotextiles are unaffected by bacteria and fungi. Properties of ProFab geotextiles are typical values and correspond to average values derived from in house and independent laboratory testing.



About Us

Leaders in Geosynthetics

Global Synthetics is a 100% Australian-owned company, proud to offer a complete range of high-quality geosynthetic products backed by over 200 years of combined staff experience in the industry.

We have supplied products to some of the largest recent infrastructure works in Australia. Global Synthetics provides major benefits to any geotechnical engineering project with the right products and our technical expertise.

Global Synthetics products are used in the following applications:

- Pavement Stabilisation
- Ground Improvement
- Soil Reinforcement and Retaining Structures
- Water Management
- Drainage Systems & Hydraulic Works
- Landfills
- Coastal Erosion Structures

Get in Touch

AUSTRALIA

Website

globalsynthetics.com.au

Email

info@globalsynthetics.com.au

New South Wales

(02) 9725 4321

North Qld

(04) 5921 1692

Victoria/Tasmania

(03) 9791 1772

Queensland

(07) 3865 7000

South Australia

(08) 8384 8894

Western Australia

(08) 9459 4300

NEW ZEALAND

Website

globalsynthetics.co.nz

Email

info@globalsynthetic.com.nz

Auckland

0800 510 120

Christchurch

0800 510 120



All information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Global Synthetics Pty Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Global Synthetics Pty Ltd have a policy of continuous development so information and product specifications may change without notice.

February 2025



Global Synthetics
LEADERS IN GEOSYNTHETICS