

PRODUCT SPECIFICATIONS

Nilex Nonwoven 4504 (White)

PROPERTY	TEST	UNIT	VALUE
Mechanical			
Grab Tensile Strength	ASTM D-4632	N (lb)	445 (100)
Grab Elongation	ASTM D-4632	%	50
Trapezoidal Tear	ASTM D-4533	N (lb)	222 (50)
Hydraulic			
Apparent Opening Size (AOS)	ASTM D-4751	mm (US Sieve)	0.212 (70)
Permittivity	ASTM D-4491	sec ⁻¹	2.0
Water Flow Rate	ASTM D-4491	l/m/m ² (gpm/ft ²)	5689 (140)
Endurance			
UV Resistance	ASTM D-4355	% retained at 500 hrs	70
Packaging			
Roll Size	Measured	m (ft)	3.81 x 150 (12.5 x 492.13)

Disclaimer: The information provided by Nilex is believed to be correct and is generally based on information supplied by the manufacturers of the product offered. Any recommendations made by Nilex concerning uses or applications of our products are also believed to be reliable; however, as Nilex has no control over design execution, and field conditions of the project which incorporate the product. Nilex disclaims all warranties, expressed or implied, including, without limitation, the warranties of merchantability and/or fitness for a particular purpose.