

DATA SHEET

DRAINCOTEX

PRODUCT DESCRIPTION : Nonwoven needled geocomposite, designed for vertical drainage

FUNCTION : Drainage

RAW MATERIAL : Polypropylene, polyester

TECHNICAL DATA TABLE

	PROPERTIES	TEST METHOD	VALUES	
			Metric	Imperial
PHYSICAL	Thickness	ASTM D5199	7,0 mm	280 mils
HYDRAULIC	Resistance to penetration by water	CAN/CGSB-4.2 - No 26.3	0 - 20 mm	0 - 0,79 in

TECHNICAL DATA TABLE – TRANSMISSIVITY AS A FUNCTION OF COMPRESSION ⁽¹⁾

CONSTRAINT		THICKNESS (± 15 %)		TRANSMISSIVITY (± 15 %)
kPa	psi	mm	mils	
8	1,2	8,00	320	$2,0 \times 10^{-4} \text{ m}^2/\text{sec}$
20	2,9	6,90	276	$1,5 \times 10^{-4} \text{ m}^2/\text{sec}$
50	7,3	5,75	230	$0,9 \times 10^{-4} \text{ m}^2/\text{sec}$
200	29,0	3,40	136	$0,2 \times 10^{-4} \text{ m}^2/\text{sec}$

Note 1 : Test method ASTM D4716, gradient = 1

TECHNICAL DATA TABLE – POCKET FILTER HOSE

	PROPERTIES	TEST METHOD	VALUES	
			Metric	Imperial
PHYSICAL	Tensile strength	ASTM D4632	400 N	90 lb
	Elongation at break	ASTM D4632	> 25 %	
	Tear strength	ASTM D4533	180 N	40 lb
	Puncture resistance (CBR)	ASTM D6241	1200 N	270 lb
HYDRAULIC	Resistance to water penetration	CAN/CGSB-4.2 - No 26.3	0 - 20 mm	0 - 0,79 po
	Permittivity	ASTM D4491	$0,05 \text{ s}^{-1}$	
	Filtration opening size (FOS) ⁽²⁾	CAN/CGSB-148.1 - No 10	150 µm	

Note 2 : Maximum average value per roll.

DATA SHEET

DRAINCOTEX (CONT.)

TABLEAU DES DIMENSIONS TECHNIQUES

PIPE DIAMETER (DRAINAGE CORE)		HEIGHT		LENGTH	
mm	in	m	ft	m	ft
150	6	0,85	2,6	30	91
150	6	1,00	3,0	30	91
150	6	1,20	3,7	30	91

The enclosed information is provided at no cost or obligation on the part of Soleno Textile Inc. The individual using this information in their possession assumes full responsibility for its use, including that of ensuring that this technical data sheet is the latest update by contacting Soleno Textile Inc. Values are calculated using the minimum average roll value (MARV), as defined by ASTM D-4439. Roll sizes can vary 0.5 % from standard sizes.

Soleno Textile Inc. offers no guarantee regarding the use, installation or suitability of the geotextiles described in this document. Since conditions surrounding the use and handling of our products can vary and are beyond the control of Soleno Textile Inc., it can in no way be held responsible for the product's performance and the consequences of improper installation or use. Soleno Textile Inc. must be advised of any defect or non-compliance of its product before installation. Soleno Textile Inc.'s liability will be limited to the replacement of the deficient or defective product to the exclusion of any legal or contractual warranty.

APPLICATIONS : Permanent public roadway
Roadway widening
Airport runways
Slab and building foundation