

DATA SHEET

GEOCELLS

PRODUCT DESCRIPTION: Cellular confinement system made of light and flexible polyethylene, composed of three-dimensional cells in a honeycomb structure

FUNCTIONS: Reinforcement and protection

RAW MATERIAL: Polyethylene

TECHNICAL DATA TABLE

	PROPERTIES	TEST METHOD	TYPICAL VALUES	
			Metric	Imperial
PHYSICAL	Minimum polymer density	ASTM D1505	0.941 - 0.960 g/cm ³	
	Sheet nominal thickness	ASTM D5199	1.25 mm	50 mils
	Carbon Black Content	ASTM D1603	1.5 %	
	Nominal-expanded cell size (width x length)	-	259 mm x 224 mm	10.2 in x 8.8 in
	Nominal-expanded cell area	-	289 cm ²	44.8 in ²
	Nominal-expanded section size (width x length)	-	2.56 m x 6.52 m	8.4 ft x 21.4 ft
	Nominal-expanded section area (width x length)	-	16.7 m ²	180.0 ft ²
MECHANICAL	Environmental stress crack resistance	ASTM D1693	4000 hours	
	Seam hang strength	-	A 102 mm (4 in) weld joint which supports a load of 72.5 kg (160 lbs) for at least 30 days or a weld joint 102 mm (4 in) that supports a load of 72.5 kg (160 lbs) for at least 7 days, while undergoing changes in temperature from 23 °C (74 °F) to 54 °C (130 °F) over a one-hour cycle.	

CELL TECHNICAL DATA TABLE

CELL DEPTH		SEAM PEEL STRENGTH		SECTION WEIGHT		SECTIONS PER PALLET
mm	in	N	lb	kg	lb	
100	4	1420	320	25.9	57.0	50
150	6	2130	480	39.0	86.0	30
200	8	2840	640	51.7	114.0	25

The enclosed information is provided at no cost or obligation on the part of Soleno Textiles Inc. The individual using this information in their possession assumes full responsibility for its use, including that of ensuring that this technical data sheet is the latest update by contacting Soleno Textiles Inc. Values are calculated using the minimum average roll value (MARV), as defined by ASTM D-4439. Roll sizes can vary 0.5 % from standard sizes.

Soleno Textiles Inc. offers no guarantee regarding the use, installation or suitability of the geotextiles described in this document. Since conditions surrounding the use and handling of our products can vary and are beyond the control of Soleno Textiles Inc., it can in no way be held responsible for the product's performance and the consequences of improper installation or use. Soleno Textiles Inc. must be advised of any defect or non-compliance of its product before installation. Soleno Textiles Inc.'s liability will be limited to the replacement of the deficient or defective product to the exclusion of any legal or contractual warranty.

DATA SHEET

GEOCELLS (CONT.)

APPLICATIONS: Retaining walls and embankments
Public access road