

DATA SHEET

TX-90

PRODUCT DESCRIPTION : Nonwoven needled geotextile

FUNCTIONS : Filtration and separation

PRODUCT SPECIFICATION : This product is NTPEP tested for AASHTO M288 standard, Class 3.
Table 601-1 of the New Brunswick specification, N2,
the Nova Scotia specification, Light Duty
and Alberta Transportation Standard Specifications for Highway Construction, Table 5.31.1, Type A.

RAW MATERIAL : Polypropylene

TECHNICAL DATA TABLE

	PROPERTIES	TEST METHOD	VALUES	
			Metric	Imperial
PHYSICAL	Thickness	ASTM D5199	≥ 1.0 mm	≥ 40 mils
	Mass per unit area	ASTM D5261	-	-
MECHANICAL	Tensile strength	ASTM D4632	≥ 600 N	≥ 135 lb
	Elongation at break	ASTM D4632	≥ 50 %	
	Tear strength	ASTM D4533	≥ 250 N	≥ 56 lb
	Puncture strength (CBR)	ASTM D6241	≥ 1700 N	≥ 382 lb
HYDRAULIC	Flow rate	ASTM D4491	≥ 4600 l/min/m ²	≥ 115 gal/min/ft ²
	Permittivity	ASTM D4491	≥ 1.70 s ⁻¹	
	Apparent opening size (AOS) ¹	ASTM D4751	212 µm	70 US Sieve
	Filtration opening size (FOS)	CAN/CGSB-148,1 - No 10-94	60 - 180 µm	
PERFORMANCE AND DURABILITY	UV* resistance (500 hours)	ASTM D4355	≥ 70 %	
DIMENSIONS	Standard width	-	3.81 m	12,5 ft
	Standard length	-	4.57 m	15 ft
			150 m	492 ft

NOTE 1 : Maximum test value

*UV: Ultraviolet.

The information contained herein is provided at no cost or obligation on the part of Soleno Textile Inc. The individual using this information in their possession assumes full responsibility for its use, including that of ensuring that this technical data sheet is the latest update by contacting Soleno Textile Inc. Values are calculated using the minimum average roll value (MARV), as defined by ASTM D-4439. Roll sizes can vary 0.5% from standard sizes. Puncture strength (ASTM D4833) is no longer recognized by AASHTO M288 and has been replaced by CBR puncture (ASTM D6241). Mullen Burst (ASTM D3786) have been removed by AASHTO M288. Soleno Textile Inc.'s quality control laboratory is certified by the Geosynthetic Accreditation Institute - Laboratory Accreditation Program (GAI-LAP).

Soleno Textile Inc. offers no guarantee regarding the use, installation or fitness for purpose of its geotextiles described in this document. Since conditions of use and handling of our products can vary and are beyond the control of Soleno Textile Inc., it can in no way be held responsible for the product's performance and the consequences of improper installation or use. Soleno Textile Inc. must be advised of any defect or non-compliance of its product before installation. Soleno Textile Inc.'s liability is limited to the replacement of the defective or noncompliant product, with the exception of any legal or contractual warranty.

APPLICATIONS : Temporary roadway
Permanent public roadway
Permanent private roadway
Public access road
Commercial parking areas
Storage and loading areas
Roadway widening
Airport runways

Basin
Residential parking areas

