


# MIRAGRID Miramesh

**MIRAGRID** Miramesh are biaxial geosynthetics designed to provide surface erosion protection and secondary reinforcement in MSE structures. **MIRAGRID** Miramesh GR is designed with a UV package for long-term applications and **MIRAGRID** Miramesh TR is ideal for temporary retaining wall structures.



## FEATURES AND BENEFITS

- Vegetation support
- Strength
- Color
- Highly flexible
- UV stability
- Vegetated face

## APPLICATIONS

- Slopes: vegetated & wrapped face
- Walls: permanent & temporary

| Properties                           | Test Method                    | Units        | GR*                   | TR                    |
|--------------------------------------|--------------------------------|--------------|-----------------------|-----------------------|
| Tensile Strength @ Ultimate (MD/CD)  | ASTM D4595                     | lb/ft (kN/m) | 1440/1733 (21.0/25.3) | 2100/2100 (30.6/30.6) |
| Creep Reduced Strength (MD)          | ASTM D5262                     | lb/ft (kN/m) | 471 (6.9)             | 686 (10.0)            |
| Long Term Allowable Design Load (MD) | GRI-GT-7<br>(sand, silt, clay) | lb/ft (kN/m) | 407 (5.9)             | 594 (8.7)             |
| Aperture Size (MD)                   |                                | in (mm)      | 0.08 (2)              | 0.08 (2)              |
| Life Expectancy                      | See Note²                      | Years        | 75                    | 25                    |
| Product Application Color            |                                |              | Long-term/Green       | Temporary/Black       |

**NOTES**  
Values shown are minimum average roll values.  
\* (Patent# 7,740,420)  
² Extrapolated from the average half life based on ASTM D7238 (QUV). Data also found on **MIRAFI** UV Durability Tech Note.