

StrataTex HSR™ 200/200



StrataTex HSR™ is a next generation flexible polyester high performance geotextile used in soil reinforcement and other civil engineering applications. StrataTex HSR™ is manufactured using a high-grade polyester yarn with special high tenacity and low creep properties knitted into a stable network.

		Unit	HSR™ 200/200
Mechanical properties			
Minimum ultimate tensile strength (ASTM D 4595 / EN ISO 10319) (min.)	MD	lbs/ ft	13,700
		kN/ m	200
Minimum ultimate tensile strength (ASTM D 4595 / EN ISO 10319) (min.)	CMD	lbs/ ft	13,700
		kN/ m	200
Elongation at minimum ultimate tensile strength (ASTM D 4595 / EN ISO 10319) (± 2%)	MD	%	10
	CMD		12
Creep reduction factor (at 20°C, 120 years design life)			1.4
Creep limited strength (min.)		lbs/ ft	9,786
		kN/ m	142.9
Physical properties			
Roll width		ft	17
		m	5
Roll length		ft	328
		m	100
Roll area		sq. yd	622
		m ²	520
Mass per unit area (± 10%)		oz/ sq. yd	22
		gm/ m ²	750

Notes

- MD = machine direction / CMD = cross machine direction.
- The above properties might change at the time of the manufacturing, storing, handling or shipping.
- The above values are subject to change as per the discretion of the company.
- Varying roll widths can be provided on order 5.2m / 5.8m
- Customised rolls with varying lengths of 50m/ 100m/ 200m or master rolls can be manufactured on order.
- Tested in GAI-LAP and NABL accredited laboratories



GAI-LAP

CE

