



1831 N Park Ave, Burlington, NC 27217 NC USA  
800-680-7750 - Fax: (336) 226-8133  
www.geogrid.com

## STRATADRAIN Product Data Minimum Average Roll Values - 4 oz/yd<sup>2</sup> Fabric.

Stratadrain is a geonet-geotextile drainage composite manufactured with high-density polyethylene (HDPE) geonet and polypropylene nonwoven fabric bonded to one or both sides. This drainage composite system is engineered to be both mechanically and chemically durable, in both the harsh construction installation phase and aggressive soil (pH range from 2-10) or aqueous environments. The purpose of Stratadrain is to provide excellent lateral transmissivity for the transmission of water or other fluids within the plane of the drain. Applications include sheet interceptor drains behind retaining walls and reinforced steep slopes, landfill leachate transmission and collection, and use with multiple-layered waterproofing and roof deck drain systems.

### Design Properties

|                  | Property                           | Test Method | Imperial Units    | Metric Units     |
|------------------|------------------------------------|-------------|-------------------|------------------|
| <b>Core</b>      | Color                              | visual      | black             | black            |
|                  | Compressive Strength               | ASTM D-1621 | 40,000 psf        | 1915 kPa         |
|                  | Thickness                          | ASTM D-1777 | 0.22 in.          | 5.6 mm           |
|                  | Flow<br>And hydraulic gradient = 1 | ASTM D-4716 |                   |                  |
|                  | Stratadrain 30-1                   |             | 8.5 gpm/ft. width |                  |
|                  | Stratadrain 30-2                   |             | 8.5 gpm/ft. width |                  |
| <b>Fabric</b>    | Weight                             | ASTM D-3776 | 4 oz/sy           | 136 g/sm         |
|                  | Flow                               | ASTM D-4491 | 135 gpm/sf        | 5500 l/min/sm    |
|                  | Mullen Burst                       | ASTM D-3786 | 210 psi           | 1448 kPa         |
|                  | Puncture                           | ASTM D-4833 | 65 lbs            | 0.30 kN          |
|                  | U.V. Resistance                    | ASTM D-4355 | Fully Stabilized  | Fully Stabilized |
|                  | AOS                                | CW-02215    | 70                | 0.212 mm         |
|                  | Grab Tensile                       | ASTM D-4632 | 120 lbs.          | 0.53 kN          |
| <b>Roll Data</b> | Width x Length                     | Measured    | 4 ft. x 75 ft.    | 1.21 m x 22.86 m |
|                  | Area                               | Calculated  | 300 sf            | 27.66 sm         |
|                  | Weight - Stratadrain 30-1          | Measured    | 70 lbs.           | 31.8 kg          |
|                  | Weight - Stratadrain 30-2          | Measured    | 80 lbs.           | 36.3 kg          |

This product specification supersedes all prior specifications for the products described and is not applicable to any products shipped prior to March 28, 2008. This information has been carefully compiled by Strata Systems, Inc., and to the best of our knowledge is accurate. Final determination of the suitability of any information or material is the sole responsibility of the user. Structural design shall be performed by a licensed design professional.