

PRODUCT SPECIFICATIONS

NuDrain™ WD15 Series

Property	Test	Unit	NuDrain™ WD15	NuDrain™ WD15WP
Core				
Compressive Strength	ASTM D-1621	kNm ² (psf)	719 (15000)	719 (15000)
Thickness	ASTM D-1777	mm (in)	10.16 (0.40)	10.16 (0.40)
In-Plane Flow	ASTM D-4716	l/min/m (gpm/ft)	260 (21)	260 (21)
Fabric				
Flow	ASTM D-4491	l/min/m ² (gpm/ft ²)	5704 (140)	5704 (140)
Puncture	ASTM D-4833	kN (lb)	0.30 (65)	0.30 (65)
Apparent Opening Size (AOS)	—	mm (US Sieve)	0.212 (70)	0.212 (70)
Grab Tensile Strength	ASTM D-4632	kN (lb)	0.45 (100)	0.45 (100)
Packaging				
Roll Width	Measured	m (ft)	1.22 (4) 1.98 (6.5) 2.59 (8.5)	1.22 (4) 1.98 (6.5) 2.59 (8.5)
Roll Length	Measured	m (ft)	15.24 (50)	15.24 (50)
Roll Weight	Calculated	kg (lb)	17.69 (39) 28.58 (63) 37.19 (82)	18.37 (40.5) 29.71 (65.5) 38.56 (85)

Note: Nilex NuDrain™ WD15 is identical to WD15WP with the addition of a membrane protective film on the back side.

Disclaimer: The information provided by Nilex is believed to be correct and is generally based on information supplied by the manufacturers of the product offered. Any recommendations made by Nilex concerning uses or applications of our products are also believed to be reliable; however, as Nilex has no control over design execution, and field conditions of the project which incorporate the product. Nilex disclaims all warranties, expressed or implied, including, without limitation, the warranties of merchantability and/or fitness for a particular purpose.



DRAINAGE

nilex.com