

TE-SC32 BD

EROSION CONTROL BLANKET



TE-SC32 BD is an extended-term 100% biodegradable double net straw/coconut fiber erosion control blanket designed for use on a severe slope and channel applications requiring erosion control for up to 24 months depending on moisture, light, and environmental conditions. The blanket is sewn together on 1.5-inch (38.1 mm) centers. The TE-SC32 BD meets all requirements established in the FHWA FP-03 as a Type 3B erosion control blanket for use on slopes with gradients not exceeding 1.5:1 (h:v) and has been tested by the National Transportation Product Evaluation Program (NTPEP). The TE-SC32 BD comes packaged in clear shrink-wrap with an orange band and included installation instructions

Product Nomenclature & Properties

SC = 70% agricultural straw fiber matrix

3 = straw/coconut fiber matrix applied at a rate of 0.5 lbs/yd² (270 g/m²)

2 = top and bottom leno woven biodegradable nets with a mesh size of 0.5 x 1.0 in (1.3 x 2.54 cm)

BD = 100% biodegradable leno woven net, thread, and matrix to ensure consistent functional longevity

TESTED PROPERTY	TEST METHOD	UNIT ENGLISH (METRIC)	VALUE ENGLISH (METRIC)
Mass Per Unit Area	ASTM D 6475	oz/yd ²	9.34
Tensile Strength	ASTM D 6818	lbs/in @ %	18.4 @ 10.7 MD 14.0 @ 15.7 TD
Thickness	ASTM D 6525	in	0.293
Light Penetration / Ground Cover	ASTM D 6567	% / %	6 / 94
Water Absorption	ASTM D1117 & ECTCTASC 00197	%	398
Unvegetated Bench-Scale Rain Splash & Runoff (not to be used as a design value)	ASTM D 7101	1/sec	Soil Loss Ratio* = 16.17 Soil Loss Ratio* = 17.86 Soil Loss Ratio* = 19.73
Unvegetated Bench-Scale Shear Stress (not to be used as a design value)	ASTM D 7207	lbs/ft ² @ ½ in soil loss	2.3
Seed Germination & Plant Growth Under Bench-Scale Conditions	ASTM D 7322	% Improvement (Increased biomass)	558
TYPICAL ROLL DIMENSIONS			
Roll Dimensions		ft (m)	8 (2.44) x 112.5 (34.3) 16 (4.88) x 112.5 (34.3)
Roll Area		yd ² (m ²)	100 (83.61) 200 (167.23)
Roll Weight ± 10%		lbs (kg)	54 (25) 108 (50)

NOTES: *Soil Loss Ratio = Soil Loss Bare Soil / Soil Loss with RECP = 1 / C-Factor (Note: Soil loss is based on regression analysis)

Design Values

- "C" factor = 0.03
- Maximum Permissible Shear Stress = 2.00 lbs/ft² (96 Pa)
- Maximum Permissible Velocity = 8 ft/sec (2.44 m/s)
- Manning's "n" = 0.03

This data is provided for informational purposes only. Titan Environmental Containment Ltd. makes no warranties as to the suitability or the fitness for a specific use or merchantability of the products referred to, no guarantee of satisfactory results from reliance upon contained information or recommendations and disclaims all liability from resulting loss or damage. This information is subject to change without notice, please check with Titan Environmental Containment Ltd. for current updates.

Titan Environmental Containment

Toll free: 1-866-327-1957 | info@titanenviro.com | [TitanEnviro.com](https://www.titanenviro.com)

Rev. August 2023