

Typar® SF Geotextile

Recommended styles

	SF20	SF24	SF27	SF32	SF33	SF37	SF40	SF44	SF45	SF49	SF56	SF65	SF66	SF78	SF85	SF95
Separation/stabilisation																
Sport fields		•	•	•	•	•	•									
Car parks				•	•	•	•	•	•	•						
Car parks for heavy good vehicles										•	•	•	•	•		
Forest roads, access roads				•	•	•	•	•	•	•						
Access roads for heavy vehicles on soft soils											•	•	•	•	•	
Permanent roads/motorways					•	•	•	•	•	•	•					
Roads with low traffic				•	•	•	•									
Embankment > 2 m							•	•	•	•	•					
Runways/taxiways								•	•	•	•	•	•			
Railways													•	•	•	•
Breakwaters, jetties													•	•	•	•
Filtration																
Drainage composites			•	•	•	•	•									
Agricultural drains	•	•	•													
Trench drains			•	•	•	•	•									
Trench drains in silty clay soils						•	•	•	•	•						
Drains for earth dams							•	•	•	•	•	•				
Erosion control																
River/lake embankments				•	•	•	•	•	•	•	•					
Sea shores										•	•	•	•	•	•	•
Seawalls – seaside										•	•	•	•	•	•	•
Seawalls – landside						•	•	•	•	•	•					
Prevention of foundation undermining											•	•	•	•	•	•
Landfill																
Membrane protection													•	•	•	•
Separation and filtration capping				•	•	•	•	•	•	•						
Separation and filtration edges/bottom							•	•	•	•	•	•				

- – Style most commonly used
- – Recommended styles (depending on site conditions)



DuPont™ Typar® products contain up to 55% of recycled internal excess material. With this, DuPont™ significantly reduces the waste generated during the Typar® production process and limits the need for using virgin polymer.

DuPont de Nemours (Luxembourg) S.à r.l.
Rue Général Patton
L-2984 Luxembourg

www.typargeo.com

Further product information is available upon request. This information corresponds to our current knowledge on the subject. It is offered solely to provide possible suggestions for your own testing. It is not intended, however, to substitute for any testing you may need to conduct to determine for yourself the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge and experience becomes available. Since we cannot anticipate all variations in actual end-use conditions DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a license to operate under or a recommendation to infringe any patent right.