




# US 100GC

## Woven Geotextile

US 100GC is a black, woven geotextile with a blue, green or yellow stripe every 12" and is made of 100% high-tenacity polypropylene yarns. This product is used in landscaping, greenhouses and nurseries as a cover around plantings. US 100GC resists ultraviolet and biological deterioration, rotting, naturally encountered basics and acids. Polypropylene is stable within a pH range of 2 to 13. US 100GC meets the following TYPICAL values except where noted:



| PROPERTY                             | TEST METHOD                 | ENGLISH                 | METRIC                     |
|--------------------------------------|-----------------------------|-------------------------|----------------------------|
| Weight <small>Typical</small>        | <a href="#">ASTM D-5261</a> | 3.1 oz/y <sup>2</sup>   | 105.09 g/m <sup>2</sup>    |
| Grab Tensile Strength                | <a href="#">ASTM D-4632</a> | 170 x 100 lbs           | 750 x 440 N                |
| Elongation @ Break                   | <a href="#">ASTM D-4632</a> | 15 %                    | 15 %                       |
| Mullen Burst                         | <a href="#">ASTM D-3786</a> | 305 psi                 | 2,103 kPa                  |
| Pin Puncture                         | <a href="#">ASTM D-4833</a> | 45 lbs                  | 180 N                      |
| Trapezoidal Tear                     | <a href="#">ASTM D-4533</a> | 75 x 65 lbs             | 330 x 290 N                |
| Apparent Opening Size <sup>(1)</sup> | <a href="#">ASTM D-4751</a> | 30 US Sieve             | 0.595 mm                   |
| Water Flow Rate <sup>(1)</sup>       | <a href="#">ASTM D-4491</a> | 10 g/min/f <sup>2</sup> | 407.4 L/min/m <sup>2</sup> |
| UV Resistance @ 2,500 Hours          | <a href="#">ASTM D-4355</a> | 70 %                    | 70 %                       |

<sup>(1)</sup> At the time of manufacturing. Handling, storage, and shipping may change these properties.

## US 100GC Shipping & Packaging Information

| SIZE       | WEIGHT | AREA                 |
|------------|--------|----------------------|
| 12' x 300' | 80 lbs | 400 y <sup>2</sup>   |
| 6' x 300'  | 40 lbs | 200 y <sup>2</sup>   |
| 4' x 300'  | 25 lbs | 133.3 y <sup>2</sup> |
| 3' x 300'  | 20 lbs | 100 y <sup>2</sup>   |

**US Fabrics, Inc. | 3904 Virginia Avenue | Cincinnati, OH 45227**  
**Phone: (800) 518-2290 | Fax: (513) 271-4420 | email: [info@usfabrics.com](mailto:info@usfabrics.com)**

This information is provided for reference only and is not intended as a warranty or guarantee.  
US Fabrics assumes no liability in connection with the use of this information.