




US 550NWE

Environmental Nonwoven Geotextile



US 550NWE is a 28 OZ MARV WEIGHT, nonwoven, needlepunched geotextile made of 100% polypropylene staple filaments used for liner protection in landfills. US 550NWE is resistant to ultraviolet deterioration, rotting, biological degradation, naturally encountered bases and acids. Polypropylene is stable within a pH range of 2 to 13. US 550NWE meets the following M.A.R.V. values:



PROPERTY	TEST METHOD	ENGLISH	METRIC
Weight	ASTM D-5261	28 oz/y ²	949.2 g/m ²
Grab Tensile Strength	ASTM D-4632	550 lbs	2,448 N
Elongation @ Break	ASTM D-4632	50 %	50 %
CBR Puncture	ASTM D-6241	2,004 lbs	8,918 N
Trapezoidal Tear	ASTM D-4533	250 lbs	1,113 N
UV Resistance @ 500 Hours	ASTM D-4355	70 %	70 %

US 550NWE Shipping & Packaging Information

SIZE	WIDTH	WEIGHT	AREA	ROLLS PER TRAILER
15 x 150	15'	490 lbs	250 y ²	27

US Fabrics, Inc. | 3904 Virginia Avenue | Cincinnati, OH 45227
Phone: (800) 518-2290 | Fax: (513) 271-4420 | email: info@usfabrics.com

This information is provided for reference only and is not intended as a warranty or guarantee.
US Fabrics assumes no liability in connection with the use of this information.