



US 830

Woven monofilament

EROSION CONTROL




BULKHEAD



RIP-RAP



FILTRATION



US 830 is a woven high tenacity monofilament filtration geotextile made of 100% polypropylene yarns. This product is specifically designed for drainage and filtration applications. This product's Percent Open Area of 8%, gives it excellent hydraulic properties and high flow rates, while reducing the chances of clogging. US 830 resists ultraviolet and biological deterioration, rotting, naturally encountered basics and acids. US 830 meets the following M.A.R.V. values except where noted:



PROPERTY	TEST METHOD	ENGLISH	METRIC
Grab Tensile Strength	ASTM D-4632	400 x 335 lbs	1,780 x 1,491 N
Elongation @ Break	ASTM D-4632	20 x 15 %	20 x 15 %
Wide Width Tensile Strength	ASTM D-4595	2,760 x 2,700 lbs/ft	40.28 x 39.4 kN/m
CBR Puncture	ASTM D-6241	1,250 lbs	5,563 N
Trapezoidal Tear	ASTM D-4533	145 x 125 lbs	645 x 556 N
Apparent Opening Size ^(1,2)	ASTM D-4751	30 US Sieve	0.595 mm
Permittivity ⁽¹⁾	ASTM D-4491	1.5 Sec ⁻¹	1.5 Sec ⁻¹
Permeability ⁽¹⁾	ASTM D-4491	0.13 cm/sec	0.13 cm/sec
Water Flow Rate ⁽¹⁾	ASTM D-4491	115 g/min/f ²	4,685 L/min/m ²
Percent Open Area	CW-02215	8 %	8 %
UV Resistance @ 500 Hours	ASTM D-4355	90 %	90 %

⁽¹⁾ At the time of manufacturing. Handling, storage, and shipping may change these properties.

⁽²⁾ Maximum average roll value (MaxARV).

US 830 Shipping & Packaging Information

SIZE	DIAMETER	WIDTH	WEIGHT	AREA	ROLLS PER TRAILER
12.5' x 300'	13"	12.5'	220 lbs	417 y ²	150

US Fabrics, Inc. | 3904 Virginia Avenue | Cincinnati, OH 45227
Phone: (800) 518-2290 | Fax: (513) 271-4420 | email: info@usfabrics.com

This information is provided for reference only and is not intended as a warranty or guarantee.
US Fabrics assumes no liability in connection with the use of this information.