



REINFORCING SUCCESS

WINFAB® Type 1 DOT FTB is a Yellow PVC coated polyester fabric floating turbidity barrier. It is designed to control silt, floating vegetation, and other debris in ditches, streams, canals, marshes, ponds, and lakes.

WINFAB® Type 1 DOT FTB can be used in Fresh, Salt, and Brackish water.



PROPERTY	TYPICAL ENGLISH
Fabric Weight	18.0 oz/yd ²
Rope	5/8 in Diameter Poly
Grommets	#4 Brass
Chain Ballast	1/4 in Galvanized
Seams	Heat Sealed
EPS Flotation	6 in
Freshwater Buoyancy	13.5 lbs/ft
Saltwater Buoyancy	14.4 lbs/ft
Height	5 ft (Standard) Custom Available
Length	50 ft (Standard) Custom Available

Disclaimer: WINFAB assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. WINFAB disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The property values listed above are subject to change without notice.

WINFAB® &  WINFAB® are trademarks of Willacoochee Industrial Fabrics, Inc.

©2021 Willacoochee Industrial Fabrics Inc.

WINFAB | www.winfabusa.com
1 Nashville Mills Rd. Nashville GA 31639
Ph: (912) 534-5757 • Fax: (912) 534-5533

