



PRODUCT DATA SHEET

WINFAB® 2050HDX

WINFAB® 2050HDX-USA

patent pending

WINFAB® 2050HDX & WINFAB® 2050HDX-USA is an isotropic, heavy duty, high modulus silt fence fabric manufactured using high tenacity polypropylene yarns that are woven to form a dimensionally stable network capable of providing sediment retention, water filtration, and silt fence structural integrity; even in the most demanding silt fence applications. Additionally, the fabric resists ultraviolet deterioration, rotting, and biological degradation and is inert to commonly encountered soil chemicals.

WINFAB® 2050HDX & WINFAB® 2050HDX-USA is specifically designed and engineered for utilization where “reinforced silt fence” or “super silt fence” systems are specified, but does not require chain link fence or wire backing for reinforcement.

WINFAB® 2050HDX & WINFAB® 2050HDX-USA fabric possesses superior strength at low strains, and even in the most extreme sediment and hydraulic loading conditions, maintains structural silt fence system integrity and filtration efficiencies for desired sediment and erosion control without the need for metal reinforcement.

WINFAB® 2050HDX & WINFAB® 2050HDX-USA fabric enables the next generation reinforced silt fence system(s) to be more economical, easily installed, all the while supporting sustainable sourcing and construction practices by eliminating the need for metal backing when compared to the traditional reinforced silt fence systems.

PROPERTY	TEST METHOD	MARV ENGLISH	MARV METRIC
Wide Width Tensile @ Ultimate	ASTM D4595	5200 x 5200 lbs/ft	75.9 x 75.9 kN/m
Tensile Strength (Grab)	ASTM D4632	550 x 550 lbs	2446 x 2446 N
Elongation (Grab)	ASTM D4632	8% x 8%	8% x 8%
Trapezoidal Tear Strength	ASTM D4533	195 x 170 lbs	867 x 756 N
UV Resistance (500 hrs)	ASTM D4355	90%	90%
CBR Puncture	ASTM D6241	2000 lbs	8896 N
Apparent Opening Size*	ASTM D4751	30 US Std. Sieve	0.60 mm
Permittivity	ASTM D4491	0.73 sec ⁻¹	0.73 sec ⁻¹
Water Flow Rate	ASTM D4491	55 gpm/ft ²	2241 lpm/m ²

*Maximum Average Roll Value

Domestic Procurement Preference

WINFAB® 2050HDX-USA is compliant with the Build America, Buy America (BABA) Act, Pub. L. No. 117-58, div. G §§ 70901-52. To ensure BABA documentation is appropriately captured and maintained throughout the manufacturing process, BABA (along with any other regulatory requirements) must be specified at the time of quotation and order to WINFAB. The inclusion of a “-USA” suffix on the end of the style name indicates the product is BABA certifiable.

PROPERTY	TEST METHOD	TYPICAL ENGLISH	TYPICAL METRIC
Roll Dimensions	Measured	45 in x 900 ft	1.14 m x 274.32 m

Disclaimer: WINFAB assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. WINFAB disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The information listed above are subject to change without notice. Build America, Buy America Act, Pub. L. No. 117-58 certification is conditional for WINFAB 2050HDX, and is not a guarantee. Date Issued: 3.1.2025

WINFAB® &  WINFAB® are trademarks of Willacoochee Industrial Fabrics, Inc.

©2023 Willacoochee Industrial Fabrics Inc.

WINFAB | www.winfabusa.com
1 Nashville Mills Rd. Nashville GA 31639
Ph: (912) 534-5757 • Fax: (912) 534-5533

